

# Namespace NWH.Common

## Classes

### **MathUtility (NWH.Common.MathUtility.html)**

Mathematical utility functions for common calculations.

# Class MathUtility

Mathematical utility functions for common calculations.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ MathUtility

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class MathUtility
```

## Methods

### ClampWithRemainder(ref float, in float, out float)

Clamps a value to a range and outputs how much it exceeded the range. Useful for clamping values while preserving overflow information.

#### Declaration

```
public static void ClampWithRemainder(ref float x, in float range, out float remainder)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>x</i>	Value to clamp (will be modified).
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>range</i>	Range limit (value will be clamped to [-range, +range]).
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>remainder</i>	Amount by which x exceeded the range (output).

# Namespace NWH.Common.AssetInfo

## Classes

### **AssetInfo (NWH.Common.AssetInfo.AssetInfo.html)**

ScriptableObject containing metadata and URLs for an NWH asset. Used by the welcome window and asset information systems.

# Class AssetInfo

ScriptableObject containing metadata and URLs for an NWH asset. Used by the welcome window and asset information systems.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [ScriptableObject](https://docs.unity3d.com/ScriptReference/ScriptableObject.html) (<https://docs.unity3d.com/ScriptReference/ScriptableObject.html>).
- ↳ AssetInfo

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [AssetInfo](#) ([NWH.Common.AssetInfo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[CreateAssetMenu(fileName = "AssetInfo", menuName = "NWH/AssetInfo", order = 0)]  
public class AssetInfo : ScriptableObject
```

## Fields

### assetName

Display name of the asset.

#### Declaration

```
public string assetName
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	

### assetURL

Unity Asset Store URL for this asset.

#### Declaration

```
public string assetURL
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a>	

## changelogURL

URL to the changelog documentation page.

### Declaration

```
public string changelogURL
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a>	

## discordURL

Discord server invite link for support and community.

### Declaration

```
public string discordURL
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a>	

## documentationURL

URL to the main documentation page.

### Declaration

```
public string documentationURL
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a>	

## emailURL

Support email contact link.

### Declaration

```
public string emailURL
```

### Field Value

Type	Description
<u><a href="https://learn.microsoft.com/dotnet/api/system.string">string</a></u> ( <u><a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a></u> ).	

## forumURL

Unity Forum thread URL for this asset.

### Declaration

```
public string forumURL
```

### Field Value

Type	Description
<u><a href="https://learn.microsoft.com/dotnet/api/system.string">string</a></u> ( <u><a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a></u> ).	

## publisherURL

NWH publisher page URL on Unity Asset Store.

### Declaration

```
public string publisherURL
```

### Field Value

Type	Description
<u><a href="https://learn.microsoft.com/dotnet/api/system.string">string</a></u> ( <u><a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a></u> ).	

## quickStartURL

URL to quick start guide documentation.

### Declaration

```
public string quickStartURL
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a> .	

## recentUpdates

Recent updates/changes in the current version (3-5 bullet points).

### Declaration

```
[TextArea(3, 10)]  
public string[] recentUpdates
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a> []	

## upgradeNotesURL

URL to upgrade notes between versions.

### Declaration

```
public string upgradeNotesURL
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a> .	

## version

Current version string of the asset.

### Declaration

```
public string version
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string_(https://learn.microsoft.com/dotnet/api/system.string)</a> .	



# Namespace NWH.Common.Cameras

## Classes

### **CameraChanger (NWH.Common.Cameras.CameraChanger.html)**

Switches between the camera objects that are children to this object and contain camera tag, in order they appear in the hierarchy or in order they are added to the vehicle cameras list.

### **CameraInsideVehicle (NWH.Common.Cameras.CameraInsideVehicle.html)**

Empty component that should be attached to the cameras that are inside the vehicle if interior sound change is to be used.

### **CameraMouseDrag (NWH.Common.Cameras.CameraMouseDrag.html)**

Camera that can be dragged with the mouse.

### **VehicleCamera (NWH.Common.Cameras.VehicleCamera.html)**

Base class for vehicle camera implementations with automatic target detection.

## Enums

### **CameraMouseDrag.POVType (NWH.Common.Cameras.CameraMouseDrag.POVType.html)**

# Class CameraChanger

Switches between the camera objects that are children to this object and contain camera tag, in order they appear in the hierarchy or in order they are added to the vehicle cameras list.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ CameraChanger

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Cameras](#) ([NWH.Common.Cameras.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[DefaultExecutionOrder(20)]  
public class CameraChanger : MonoBehaviour
```

## Fields

### autoFindCameras

If true vehicleCameras list will be filled through cameraTag.

#### Declaration

```
[Tooltip(" If true vehicleCameras list will be filled through cameraTag.")]  
public bool autoFindCameras
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### cameras

List of cameras that the changer will cycle through. Leave empty if you want cameras to be automatically detected. To be detected cameras need to have camera tag and be children of the object this script is attached to.

## Declaration

```
[FormerlySerializedAs("vehicleCameras")]  
[Tooltip("List of cameras that the changer will cycle through. Leave empty if you want cameras to be automatically detected. To be detected cameras need to have camera tag and be children of the object this script is attached to.")]  
public List<GameObject> cameras
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> (< <a href="https://docs.unity3d.com/ScriptReference/GameObject.html">GameObject</a> >)	

## currentCameraIndex

Index of the camera from vehicle cameras list that will be active first.

## Declaration

```
[Tooltip("Index of the camera from vehicle cameras list that will be active first.")]  
public int currentCameraIndex
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a>	

## Methods

### NextCamera()

Activates the next camera in the list, cycling back to the first camera when reaching the end. Automatically disables all other cameras and their AudioListeners.

## Declaration

```
public void NextCamera()
```

### PreviousCamera()

Activates the previous camera in the list, cycling back to the last camera when reaching the beginning. Automatically disables all other cameras and their AudioListeners.

## Declaration

```
public void PreviousCamera()
```

# Class CameraInsideVehicle

Empty component that should be attached to the cameras that are inside the vehicle if interior sound change is to be used.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ CameraInsideVehicle

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Cameras](#) ([NWH.Common.Cameras.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class CameraInsideVehicle : MonoBehaviour
```

## Fields

### isInsideVehicle

Is the camera inside vehicle?

#### Declaration

```
[Tooltip(" Is the camera inside vehicle?")]  
public bool isInsideVehicle
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Class CameraMouseDrag

Camera that can be dragged with the mouse.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [VehicleCamera](NWH.Common.Cameras.VehicleCamera.html) (<NWH.Common.Cameras.VehicleCamera.html>).
- ↳ CameraMouseDrag

## Inherited Members

---

[VehicleCamera.target](NWH.Common.Cameras.VehicleCamera.html#NWH_Common_Cameras_VehicleCamera_target)

([NWH.Common.Cameras.VehicleCamera.html#NWH\\_Common\\_Cameras\\_VehicleCamera\\_target](NWH.Common.Cameras.VehicleCamera.html#NWH_Common_Cameras_VehicleCamera_target))

[VehicleCamera.Awake\(\)](NWH.Common.Cameras.VehicleCamera.html#NWH_Common_Cameras_VehicleCamera_Awake)

([NWH.Common.Cameras.VehicleCamera.html#NWH\\_Common\\_Cameras\\_VehicleCamera\\_Awake](NWH.Common.Cameras.VehicleCamera.html#NWH_Common_Cameras_VehicleCamera_Awake))

**Namespace:** [NWH](NWH.html) (<NWH.html>), [Common](NWH.Common.html) (<NWH.Common.html>), [Cameras](NWH.Common.Cameras.html) (<NWH.Common.Cameras.html>).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class CameraMouseDrag : VehicleCamera
```

## Fields

### allowPanning

Can the camera be panned by the user?

#### Declaration

```
[Tooltip(" Can the camera be panned by the user?")]  
public bool allowPanning
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### allowRotation

Can the camera be rotated by the user?

## Declaration

```
[Tooltip("    Can the camera be rotated by the user?")]  
public bool allowRotation
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## distance

Distance from target at which camera will be positioned. Might vary depending on smoothing.

## Declaration

```
[Range(0, 100)]  
[Tooltip("    Distance from target at which camera will be positioned. Might vary depending  
on smoothing.")]  
public float distance
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## followTargetPitchAndYaw

If true the camera will rotate with the vehicle along the X and Y axis.

## Declaration

```
[FormerlySerializedAs("followTargetsRotation")]  
[Tooltip("    If true the camera will rotate with the vehicle along the X and Y axis.")]  
public bool followTargetPitchAndYaw
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## followTargetRoll

If true the camera will rotate with the vehicle along the Z axis.

## Declaration

```
[Tooltip(" If true the camera will rotate with the vehicle along the Z axis.")]  
public bool followTargetRoll
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## initXRotation

Initial rotation around the X axis (up/down)

## Declaration

```
[Tooltip(" Initial rotation around the X axis (up/down)")]  
public float initXRotation
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## initYRotation

Initial rotation around the Y axis (left/right)

## Declaration

```
[Tooltip(" Initial rotation around the Y axis (left/right)")]  
public float initYRotation
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## maxDistance

Maximum distance that will be reached when zooming out.

## Declaration

```
[Range(0, 100)]  
[Tooltip("    Maximum distance that will be reached when zooming out.")]  
public float maxDistance
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## minDistance

Minimum distance that will be reached when zooming in.

## Declaration

```
[Range(0, 100)]  
[Tooltip("    Minimum distance that will be reached when zooming in.")]  
public float minDistance
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## panningSensitivity

Sensitivity of panning input.

## Declaration

```
[Tooltip("    Sensitivity of panning input.")]  
public Vector2 panningSensitivity
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	

## povType

Camera POV type. First person camera will invert controls. Zoom is not available in 1st person.

## Declaration

```
[Tooltip("Camera POV type. First person camera will invert controls.\r\nZoom is not available in 1st person.")]
public CameraMouseDrag.POVType povType
```

## Field Value

Type	Description
<a href="#">CameraMouseDrag (NWH.Common.Cameras.CameraMouseDrag.html)</a> . <a href="#">POVType (NWH.Common.Cameras.CameraMouseDrag.POVType.html)</a>	

## rotationSensitivity

Sensitivity of rotation input.

## Declaration

```
[Tooltip(" Sensitivity of rotation input.")]
public Vector2 rotationSensitivity
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	

## rotationSmoothing

Smoothing of the camera rotation.

## Declaration

```
[Range(0, 1)]
[Tooltip(" Smoothing of the camera rotation.")]
public float rotationSmoothing
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## shakeAxisIntensity

Movement intensity per axis. Set to 0 to disable movement on that axis or negative to reverse it.

## Declaration

```
[Tooltip(" Movement intensity per axis. Set to 0 to disable movement on that axis or negative to reverse it.")]  
public Vector3 shakeAxisIntensity
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## shakeIntensity

How much will the head move around for the given g-force.

## Declaration

```
[Range(0, 1)]  
[Tooltip(" How much will the head move around for the given g-force.")]  
public float shakeIntensity
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## shakeMaxOffset

Maximum head movement from the initial position.

## Declaration

```
[Range(0, 1)]  
[Tooltip(" Maximum head movement from the initial position.")]  
public float shakeMaxOffset
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## shakeSmoothing

Smoothing of the head movement.

## Declaration

```
[Range(0, 1)]  
[Tooltip(" Smoothing of the head movement.")]  
public float shakeSmoothing
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## targetPositionOffset

Look position offset from the target center.

## Declaration

```
[Tooltip(" Look position offset from the target center.")]  
public Vector3 targetPositionOffset
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## useShake

Should camera movement on acceleration be used?

## Declaration

```
[Tooltip("Should camera movement on acceleration be used?")]  
public bool useShake
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## verticalMaxAngle

Maximum vertical angle the camera can achieve.

## Declaration

```
[Range(-90, 90)]  
[Tooltip("    Maximum vertical angle the camera can achieve.")]  
public float verticalMaxAngle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## verticalMinAngle

Minimum vertical angle the camera can achieve.

## Declaration

```
[Range(-90, 90)]  
[Tooltip("    Minimum vertical angle the camera can achieve.")]  
public float verticalMinAngle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## zoomSensitivity

Sensitivity of the middle mouse button / wheel.

## Declaration

```
[Range(0, 15)]  
[Tooltip("    Sensitivity of the middle mouse button / wheel.")]  
public float zoomSensitivity
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## Methods

### ClampAngle(float, float, float)

## Declaration

```
public float ClampAngle(float angle, float min, float max)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>angle</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>min</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>max</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## OnDrawGizmosSelected()

### Declaration

```
public void OnDrawGizmosSelected()
```

# Enum CameraMouseDrag.POVType

Namespace: [NWH \(NWH.html\)](#), [Common \(NWH.Common.html\)](#), [Cameras \(NWH.Common.Cameras.html\)](#)

Assembly: NWH.DWP2.dll

## Syntax

```
public enum CameraMouseDrag.POVType
```

## Fields

Name	Description
FirstPerson	First-person camera view from inside the vehicle.
ThirdPerson	Third-person camera view from outside the vehicle.

# Class VehicleCamera

Base class for vehicle camera implementations with automatic target detection.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ VehicleCamera
  - ↳ [CameraMouseDrag](#) ([NWH.Common.Cameras.CameraMouseDrag.html](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Cameras](#) ([NWH.Common.Cameras.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class VehicleCamera : MonoBehaviour
```

## Fields

### target

Transform to track. Auto-detects parent Rigidbody if not assigned.

### Declaration

```
[Tooltip("Transform that this script is targeting. Can be left empty if head movement is not being used.")]  
public Transform target
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## Methods

### Awake()

## Declaration

```
public virtual void Awake()
```

## See Also

[CameraChanger \(NWH.Common.Cameras.CameraChanger.html\)](#),

[CameraInsideVehicle \(NWH.Common.Cameras.CameraInsideVehicle.html\)](#),

[CameraMouseDrag \(NWH.Common.Cameras.CameraMouseDrag.html\)](#).

# Namespace NWH.Common.CoM

## Classes

### **MassAffector (NWH.Common.CoM.MassAffector.html)**

Simple mass affector implementation that contributes a fixed mass at its transform position to the vehicle's center of mass calculations.

### **VariableCenterOfMass (NWH.Common.CoM.VariableCenterOfMass.html)**

Dynamic center of mass and inertia calculation system that updates RigidBody properties based on attached mass affectors like fuel tanks, cargo loads, and passengers.

## Interfaces

### **IMassAffector (NWH.Common.CoM.IMassAffector.html)**

Interface for objects that contribute mass and affect vehicle center of mass calculations. Implemented by fuel tanks, cargo systems, and other variable mass components.

# Interface IMassAffector

Interface for objects that contribute mass and affect vehicle center of mass calculations. Implemented by fuel tanks, cargo systems, and other variable mass components.

**Namespace:** [NWH \(NWH.html\)](#), [Common \(NWH.Common.html\)](#), [CoM \(NWH.Common.CoM.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public interface IMassAffector
```

## Remarks

Mass affectors allow dynamic vehicle physics by contributing their mass and position to the overall center of mass calculation. As fuel depletes or cargo loads change, the vehicle's handling characteristics update automatically.

## Methods

### GetMass()

Current mass of this affector in kilograms. Should return variable values for fuel tanks, cargo, etc.

#### Declaration

```
float GetMass()
```

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Mass in kg

### GetTransform()

Returns transform of the mass affector.

#### Declaration

```
Transform GetTransform()
```

#### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## GetWorldCenterOfMass()

World position of this affector's center of mass. Used for weighted center of mass calculations.

### Declaration

```
Vector3 GetWorldCenterOfMass()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

# Class MassAffector

Simple mass affector implementation that contributes a fixed mass at its transform position to the vehicle's center of mass calculations.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ MassAffector

## Implements

[IMassAffector](#) ([NWH.Common.CoM.IMassAffector.html](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [CoM](#) ([NWH.Common.CoM.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class MassAffector : MonoBehaviour, IMassAffector
```

## Remarks

Use this component for static mass contributions like passengers, cargo, or equipment. For dynamic masses like fuel tanks, create a custom IMassAffector implementation that returns varying mass values.

## Fields

### mass

Mass contribution of this affector in kilograms.

### Declaration

```
public float mass
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Methods

## GetMass()

Returns the mass of this affector.

### Declaration

```
public float GetMass()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Mass in kilograms.

## GetTransform()

Returns the transform of this mass affector.

### Declaration

```
public Transform GetTransform()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## GetWorldCenterOfMass()

Returns the world position of this mass affector's center of mass.

### Declaration

```
public Vector3 GetWorldCenterOfMass()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## Implements

[IMassAffector](#) ([NWH.Common.CoM.IMassAffector.html](#)).

# Class VariableCenterOfMass

Dynamic center of mass and inertia calculation system that updates Rigidbody properties based on attached mass affectors like fuel tanks, cargo loads, and passengers.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ VariableCenterOfMass

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [CoM](#) ([NWH.Common.CoM.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[DisallowMultipleComponent]
[DefaultExecutionOrder(-1000)]
[RequireComponent(typeof(Rigidbody))]
public class VariableCenterOfMass : MonoBehaviour
```

## Remarks

VariableCenterOfMass enables realistic vehicle physics behavior by automatically adjusting center of mass and inertia tensor as vehicle loading changes. This affects handling characteristics, stability, and acceleration response without requiring complex rigidbody hierarchies.

The system calculates total mass, weighted center of mass position, and inertia contributions from all IMassAffector components. Changes in fuel level, cargo loading, or passenger weight immediately affect vehicle dynamics, creating realistic weight distribution effects.

Critical for vehicle realism: Front-heavy vehicles understeer more, rear-heavy vehicles may oversteer, and high center of mass increases rollover tendency. The system updates these characteristics dynamically based on actual mass distribution.

## Fields

### affectors

Objects attached or part of the vehicle affecting its center of mass and inertia.

### Declaration

```
[NonSerialized]
public IMassAffector[] affectors
```

## Field Value

Type	Description
<a href="#">IMassAffector (NWH.Common.CoM.IMassAffector.html)</a> []	

## baseMass

Base mass of the object, without IMassAffectors.

### Declaration

```
[Tooltip("Base mass of the object, without IMassAffectors.")]  
public float baseMass
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## centerOfMass

Center of mass of the object. Auto calculated. To adjust center of mass use centerOfMassOffset.

### Declaration

```
[Tooltip("Center of mass of the rigidbody. Needs to be readjusted when new colliders are added.")]  
public Vector3 centerOfMass
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## combinedCenterOfMass

Combined center of mass, including the Rigidbody and any IMassAffectors.

### Declaration

```
public Vector3 combinedCenterOfMass
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## combinedInertiaTensor

Total inertia tensor. Includes Rigidbody and IMassEffectors.

### Declaration

```
public Vector3 combinedInertiaTensor
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## combinedMass

Total mass of the object with masses of IMassEffectors counted in.

### Declaration

```
[Tooltip("Total mass of the object with masses of IMassEffectors counted in.")]  
public float combinedMass
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## dimensions

Object dimensions in [m]. X - width, Y - height, Z - length. It is important to set the correct dimensions or otherwise inertia might be calculated incorrectly.

### Declaration

```
[Tooltip("Object dimensions in [m]. X - width, Y - height, Z - length.\r\nIt is important to  
set the correct dimensions or otherwise inertia might be calculated incorrectly.")]  
public Vector3 dimensions
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## inertiaTensor

Vector by which the inertia tensor of the rigidbody will be scaled on Start(). Due to the uniform density of the rigidbodies, versus the very non-uniform density of a vehicle, inertia can feel off. Use this to adjust inertia tensor values.

## Declaration

```
[Tooltip("    Vector by which the inertia tensor of the rigidbody will be scaled on Start
().\r\n    Due to the unform density of the rigidbodies, versus the very non-uniform density
of a vehicle, inertia can feel\r\n    off.\r\n    Use this to adjust inertia tensor value
s.")]
public Vector3 inertiaTensor
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## isDirty

When true, properties will be recalculated in the next FixedUpdate. Call MarkDirty() when mass affectors change to trigger update.

## Declaration

```
[Tooltip("When true, properties will be recalculated in the next FixedUpdate. Automatically
managed.")]
public bool isDirty
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	

## useDefaultCenterOfMass

When enabled the Unity-calculated center of mass will be used.

## Declaration

```
[Tooltip("When enabled the Unity-calculated center of mass will be used.")]
public bool useDefaultCenterOfMass
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	

## useDefaultInertia

When true inertia settings will be ignored and default Rigidbody inertia tensor will be used.

## Declaration

```
[Tooltip("When true inertia settings will be ignored and default RigidBody inertia tensor will be used.")]  
public bool useDefaultInertia
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## useDefaultMass

Should the default RigidBody mass be used?

## Declaration

```
public bool useDefaultMass
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## useMassAffectors

If true, the script will search for any IMassAffectors attached as a child (recursively) of this script and use them when calculating mass, center of mass and inertia tensor.

## Declaration

```
public bool useMassAffectors
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Methods

### CalculateInertia(Vector3, float)

Calculates inertia tensor for a cuboid with given dimensions and mass. Uses parallel axis theorem for rectangular prism approximation.

## Declaration

```
public static Vector3 CalculateInertia(Vector3 dimensions, float mass)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>dimensions</i>	Object dimensions in meters (width, height, length)
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>mass</i>	Total mass in kilograms

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Inertia tensor components (Ix, Iy, Iz) in kg·m <sup>2</sup>

## CalculateInertiaTensorOffset(Vector3)

Calculates the inertia tensor of the Rigidbody and attached mass affectors.

## Declaration

```
public Vector3 CalculateInertiaTensorOffset(Vector3 dimensions)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>dimensions</i>	

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## CalculateMass()

Calculates the mass of the Rigidbody and attached mass affectors.

## Declaration

```
public float CalculateMass()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## CalculateRelativeCenterOfMassOffset()

Calculates the center of mass of the Rigidbody and attached mass affectors.

### Declaration

```
public Vector3 CalculateRelativeCenterOfMassOffset()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## GetMassAffectors()

Updates list of IMassAffectors attached to this object. Call after IMassAffector has been added or removed from the object.

### Declaration

```
public IMassAffector[] GetMassAffectors()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/IMassAffector.html">IMassAffector</a> ( <a href="https://docs.unity3d.com/ScriptReference/IMassAffector.html">NWH.Common.CoM.IMassAffector.html</a> ),[]	

## GetWorldCenterOfMass()

Gets the combined center of mass position in world space coordinates.

### Declaration

```
public Vector3 GetWorldCenterOfMass()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	World space position of the center of mass

## MarkDirty()

Mark properties as needing recalculation. Call this when mass affectors change (fuel consumption, cargo loading, etc.).

### Declaration

```
public void MarkDirty()
```

## UpdateAllProperties()

Recalculates all Rigidbody properties (mass, center of mass, and inertia) based on current settings and affectors. Called automatically when isDirty flag is set.

### Declaration

```
public void UpdateAllProperties()
```

## UpdateCoM()

Calculates and applies the CoM to the Rigidbody.

### Declaration

```
public void UpdateCoM()
```

## UpdateInertia(bool)

Calculates and applies the inertia tensor to the Rigidbody.

### Declaration

```
public void UpdateInertia(bool applyUnchanged = false)
```

### Parameters

Type	Name	Description
<code>bool</code> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>applyUnchanged</i>	

## UpdateMass()

Calculates and applies the total mass to the Rigidbody. Includes mass from affectors if useMassAffectors is enabled.

## Declaration

```
public void UpdateMass()
```

## See Also

[IMassAffector \(NWH.Common.CoM.IMassAffector.html\)](#)

[MassAffector \(NWH.Common.CoM.MassAffector.html\)](#)

[Vehicle \(NWH.Common.Vehicles.Vehicle.html\)](#)

# Namespace NWH.Common.Demo

## Classes

### **DemoCameraNameDisplay (NWH.Common.Demo.DemoCameraNameDisplay.html)**

Displays the name of the currently active main camera in a Text component. Updates every 0.1 seconds.

### **DemoDtSetter (NWH.Common.Demo.DemoDtSetter.html)**

Sets Time.fixedDeltaTime to a specific value for demo scenes. Default is 0.008333s (120Hz) for optimal physics performance.

### **DemoOscillator (NWH.Common.Demo.DemoOscillator.html)**

Moves a Rigidbody in a sinusoidal oscillation pattern. Useful for creating moving platforms or obstacles in demo scenes.

### **DemoRotator (NWH.Common.Demo.DemoRotator.html)**

Continuously rotates a Rigidbody at a constant rate. Useful for rotating platforms or visual elements in demo scenes.

### **DemoVehicleNameDisplay (NWH.Common.Demo.DemoVehicleNameDisplay.html)**

Displays the name and type of the currently active vehicle in a Text component. Updates every 0.1 seconds.

### **DemoWelcomeMessage (NWH.Common.Demo.DemoWelcomeMessage.html)**

Controls the display of a welcome message panel in demo scenes. Shows the message when running outside the editor.

### **DragObject (NWH.Common.Demo.DragObject.html)**

Simple script that drags Rigidbody behind the mouse cursor when MMB is held down.

### **FpsToText (NWH.Common.Demo.FpsToText.html)**

Displays the current framerate in a Text component with optional color coding. Supports both instantaneous and averaged FPS measurements.

### **RigidbodyFPSController (NWH.Common.Demo.RigidbodyFPSController.html)**

Simple first-person controller using physics-based movement. Useful for testing and navigating demo scenes on foot.



# Class DemoCameraNameDisplay

Displays the name of the currently active main camera in a Text component. Updates every 0.1 seconds.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DemoCameraNameDisplay

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(Text))]  
public class DemoCameraNameDisplay : MonoBehaviour
```

# Class DemoDtSetter

Sets `Time.fixedDeltaTime` to a specific value for demo scenes. Default is 0.008333s (120Hz) for optimal physics performance.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DemoDtSetter

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[DefaultExecutionOrder(-500)]  
public class DemoDtSetter : MonoBehaviour
```

## Fields

### fixedDeltaTime

Target physics update rate in seconds. Default 0.008333s equals 120Hz.

#### Declaration

```
public float fixedDeltaTime
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Class DemoOscillator

Moves a Rigidbody in a sinusoidal oscillation pattern. Useful for creating moving platforms or obstacles in demo scenes.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DemoOscillator

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DemoOscillator : MonoBehaviour
```

## Fields

### speed

Speed of the oscillation in Hz. Higher values result in faster movement.

#### Declaration

```
public float speed
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### travel

Maximum displacement from the starting position in each axis.

#### Declaration

```
public Vector3 travel
```

## Field Value

Type	Description
<u>Vector3</u> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

# Class DemoRotator

Continuously rotates a Rigidbody at a constant rate. Useful for rotating platforms or visual elements in demo scenes.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DemoRotator

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DemoRotator : MonoBehaviour
```

## Fields

### rotation

Rotation speed in degrees per second for each axis.

### Declaration

```
public Vector3 rotation
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

# Class DemoVehicleNameDisplay

Displays the name and type of the currently active vehicle in a Text component. Updates every 0.1 seconds.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DemoVehicleNameDisplay

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(Text))]  
public class DemoVehicleNameDisplay : MonoBehaviour
```

# Class DemoWelcomeMessage

Controls the display of a welcome message panel in demo scenes. Shows the message when running outside the editor.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DemoWelcomeMessage

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DemoWelcomeMessage : MonoBehaviour
```

## Fields

### closeButton

Button used to close the welcome message panel.

#### Declaration

```
public Button closeButton
```

#### Field Value

Type	Description
Button	

### welcomeMessageGO

GameObject containing the welcome message UI.

#### Declaration

```
public GameObject welcomeMessageGO
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/GameObject.html">GameObject</a> ( <a href="https://docs.unity3d.com/ScriptReference/GameObject.html">https://docs.unity3d.com/ScriptReference/GameObject.html</a> ).	

# Class DragObject

Simple script that drags Rigidbody behind the mouse cursor when MMB is held down.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ DragObject

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DragObject : MonoBehaviour
```

# Class FpsToText

Displays the current framerate in a Text component with optional color coding. Supports both instantaneous and averaged FPS measurements.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ FpsToText

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(Text))]  
public class FpsToText : MonoBehaviour
```

## Fields

### bad

Text color when framerate is below badBelow threshold.

#### Declaration

```
public Color bad
```

#### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Color.html">Color</a> ( <a href="https://docs.unity3d.com/ScriptReference/Color.html">https://docs.unity3d.com/ScriptReference/Color.html</a> ).	

### badBelow

FPS threshold below which the color changes to bad (red).

#### Declaration

```
public int badBelow
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## forceIntResult

Round FPS to nearest integer for cleaner display.

### Declaration

```
public bool forceIntResult
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## good

Text color when framerate is above okayBelow threshold.

### Declaration

```
public Color good
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Color.html">Color</a> ( <a href="https://docs.unity3d.com/ScriptReference/Color.html">https://docs.unity3d.com/ScriptReference/Color.html</a> ).	

## groupSampling

Use averaging over multiple samples instead of single frame measurement.

### Declaration

```
public bool groupSampling
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## okay

Text color when framerate is between badBelow and okayBelow.

### Declaration

```
public Color okay
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Color.html">Color</a> ( <a href="https://docs.unity3d.com/ScriptReference/Color.html">https://docs.unity3d.com/ScriptReference/Color.html</a> ).	

## okayBelow

FPS threshold below which the color changes to okay (yellow).

### Declaration

```
public int okayBelow
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## sampleSize

Number of samples to average when groupSampling is enabled.

### Declaration

```
public int sampleSize
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## smoothed

Use Time.smoothDeltaTime instead of Time.deltaTime for calculations.

### Declaration

```
public bool smoothed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## updateTextEvery

Update text display every N frames. 1 = every frame.

### Declaration

```
public int updateTextEvery
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## useColors

Enable color coding based on framerate thresholds.

### Declaration

```
public bool useColors
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## useSystemTick

Use Environment.TickCount instead of Time.deltaTime for calculations.

### Declaration

```
public bool useSystemTick
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Methods

## GetSystemFramerate()

### Declaration

```
protected virtual int GetSystemFramerate()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## Group()

### Declaration

```
protected virtual void Group()
```

## Reset()

### Declaration

```
protected virtual void Reset()
```

## SingleFrame()

### Declaration

```
protected virtual void SingleFrame()
```

## Start()

### Declaration

```
protected virtual void Start()
```

## Update()

### Declaration

```
protected virtual void Update()
```



# Class RigidbodyFPSController

Simple first-person controller using physics-based movement. Useful for testing and navigating demo scenes on foot.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ RigidbodyFPSController

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Demo](#) ([NWH.Common.Demo.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(Rigidbody))]  
[RequireComponent(typeof(CapsuleCollider))]  
public class RigidbodyFPSController : MonoBehaviour
```

## Remarks

Based on Unity Community Wiki example. Uses Rigidbody for physics-accurate movement with mouse-look camera control.

## Fields

### gravity

Downward acceleration force in  $m/s^2$ .

### Declaration

```
public float gravity
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### jumpHeight

Maximum height of jumps in meters.

## Declaration

```
public float jumpHeight
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## maxVelocityChange

Maximum velocity change per fixed update, controls acceleration responsiveness.

## Declaration

```
public float maxVelocityChange
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## maximumY

Maximum upward look angle in degrees.

## Declaration

```
public float maximumY
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## minimumY

Maximum downward look angle in degrees.

## Declaration

```
public float minimumY
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## sensitivityX

Horizontal mouse look sensitivity.

### Declaration

```
public float sensitivityX
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## sensitivityY

Vertical mouse look sensitivity.

### Declaration

```
public float sensitivityY
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## speed

Movement speed in meters per second.

### Declaration

```
public float speed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	



# Namespace NWH.Common.Input

## Classes

### **InputManagerSceneInputProvider** **(NWH.Common.Input.InputManagerSceneInputProvider.html)**

Scene input provider using Unity's legacy Input Manager system. Requires input axes and buttons to be configured in Project Settings > Input Manager.

### **InputProvider** **(NWH.Common.Input.InputProvider.html)**

Base class from which all input providers inherit.

### **InputSystemSceneInputProvider** **(NWH.Common.Input.InputSystemSceneInputProvider.html)**

Unity Input System implementation of scene input provider. Handles camera controls and scene navigation using the new Input System.

### **InputUtils** **(NWH.Common.Input.InputUtils.html)**

Utility methods for safe input retrieval with automatic fallback to default keys. Prevents errors when Input Manager bindings are missing.

### **MobileInputButton** **(NWH.Common.Input.MobileInputButton.html)**

Extended Unity UI Button with state tracking for mobile input handling. Provides hasBeenClicked and isPressed flags for easier input polling.

### **MobileSceneInputProvider** **(NWH.Common.Input.MobileSceneInputProvider.html)**

Scene input provider for mobile platforms using on-screen UI buttons. Requires MobileInputButton components assigned to changeCameraButton and changeVehicleButton fields.

### **SceneInputActions** **(NWH.Common.Input.SceneInputActions.html)**

Provides programmatic access to UnityEngine.InputSystem.InputActionAsset, UnityEngine.InputSystem.InputActionMap, UnityEngine.InputSystem.InputAction and UnityEngine.InputSystem.InputControlScheme instances defined in asset "Packages/com.nwh.common/Runtime/Input/InputSystem/SceneInputActions.inputactions".

### **SceneInputProviderBase** **(NWH.Common.Input.SceneInputProviderBase.html)**

InputProvider for scene and camera related behavior.

# Structs

## **SceneInputActions.CameraControlsActions** **(NWH.Common.Input.SceneInputActions.CameraControlsActions.html)**

Provides access to input actions defined in input action map "CameraControls".

## **SceneInputActions.SceneControlsActions** **(NWH.Common.Input.SceneInputActions.SceneControlsActions.html)**

Provides access to input actions defined in input action map "SceneControls".

# Interfaces

## **SceneInputActions.ICameraControlsActions** **(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html)**

Interface to implement callback methods for all input action callbacks associated with input actions defined by "CameraControls" which allows adding and removing callbacks.

## **SceneInputActions.ISceneControlsActions** **(NWH.Common.Input.SceneInputActions.ISceneControlsActions.html)**

Interface to implement callback methods for all input action callbacks associated with input actions defined by "SceneControls" which allows adding and removing callbacks.

# Class InputManagerSceneInputProvider

Scene input provider using Unity's legacy Input Manager system. Requires input axes and buttons to be configured in Project Settings > Input Manager.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [SceneInputProviderBase](#) ([NWH.Common.Input.SceneInputProviderBase.html](#)).
- ↳ InputManagerSceneInputProvider

## Inherited Members

[SceneInputProviderBase.requireCameraPanningModifier](#)  
([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase requireCameraPanningModifier](#)).

[SceneInputProviderBase.requireCameraRotationModifier](#)  
([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase requireCameraRotationModifier](#)).

[InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Instances](#)).

[InputProvider.Awake\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Awake](#)).

[InputProvider.OnDestroy\(\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider OnDestroy](#)).

[InputProvider.CombinedInput<T>\(Func<T, int>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32](#)).

[InputProvider.CombinedInput<T>\(Func<T, float>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single](#)).

[InputProvider.CombinedInput<T>\(Func<T, bool>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean](#)).

[InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class InputManagerSceneInputProvider : SceneInputProviderBase
```

## Methods

## CameraPanning()

Returns camera panning input as a Vector2 (x = horizontal, y = vertical).

### Declaration

```
public override Vector2 CameraPanning()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

### Overrides

[SceneInputProviderBase.CameraPanning\(\)](#).

([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase CameraPanning\(\)](#)).

## CameraPanningModifier()

Returns true when the camera panning modifier button is held. If requireCameraPanningModifier is false, always returns true.

### Declaration

```
public override bool CameraPanningModifier()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### Overrides

[SceneInputProviderBase.CameraPanningModifier\(\)](#).

([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase CameraPanningModifier\(\)](#)).

## CameraRotation()

Returns camera rotation input as a Vector2 (x = horizontal, y = vertical).

### Declaration

```
public override Vector2 CameraRotation()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## Overrides

[ScenInputProviderBase.CameraRotation\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraRotation](#)).

## CameraRotationModifier()

Returns true when the camera rotation modifier button is held. If requireCameraRotationModifier is false, always returns true.

### Declaration

```
public override bool CameraRotationModifier()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.CameraRotationModifier\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraRotationModifier](#)).

## CameraZoom()

Returns camera zoom input value. Positive = zoom in, negative = zoom out.

### Declaration

```
public override float CameraZoom()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Overrides

[ScenInputProviderBase.CameraZoom\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraZoom](#)).

## ChangeCamera()

Returns true when the change camera button is pressed.

### Declaration

```
public override bool ChangeCamera()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.ChangeCamera\(\)](#).

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase ChangeCamera](#)).

## ChangeVehicle()

Returns true when the change vehicle button is pressed.

## Declaration

```
public override bool ChangeVehicle()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.ChangeVehicle\(\)](#).

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase ChangeVehicle](#)).

## CharacterMovement()

Returns character movement input as a Vector2 (x = horizontal, y = forward/back).

## Declaration

```
public override Vector2 CharacterMovement()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## Overrides

[ScenInputProviderBase.CharacterMovement\(\)](#).

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CharacterMovement](#)).

## ToggleGUI()

Returns true when the toggle GUI button is pressed.

## Declaration

```
public override bool ToggleGUI()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[SceneInputProviderBase.ToggleGUI\(\)](#).

([NWH.Common.Input.SceneInputProviderBase.html#NWH\\_Common\\_Input\\_SceneInputProviderBase\\_ToggleGUI](#)).

# Class InputProvider

Base class from which all input providers inherit.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ InputProvider
  - ↳ [SceneInputProviderBase](#) ([NWH.Common.Input.SceneInputProviderBase.html](#)).
  - ↳ [ShipInputProvider](#) ([NWH.DWP2.ShipController.ShipInputProvider.html](#)).

Namespace: [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#))

Assembly: NWH.DWP2.dll

## Syntax

```
public abstract class InputProvider : MonoBehaviour
```

## Fields

## Instances

List of all InputProviders in the scene.

## Declaration

```
public static List<InputProvider> Instances
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> ), <a href="#">InputProvider</a> ( <a href="#">NWH.Common.Input.InputProvider.html</a> ), < <a href="#">InputProvider</a> ( <a href="#">NWH.Common.Input.InputProvider.html</a> )>	

## Methods

### Awake()

## Declaration

```
public virtual void Awake()
```

## CombinedInput<T>(Func<T, bool>)

Returns combined input of all InputProviders present in the scene. Result will be positive if any InputProvider has the selected input set to true. T is a type of InputProvider that the input will be retrieved from.

## Declaration

```
public static bool CombinedInput<T>(Func<T, bool> selector) where T : InputProvider
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.func-2">Func</a> (<T, bool> selector), <a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a>	<i>selector</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a>	

## Type Parameters

Name	Description
<i>T</i>	

## CombinedInput<T>(Func<T, int>)

Returns combined input of all InputProviders present in the scene. Result will be a sum of all inputs of the selected type. T is a type of InputProvider that the input will be retrieved from.

## Declaration

```
public static int CombinedInput<T>(Func<T, int> selector) where T : InputProvider
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.func-2">Func</a> (<T, int> selector), <a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a>	<i>selector</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## Type Parameters

Name	Description
<i>T</i>	

## CombinedInput<T>(Func<T, float>)

Returns combined input of all InputProviders present in the scene. Result will be a sum of all inputs of the selected type. T is a type of InputProvider that the input will be retrieved from.

### Declaration

```
public static float CombinedInput<T>(Func<T, float> selector) where T : InputProvider
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.func-2">Func</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.func-2">https://learn.microsoft.com/dotnet/api/system.func-2</a> ), <T, <a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> )>	<i>selector</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Type Parameters

Name	Description
<i>T</i>	

## CombinedInput<T>(Func<T, Vector2>)

Returns combined input of all InputProviders present in the scene. Result will be a sum of all inputs of the selected type. T is a type of InputProvider that the input will be retrieved from.

### Declaration

```
public static Vector2 CombinedInput<T>(Func<T, Vector2> selector) where T : InputProvider
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.func-2">Func</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.func-2">https://learn.microsoft.com/dotnet/api/system.func-2</a> ), <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ), <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> )>	<i>selector</i>	

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## Type Parameters

Name	Description
<i>T</i>	

## OnDestroy()

### Declaration

```
public virtual void OnDestroy()
```

# Class InputSystemSceneInputProvider

Unity Input System implementation of scene input provider. Handles camera controls and scene navigation using the new Input System.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [SceneInputProviderBase](#) ([NWH.Common.Input.SceneInputProviderBase.html](#)).
- ↳ InputSystemSceneInputProvider

## Inherited Members

---

[SceneInputProviderBase.requireCameraPanningModifier](#)  
([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase requireCameraPanningModifier](#)).

[SceneInputProviderBase.requireCameraRotationModifier](#)  
([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase requireCameraRotationModifier](#)).

[InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Instances](#)).

[InputProvider.OnDestroy\(\)](#)  
([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider OnDestroy](#)).

[InputProvider.CombinedInput<T>\(Func<T, int>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32](#)).

[InputProvider.CombinedInput<T>\(Func<T, float>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single](#)).

[InputProvider.CombinedInput<T>\(Func<T, bool>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean](#)).

[InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class InputSystemSceneInputProvider : SceneInputProviderBase
```

# Fields

## sceneInputActions

### Declaration

```
public SceneInputActions sceneInputActions
```

### Field Value

Type	Description
<a href="#">SceneInputActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.html</a> ).	

# Methods

## Awake()

### Declaration

```
public override void Awake()
```

### Overrides

[InputProvider.Awake\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_Awake](#)).

## CameraPanning()

Returns camera panning input as a Vector2 (x = horizontal, y = vertical).

### Declaration

```
public override Vector2 CameraPanning()
```

### Returns

Type	Description
<a href="#">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

### Overrides

[SceneInputProviderBase.CameraPanning\(\)](#) ([NWH.Common.Input.SceneInputProviderBase.html#NWH\\_Common\\_Input\\_SceneInputProviderBase\\_CameraPanning](#)).

## CameraPanningModifier()

Returns true when the camera panning modifier button is held. If requireCameraPanningModifier is false, always returns true.

## Declaration

```
public override bool CameraPanningModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.CameraPanningModifier\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraPanningModifier](#)).

## CameraRotation()

Returns camera rotation input as a Vector2 (x = horizontal, y = vertical).

## Declaration

```
public override Vector2 CameraRotation()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## Overrides

[ScenInputProviderBase.CameraRotation\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraRotation](#)).

## CameraRotationModifier()

Returns true when the camera rotation modifier button is held. If requireCameraRotationModifier is false, always returns true.

## Declaration

```
public override bool CameraRotationModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.CameraRotationModifier\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraRotati](#)

onModifier).

## CameraZoom()

Returns camera zoom input value. Positive = zoom in, negative = zoom out.

### Declaration

```
public override float CameraZoom()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### Overrides

[ScenInputProviderBase.CameraZoom\(\)](#).

([NWH.Common.Input.ScenInputProviderBase.html#NWH\\_Common\\_Input\\_ScenInputProviderBase\\_CameraZoom](#)).

## ChangeCamera()

Returns true when the change camera button is pressed.

### Declaration

```
public override bool ChangeCamera()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### Overrides

[ScenInputProviderBase.ChangeCamera\(\)](#).

([NWH.Common.Input.ScenInputProviderBase.html#NWH\\_Common\\_Input\\_ScenInputProviderBase\\_ChangeCamera](#)).

## ChangeVehicle()

Returns true when the change vehicle button is pressed.

### Declaration

```
public override bool ChangeVehicle()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.ChangeVehicle\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase ChangeVehicle](#)).

## CharacterMovement()

Returns character movement input as a Vector2 (x = horizontal, y = forward/back).

### Declaration

```
public override Vector2 CharacterMovement()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## Overrides

[ScenInputProviderBase.CharacterMovement\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CharacterMovement](#)).

## ToggleGUI()

Returns true when the toggle GUI button is pressed.

### Declaration

```
public override bool ToggleGUI()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.ToggleGUI\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase ToggleGUI](#)).

# Class InputUtils

Utility methods for safe input retrieval with automatic fallback to default keys. Prevents errors when Input Manager bindings are missing.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)  
↳ InputUtils

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class InputUtils
```

## Methods

### TryGetAxis(string, bool)

Attempts to retrieve axis value from Input Manager, returns 0 if binding is missing.

#### Declaration

```
public static float TryGetAxis(string axisName, bool showWarning = true)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>axisName</i>	Input Manager axis name to query.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>showWarning</i>	Display warning message when axis is missing.

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Axis value between -1 and 1, or 0 if binding is missing.

### TryGetAxisRaw(string, bool)

Attempts to retrieve raw axis value from Input Manager, returns 0 if binding is missing. Raw axes return only -1, 0, or 1 without smoothing.

## Declaration

```
public static float TryGetAxisRaw(string axisName, bool showWarning = true)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>axisName</i>	Input Manager axis name to query.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>showWarning</i>	Display warning message when axis is missing.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Raw axis value (-1, 0, or 1), or 0 if binding is missing.

## TryGetButton(string, KeyCode, bool)

Attempts to retrieve button state from Input Manager, falls back to KeyCode if binding is missing.

## Declaration

```
public static bool TryGetButton(string buttonName, KeyCode altKey, bool showWarning = true)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>buttonName</i>	Input Manager button name to query.
KeyCode	<i>altKey</i>	Fallback KeyCode to use if binding is missing.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>showWarning</i>	Display warning message when falling back to default key.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if button is currently held down.

## TryGetButtonDown(string, KeyCode, bool)

Attempts to retrieve button press from Input Manager, falls back to KeyCode if binding is missing.

## Declaration

```
public static bool TryGetButtonDown(string buttonName, KeyCode altKey, bool showWarning = true)
```

## Parameters

Type	Name	Description
<u>string</u> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>buttonName</i>	Input Manager button name to query.
KeyCode	<i>altKey</i>	Fallback KeyCode to use if binding is missing.
<u>bool</u> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>showWarning</i>	Display warning message when falling back to default key.

## Returns

Type	Description
<u>bool</u> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True on the frame the button was pressed.

# Class MobileInputButton

Extended Unity UI Button with state tracking for mobile input handling. Provides `hasBeenClicked` and `isPressed` flags for easier input polling.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [UIBehaviour](#)
- ↳ [Selectable](#)
- ↳ [Button](#)
- ↳ [MobileInputButton](#)

## Implements

[IMoveHandler](#)  
[IPointerDownHandler](#)  
[IPointerUpHandler](#)  
[IPointerEnterHandler](#)  
[IPointerExitHandler](#)  
[ISelectHandler](#)  
[IDeselectHandler](#)  
[IPointerClickHandler](#)  
[ISubmitHandler](#)  
[IEventSystemHandler](#)

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#)).

**Assembly:** [NWH.DWP2.dll](#)

## Syntax

```
[DefaultExecutionOrder(1000)]  
public class MobileInputButton : Button, IMoveHandler, IPointerDownHandler, IPointerUpHandle  
r, IPointerEnterHandler, IPointerExitHandler, ISelectHandler, IDeselectHandler, IPointerClic  
kHandler, ISubmitHandler, IEventSystemHandler
```

## Fields

### hasBeenClicked

True for one frame after the button is clicked. Automatically resets to false.

### Declaration

```
public bool hasBeenClicked
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## isPressed

True while the button is being held down. Updates every frame.

### Declaration

```
public bool isPressed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Methods

### OnPointerDown(PointerEventData)

#### Declaration

```
public override void OnPointerDown(PointerEventData eventData)
```

#### Parameters

Type	Name	Description
PointerEventData	<i>eventData</i>	

#### Overrides

UnityEngine.UI.Selectable.OnPointerDown(UnityEngine.EventSystems.PointerEventData)

## Implements

- UnityEngine.EventSystems.IMoveHandler
- UnityEngine.EventSystems.IPointerDownHandler
- UnityEngine.EventSystems.IPointerUpHandler
- UnityEngine.EventSystems.IPointerEnterHandler
- UnityEngine.EventSystems.IPointerExitHandler
- UnityEngine.EventSystems.ISelectHandler
- UnityEngine.EventSystems.IDeselectHandler
- UnityEngine.EventSystems.IPointerClickHandler
- UnityEngine.EventSystems.ISubmitHandler
- UnityEngine.EventSystems.IEventSystemHandler



# Class MobileSceneInputProvider

Scene input provider for mobile platforms using on-screen UI buttons. Requires MobileInputButton components assigned to changeCameraButton and changeVehicleButton fields.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [SceneInputProviderBase](#) ([NWH.Common.Input.SceneInputProviderBase.html](#)).
- ↳ MobileSceneInputProvider

## Inherited Members

---

[SceneInputProviderBase.requireCameraPanningModifier](#)  
([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase requireCameraPanningModifier](#)).

[SceneInputProviderBase.requireCameraRotationModifier](#)  
([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase requireCameraRotationModifier](#)).

[InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Instances](#)).

[InputProvider.Awake\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Awake](#)).

[InputProvider.OnDestroy\(\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider OnDestroy](#)).

[InputProvider.CombinedInput<T>\(Func<T, int>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32](#)).

[InputProvider.CombinedInput<T>\(Func<T, float>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single](#)).

[InputProvider.CombinedInput<T>\(Func<T, bool>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean](#)).

[InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class MobileSceneInputProvider : SceneInputProviderBase
```

# Fields

## changeCameraButton

UI button for changing camera. Should reference a MobileInputButton in the scene.

### Declaration

```
public MobileInputButton changeCameraButton
```

### Field Value

Type	Description
<a href="#">MobileInputButton (NWH.Common.Input.MobileInputButton.html)</a>	

## changeVehicleButton

UI button for changing vehicle. Should reference a MobileInputButton in the scene.

### Declaration

```
public MobileInputButton changeVehicleButton
```

### Field Value

Type	Description
<a href="#">MobileInputButton (NWH.Common.Input.MobileInputButton.html)</a>	

# Methods

## CameraPanning()

Returns camera panning input as a Vector2 (x = horizontal, y = vertical).

### Declaration

```
public override Vector2 CameraPanning()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	

### Overrides

[ScenInputProviderBase.CameraPanning\(\)](#)

[\(NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraPanning\)](#)

g).

## CameraPanningModifier()

Returns true when the camera panning modifier button is held. If requireCameraPanningModifier is false, always returns true.

### Declaration

```
public override bool CameraPanningModifier()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### Overrides

[ScenInputProviderBase.CameraPanningModifier\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraPanningModifier](#)).

## CameraRotation()

Returns camera rotation input as a Vector2 (x = horizontal, y = vertical).

### Declaration

```
public override Vector2 CameraRotation()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

### Overrides

[ScenInputProviderBase.CameraRotation\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraRotation](#)).

## CameraRotationModifier()

Returns true when the camera rotation modifier button is held. If requireCameraRotationModifier is false, always returns true.

### Declaration

```
public override bool CameraRotationModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.CameraRotationModifier\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraRotationModifier](#)).

## CameraZoom()

Returns camera zoom input value. Positive = zoom in, negative = zoom out.

## Declaration

```
public override float CameraZoom()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Overrides

[ScenInputProviderBase.CameraZoom\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase CameraZoom](#)).

## ChangeCamera()

Returns true when the change camera button is pressed.

## Declaration

```
public override bool ChangeCamera()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[ScenInputProviderBase.ChangeCamera\(\)](#)

([NWH.Common.Input.ScenInputProviderBase.html#NWH Common Input ScenInputProviderBase ChangeCamera](#)).

## ChangeVehicle()

Returns true when the change vehicle button is pressed.

## Declaration

```
public override bool ChangeVehicle()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[SceneInputProviderBase.ChangeVehicle\(\)](#).

([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase ChangeVehicle](#)).

## CharacterMovement()

Returns character movement input as a Vector2 (x = horizontal, y = forward/back).

## Declaration

```
public override Vector2 CharacterMovement()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## Overrides

[SceneInputProviderBase.CharacterMovement\(\)](#).

([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase CharacterMovement](#)).

## ToggleGUI()

Returns true when the toggle GUI button is pressed.

## Declaration

```
public override bool ToggleGUI()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Overrides

[SceneInputProviderBase.ToggleGUI\(\)](#).

([NWH.Common.Input.SceneInputProviderBase.html#NWH Common Input SceneInputProviderBase ToggleGUI](#)).



# Class SceneInputActions

Provides programmatic access to `UnityEngine.InputSystem.InputActionAsset`, `UnityEngine.InputSystem.InputActionMap`, `UnityEngine.InputSystem.InputAction` and `UnityEngine.InputSystem.InputControlScheme` instances defined in asset "Packages/com.nwh.common/Runtime/Input/InputSystem/SceneInputActions.inputactions".

## Inheritance

---

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (https://learn.microsoft.com/dotnet/api/system.object)  
↳ SceneInputActions

## Implements

`IInputActionCollection2`

`IInputActionCollection`

`IEnumerable` (https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1).<InputAction>

`IEnumerable` (https://learn.microsoft.com/dotnet/api/system.collections.ienumerable).

`IDisposable` (https://learn.microsoft.com/dotnet/api/system.idisposable).

**Namespace:** [NWH](#) (NWH.html), [Common](#) (NWH.Common.html), [Input](#) (NWH.Common.Input.html)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class SceneInputActions : IInputActionCollection2, IInputActionCollection, IEnumerable<InputAction>, IEnumerable, IDisposable
```

## Remarks

This class is source generated and any manual edits will be discarded if the associated asset is reimported or modified.

## Examples

```
using namespace UnityEngine;
using UnityEngine.InputSystem;

// Example of using an InputActionMap named "Player" from a UnityEngine.MonoBehaviour implementing callback interface.
public class Example : MonoBehaviour, MyActions.IPlayerActions
{
    private MyActions.Actions m_Actions;           // Source code representation of a
    private MyActions.Actions.PlayerActions m_Player; // Source code representation of a
    private InputActionMap m_Map;                  // Action map.

    void Awake()
    {
        m_Actions = new MyActions.Actions();           // Create asset object.
        m_Player = m_Actions.Player;                   // Extract action map object.
        m_Map.AddCallbacks(this);                       // Register callback interface IPlayerActions.
    }

    void OnDestroy()
    {
        m_Actions.Dispose();                           // Destroy asset object.
    }

    void OnEnable()
    {
        m_Player.Enable();                             // Enable all actions within map.
    }

    void OnDisable()
    {
        m_Player.Disable();                            // Disable all actions within map.
    }

    #region Interface implementation of MyActions.IPlayerActions

    // Invoked when "Move" action is either started, performed or canceled.
    public void OnMove(InputAction.CallbackContext context)
    {
        Debug.Log($"OnMove: {context.ReadValue<Vector2>()}");
    }

    // Invoked when "Attack" action is either started, performed or canceled.
    public void OnAttack(InputAction.CallbackContext context)
    {
        Debug.Log($"OnAttack: {context.ReadValue<float>()}");
    }

    #endregion
}
```

## Constructors

## SceneInputActions()

Constructs a new instance.

### Declaration

```
public SceneInputActions()
```

## Properties

### CameraControls

Provides a new [SceneInputActions.CameraControlsActions \(NWH.Common.Input.SceneInputActions.CameraControlsActions.html\)](#) instance referencing this action map.

### Declaration

```
public SceneInputActions.CameraControlsActions CameraControls { get; }
```

### Property Value

Type	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a> . <a href="#">CameraControlsActions (NWH.Common.Input.SceneInputActions.CameraControlsActions.html)</a>	

### SceneControls

Provides a new [SceneInputActions.SceneControlsActions \(NWH.Common.Input.SceneInputActions.SceneControlsActions.html\)](#) instance referencing this action map.

### Declaration

```
public SceneInputActions.SceneControlsActions SceneControls { get; }
```

### Property Value

Type	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a> . <a href="#">SceneControlsActions (NWH.Common.Input.SceneInputActions.SceneControlsActions.html)</a>	

### asset

Provides access to the underlying asset instance.

## Declaration

```
public InputActionAsset asset { get; }
```

## Property Value

Type	Description
InputActionAsset	

## bindingMask

### Declaration

```
public InputBinding? bindingMask { get; set; }
```

## Property Value

Type	Description
InputBinding?	

## bindings

### Declaration

```
public IEnumerable<InputBinding> bindings { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> ). <InputBinding>	

## controlSchemes

### Declaration

```
public ReadOnlyArray<InputControlScheme> controlSchemes { get; }
```

## Property Value

Type	Description
ReadOnlyArray<InputControlScheme>	

## devices

### Declaration

```
public ReadOnlyArray<InputDevice>? devices { get; set; }
```

### Property Value

Type	Description
ReadOnlyArray<InputDevice>?	

## Methods

### Contains(InputAction)

#### Declaration

```
public bool Contains(InputAction action)
```

#### Parameters

Type	Name	Description
InputAction	<i>action</i>	

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### Disable()

#### Declaration

```
public void Disable()
```

### Dispose()

Destroys this asset and all associated UnityEngine.InputSystem.InputAction instances.

#### Declaration

```
public void Dispose()
```

## Enable()

### Declaration

```
public void Enable()
```

## ~SceneInputActions()

### Declaration

```
protected ~SceneInputActions()
```

## FindAction(string, bool)

### Declaration

```
public InputAction FindAction(string actionNameOrId, bool throwIfNotFound = false)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>actionNameOrId</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>throwIfNotFound</i>	

### Returns

Type	Description
InputAction	

## FindBinding(InputBinding, out InputAction)

### Declaration

```
public int FindBinding(InputBinding bindingMask, out InputAction action)
```

### Parameters

Type	Name	Description
InputBinding	<i>bindingMask</i>	
InputAction	<i>action</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## GetEnumerator()

Returns an enumerator that iterates through the collection.

### Declaration

```
public IEnumerator<InputAction> GetEnumerator()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerator-1">IEnumerator</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerator-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerator-1</a> ). <InputAction>	An enumerator that can be used to iterate through the collection.

## Implements

UnityEngine.InputSystem.IInputActionCollection2

UnityEngine.InputSystem.IInputActionCollection

[IEnumerable<T>](https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1) (<https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1>).

[IEnumerable](https://learn.microsoft.com/dotnet/api/system.collections.ienumerable) (<https://learn.microsoft.com/dotnet/api/system.collections.ienumerable>).

[IDisposable](https://learn.microsoft.com/dotnet/api/system.idisposable) (<https://learn.microsoft.com/dotnet/api/system.idisposable>).

# Struct SceneInputActions.CameraControlsActions

Provides access to input actions defined in input action map "CameraControls".

**Namespace:** [NWH \(NWH.html\)](#).[Common \(NWH.Common.html\)](#).[Input \(NWH.Common.Input.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public struct SceneInputActions.CameraControlsActions
```

## Constructors

### CameraControlsActions(SceneInputActions)

Construct a new instance of the input action map wrapper class.

#### Declaration

```
public CameraControlsActions(SceneInputActions wrapper)
```

#### Parameters

Type	Name	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a>	<i>wrapper</i>	

## Properties

### CameraPanning

Provides access to the underlying input action "CameraControls/CameraPanning".

#### Declaration

```
public InputAction CameraPanning { get; }
```

#### Property Value

Type	Description
InputAction	

## CameraPanningModifier

Provides access to the underlying input action "CameraControls/CameraPanningModifier".

### Declaration

```
public InputAction CameraPanningModifier { get; }
```

### Property Value

Type	Description
InputAction	

## CameraRotation

Provides access to the underlying input action "CameraControls/CameraRotation".

### Declaration

```
public InputAction CameraRotation { get; }
```

### Property Value

Type	Description
InputAction	

## CameraRotationModifier

Provides access to the underlying input action "CameraControls/CameraRotationModifier".

### Declaration

```
public InputAction CameraRotationModifier { get; }
```

### Property Value

Type	Description
InputAction	

## CameraZoom

Provides access to the underlying input action "CameraControls/CameraZoom".

### Declaration

```
public InputAction CameraZoom { get; }
```

## Property Value

Type	Description
InputAction	

## ChangeCamera

Provides access to the underlying input action "CameraControls/ChangeCamera".

### Declaration

```
public InputAction ChangeCamera { get; }
```

## Property Value

Type	Description
InputAction	

## enabled

### Declaration

```
public bool enabled { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Methods

### AddCallbacks(ICameraControlsActions)

Adds UnityEngine.InputSystem.InputAction.started, UnityEngine.InputSystem.InputAction.performed and Unity Engine.InputSystem.InputAction.canceled callbacks provided via on all input actions contained in this map.

### Declaration

```
public void AddCallbacks(SceneInputActions.ICameraControlsActions instance)
```

## Parameters

Type	Name	Description
<a href="#">ScenelInputActions (NWH.Common.Input.ScenelInputActions.html)</a> . <a href="#">ICameraControlsActions (NWH.Common.Input.ScenelInputActions.ICameraControlsActions.html)</a> .	<i>instance</i>	Callback instance.

## Remarks

If instance is null or instance have already been added this method does nothing.

## See Also

[ScenelInputActions \(NWH.Common.Input.ScenelInputActions.html\)](#).  
[ICameraControlsActions \(NWH.Common.Input.ScenelInputActions.ICameraControlsActions.html\)](#).

## Disable()

### Declaration

```
public void Disable()
```

## Enable()

### Declaration

```
public void Enable()
```

## Get()

Provides access to the underlying input action map instance.

### Declaration

```
public InputActionMap Get()
```

## Returns

Type	Description
InputActionMap	

## RemoveCallbacks(ICameraControlsActions)

Unregisters and unregisters all input action callbacks via [UnregisterCallbacks\(ICameraControlsActions\) \(NWH.Common.Input.ScenelInputActions.ICameraControlsActions.html\)](#).

## Declaration

```
public void RemoveCallbacks(SceneInputActions.ICameraControlsActions instance)
```

## Parameters

Type	Name	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a> . <a href="#">ICameraControlsActions (NWH.Common.Input.SceneInputActions.ICameraControlsActions.html)</a> .	<i>instance</i>	

## See Also

[UnregisterCallbacks \(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html\)](#)([ICameraControlsActions \(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html\)](#))

## SetCallbacks(ICameraControlsActions)

Replaces all existing callback instances and previously registered input action callbacks associated with them with callbacks provided via .

## Declaration

```
public void SetCallbacks(SceneInputActions.ICameraControlsActions instance)
```

## Parameters

Type	Name	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a> . <a href="#">ICameraControlsActions (NWH.Common.Input.SceneInputActions.ICameraControlsActions.html)</a> .	<i>instance</i>	

## Remarks

If *instance* is *null* , calling this method will only unregister all existing callbacks but not register any new callbacks.

## See Also

[AddCallbacks\(ICameraControlsActions\)](#)

([NWH.Common.Input.SceneInputActions.CameraControlsActions.html#NWH Common Input SceneInputActions CameraControlsActions AddCallbacks NWH Common Input SceneInputActions ICameraControlsActions](#).)

[RemoveCallbacks\(ICameraControlsActions\)](#)

([NWH.Common.Input.SceneInputActions.CameraControlsActions.html#NWH Common Input SceneInputActions CameraControlsActions RemoveCallbacks NWH Common Input SceneInputActions ICameraControlsActions](#).)

[UnregisterCallbacks \(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html\)](#)([ICameraControlsActions \(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html\)](#))

## Operators

### implicit operator InputActionMap(CameraControlsActions)

Implicitly converts an to an instance.

## Declaration

```
public static implicit operator InputActionMap(SceneInputActions.CameraControlsActions set)
```

## Parameters

Type	Name	Description
<a href="#">SceneInputActions</a> (NWH.Common.Input.SceneInputActions.html). <a href="#">CameraControlsActions</a> (NWH.Common.Input.SceneInputActions.CameraControlsActions.html).	<i>set</i>	

## Returns

Type	Description
InputActionMap	

# Interface SceneInputActions.ICameraControlsActions

Interface to implement callback methods for all input action callbacks associated with input actions defined by "CameraControls" which allows adding and removing callbacks.

**Namespace:** [NWH \(NWH.html\)](#).[Common \(NWH.Common.html\)](#).[Input \(NWH.Common.Input.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public interface SceneInputActions.ICameraControlsActions
```

## Methods

### OnCameraPanning(CallbackContext)

Method invoked when associated input action "CameraPanning" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

#### Declaration

```
void OnCameraPanning(InputAction.CallbackContext context)
```

#### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

#### See Also

`started`  
`performed`  
`canceled`

### OnCameraPanningModifier(CallbackContext)

Method invoked when associated input action "CameraPanningModifier" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

#### Declaration

```
void OnCameraPanningModifier(InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnCameraRotation(CallbackContext)

Method invoked when associated input action "CameraRotation" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

## Declaration

```
void OnCameraRotation(UnityEngine.InputSystem.InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnCameraRotationModifier(CallbackContext)

Method invoked when associated input action "CameraRotationModifier" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

## Declaration

```
void OnCameraRotationModifier(UnityEngine.InputSystem.InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnCameraZoom(CallbackContext)

Method invoked when associated input action "CameraZoom" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnCameraZoom(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)  
[performed](#)  
[canceled](#)

## OnChangeCamera(CallbackContext)

Method invoked when associated input action "ChangeCamera" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnChangeCamera(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)  
[performed](#)  
[canceled](#)

## See Also

### [AddCallbacks](#)

[\(NWH.Common.Input.SceneInputActions.CameraControlsActions.html#NWH\\_Common\\_Input\\_SceneInputActions\\_CameraControlsActions\\_AddCallbacks\\_NWH\\_Common\\_Input\\_SceneInputActions\\_ICameraControlsActions\\_\)\(ICameraControlsActions \(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html\)\)](#)

### [RemoveCallbacks](#)

[\(NWH.Common.Input.SceneInputActions.CameraControlsActions.html#NWH\\_Common\\_Input\\_SceneInputActions\\_CameraControlsActions\\_RemoveCallbacks\\_NWH\\_Common\\_Input\\_SceneInputActions\\_ICameraControlsActions\\_\)\(ICameraControlsActions \(NWH.Common.Input.SceneInputActions.ICameraControlsActions.html\)\)](#)



# Interface SceneInputActions.ISceneControlsActions

Interface to implement callback methods for all input action callbacks associated with input actions defined by "SceneControls" which allows adding and removing callbacks.

**Namespace:** [NWH \(NWH.html\)](#), [Common \(NWH.Common.html\)](#), [Input \(NWH.Common.Input.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public interface SceneInputActions.ISceneControlsActions
```

## Methods

### OnChangeVehicle(CallbackContext)

Method invoked when associated input action "ChangeVehicle" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

#### Declaration

```
void OnChangeVehicle(InputAction.CallbackContext context)
```

#### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

#### See Also

`started`  
`performed`  
`canceled`

### OnDragObjectModifier(CallbackContext)

Method invoked when associated input action "DragObjectModifier" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

#### Declaration

```
void OnDragObjectModifier(InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnFPSMovement(CallbackContext)

Method invoked when associated input action "FPSMovement" is either UnityEngine.InputSystem.InputAction.started, UnityEngine.InputSystem.InputAction.performed or UnityEngine.InputSystem.InputAction.canceled.

## Declaration

```
void OnFPSMovement(UnityEngine.InputSystem.InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnShowCursor(CallbackContext)

Method invoked when associated input action "ShowCursor" is either UnityEngine.InputSystem.InputAction.started, UnityEngine.InputSystem.InputAction.performed or UnityEngine.InputSystem.InputAction.canceled.

## Declaration

```
void OnShowCursor(UnityEngine.InputSystem.InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnToggleGUI(CallbackContext)

Method invoked when associated input action "ToggleGUI" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnToggleGUI(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)

[performed](#)

[canceled](#)

## See Also

### [AddCallbacks](#)

([NWH.Common.Input.SceneInputActions.SceneControlsActions.html#NWH\\_Common\\_Input\\_SceneInputActions\\_SceneControlsActions\\_AddCallbacks\\_NWH\\_Common\\_Input\\_SceneInputActions\\_ISceneControlsActions](#)).(ISceneControlsActions ([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#)))

### [RemoveCallbacks](#)

([NWH.Common.Input.SceneInputActions.SceneControlsActions.html#NWH\\_Common\\_Input\\_SceneInputActions\\_SceneControlsActions\\_RemoveCallbacks\\_NWH\\_Common\\_Input\\_SceneInputActions\\_ISceneControlsActions](#)).(ISceneControlsActions ([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#)))

# Struct SceneInputActions.SceneControlsActions

Provides access to input actions defined in input action map "SceneControls".

**Namespace:** [NWH \(NWH.html\)](#).[Common \(NWH.Common.html\)](#).[Input \(NWH.Common.Input.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public struct SceneInputActions.SceneControlsActions
```

## Constructors

### SceneControlsActions(SceneInputActions)

Construct a new instance of the input action map wrapper class.

#### Declaration

```
public SceneControlsActions(SceneInputActions wrapper)
```

#### Parameters

Type	Name	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a>	<i>wrapper</i>	

## Properties

### ChangeVehicle

Provides access to the underlying input action "SceneControls/ChangeVehicle".

#### Declaration

```
public InputAction ChangeVehicle { get; }
```

#### Property Value

Type	Description
InputAction	

## DragObjectModifier

Provides access to the underlying input action "SceneControls/DragObjectModifier".

### Declaration

```
public InputAction DragObjectModifier { get; }
```

### Property Value

Type	Description
InputAction	

## FPSMovement

Provides access to the underlying input action "SceneControls/FPSMovement".

### Declaration

```
public InputAction FPSMovement { get; }
```

### Property Value

Type	Description
InputAction	

## ShowCursor

Provides access to the underlying input action "SceneControls/ShowCursor".

### Declaration

```
public InputAction ShowCursor { get; }
```

### Property Value

Type	Description
InputAction	

## ToggleGUI

Provides access to the underlying input action "SceneControls/ToggleGUI".

### Declaration

```
public InputAction ToggleGUI { get; }
```

## Property Value

Type	Description
InputAction	

## enabled

### Declaration

```
public bool enabled { get; }
```

## Property Value

Type	Description
bool ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Methods

### AddCallbacks(ISceneControlsActions)

Adds UnityEngine.InputSystem.InputAction.started, UnityEngine.InputSystem.InputAction.performed and Unity Engine.InputSystem.InputAction.canceled callbacks provided via on all input actions contained in this map.

### Declaration

```
public void AddCallbacks(SceneInputActions.ISceneControlsActions instance)
```

### Parameters

Type	Name	Description
<a href="#">SceneInputActions (NWH.Common.Input.SceneInputActions.html)</a> , <a href="#">ISceneControlsActions (NWH.Common.Input.SceneInputActions.ISceneControlsActions.html)</a> .	<i>instance</i>	Callback instance.

### Remarks

If instance is null or instance have already been added this method does nothing.

### See Also

[SceneInputActions \(NWH.Common.Input.SceneInputActions.html\)](#), [SceneControlsActions \(NWH.Common.Input.SceneInputActions.SceneControlsActions.html\)](#).

## Disable()

## Declaration

```
public void Disable()
```

## Enable()

### Declaration

```
public void Enable()
```

## Get()

Provides access to the underlying input action map instance.

### Declaration

```
public InputActionMap Get()
```

### Returns

Type	Description
InputActionMap	

## RemoveCallbacks(ISceneControlsActions)

Unregisters and unregisters all input action callbacks via [UnregisterCallbacks\(ISceneControlsActions\)](#).  
([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#)).

### Declaration

```
public void RemoveCallbacks(SceneInputActions.ISceneControlsActions instance)
```

### Parameters

Type	Name	Description
<a href="#">SceneInputActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.html</a> ), <a href="#">ISceneControlsActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.ISceneControlsActions.html</a> ).	<i>instance</i>	

### See Also

[UnregisterCallbacks](#) ([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#)), ([ISceneControlsActions](#)  
([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#)))

## SetCallbacks(ISceneControlsActions)

Replaces all existing callback instances and previously registered input action callbacks associated with them with callbacks provided via .

### Declaration

```
public void SetCallbacks(SceneInputActions.ISceneControlsActions instance)
```

### Parameters

Type	Name	Description
<a href="#">SceneInputActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.html</a> ), <a href="#">ISceneControlsActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.ISceneControlsActions.html</a> ).	<i>instance</i>	

### Remarks

If *instance* is *null*, calling this method will only unregister all existing callbacks but not register any new callbacks.

### See Also

[AddCallbacks\(ISceneControlsActions\)](#)

([NWH.Common.Input.SceneInputActions.SceneControlsActions.html#NWH Common Input SceneInputActions SceneControlsActions AddCallbacks NWH Common Input SceneInputActions ISceneControlsActions](#).)

[RemoveCallbacks\(ISceneControlsActions\)](#)

([NWH.Common.Input.SceneInputActions.SceneControlsActions.html#NWH Common Input SceneInputActions SceneControlsActions RemoveCallbacks NWH Common Input SceneInputActions ISceneControlsActions](#).)

[UnregisterCallbacks](#) ([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#))([ISceneControlsActions](#) ([NWH.Common.Input.SceneInputActions.ISceneControlsActions.html](#)))

## Operators

### implicit operator InputActionMap(SceneControlsActions)

Implicitly converts an to an instance.

### Declaration

```
public static implicit operator InputActionMap(SceneInputActions.SceneControlsActions set)
```

### Parameters

Type	Name	Description
<a href="#">SceneInputActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.html</a> ), <a href="#">SceneControlsActions</a> ( <a href="#">NWH.Common.Input.SceneInputActions.SceneControlsActions.html</a> ).	<i>set</i>	

### Returns

Type	Description
<a href="#">InputActionMap</a>	



# Class SceneInputProviderBase

InputProvider for scene and camera related behavior.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [SceneInputProviderBase](#)
  - ↳ [InputManagerSceneInputProvider](#) ([NWH.Common.Input.InputManagerSceneInputProvider.html](#)).
  - ↳ [InputSystemSceneInputProvider](#) ([NWH.Common.Input.InputSystemSceneInputProvider.html](#)).
  - ↳ [MobileSceneInputProvider](#) ([NWH.Common.Input.MobileSceneInputProvider.html](#)).

## Inherited Members

---

- [InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Instances](#)).
- [InputProvider.Awake\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Awake](#)).
- [InputProvider.OnDestroy\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider OnDestroy](#)).
- [InputProvider.CombinedInput<T>\(Func<T, int>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32](#)).
- [InputProvider.CombinedInput<T>\(Func<T, float>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single](#)).
- [InputProvider.CombinedInput<T>\(Func<T, bool>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean](#)).
- [InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Input](#) ([NWH.Common.Input.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public abstract class SceneInputProviderBase : InputProvider
```

## Fields

### **requireCameraPanningModifier**

If true a button press will be required to unlock camera panning.

## Declaration

```
[Tooltip(" If true a button press will be required to unlock camera panning.")]  
public bool requireCameraPanningModifier
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## requireCameraRotationModifier

If true a button press will be required to unlock camera rotation.

## Declaration

```
[Tooltip(" If true a button press will be required to unlock camera rotation.")]  
public bool requireCameraRotationModifier
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Methods

## CameraPanning()

Returns camera panning input as a Vector2 (x = horizontal, y = vertical).

## Declaration

```
public virtual Vector2 CameraPanning()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## CameraPanningModifier()

Returns true when the camera panning modifier button is held. If requireCameraPanningModifier is false, always returns true.

## Declaration

```
public virtual bool CameraPanningModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## CameraRotation()

Returns camera rotation input as a Vector2 (x = horizontal, y = vertical).

## Declaration

```
public virtual Vector2 CameraRotation()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## CameraRotationModifier()

Returns true when the camera rotation modifier button is held. If requireCameraRotationModifier is false, always returns true.

## Declaration

```
public virtual bool CameraRotationModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## CameraZoom()

Returns camera zoom input value. Positive = zoom in, negative = zoom out.

## Declaration

```
public virtual float CameraZoom()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## ChangeCamera()

Returns true when the change camera button is pressed.

### Declaration

```
public virtual bool ChangeCamera()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a>	

## ChangeVehicle()

Returns true when the change vehicle button is pressed.

### Declaration

```
public virtual bool ChangeVehicle()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a>	

## CharacterMovement()

Returns character movement input as a Vector2 (x = horizontal, y = forward/back).

### Declaration

```
public virtual Vector2 CharacterMovement()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a>	

## ToggleGUI()

Returns true when the toggle GUI button is pressed.

### Declaration

```
public virtual bool ToggleGUI()
```

### Returns

Type	Description
<u>bool</u> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Namespace NWH.Common.Scene Management

## Classes

### **VehicleChanger (NWH.Common.SceneManagement.VehicleChanger.html)**

Manages switching between multiple vehicles in a scene with support for both instant and character-based (enter/exit) modes.

## Enums

### **VehicleChanger.CharacterLocation (NWH.Common.SceneManagement.VehicleChanger.CharacterLocation.html)**

Represents the player's spatial relationship to vehicles.

# Class VehicleChanger

Manages switching between multiple vehicles in a scene with support for both instant and character-based (enter/exit) modes.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ VehicleChanger

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [SceneManagement](#) ([NWH.Common.SceneManagement.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[DefaultExecutionOrder(500)]  
public class VehicleChanger : MonoBehaviour
```

## Remarks

VehicleChanger supports two modes: - Instant switching: Press a button to cycle through vehicles immediately - Character-based: Player must walk to a vehicle and enter/exit at designated points

In character-based mode, the player can only enter vehicles when near an EnterExitPoint and the vehicle is moving slowly enough. This creates more realistic vehicle switching similar to GTA-style games.

Inactive vehicles can optionally be put to sleep to improve performance when managing many vehicles in a scene.

## Fields

### activeVehicleIndex

Index of the current vehicle in vehicles list.

#### Declaration

```
[Tooltip("    Index of the current vehicle in vehicles list.")]  
public int activeVehicleIndex
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## characterBased

Is vehicle changing character based? When true changing vehicles will require getting close to them to be able to enter, opposed to pressing a button to switch between vehicles.

### Declaration

```
[Tooltip("Is vehicle changing character based? When true changing vehicles will require getting close to them\r\nto be able to enter, opposed to pressing a button to switch between vehicles.")]  
public bool characterBased
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## characterObject

Game object representing a character. Can also be another vehicle.

### Declaration

```
[Tooltip(" Game object representing a character. Can also be another vehicle.")]  
public GameObject characterObject
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/GameObject.html">GameObject</a> ( <a href="https://docs.unity3d.com/ScriptReference/GameObject.html">https://docs.unity3d.com/ScriptReference/GameObject.html</a> ).	

## enterDistance

Maximum distance at which the character will be able to enter the vehicle.

### Declaration

```
[Range(0.2, 3)]  
[Tooltip(" Maximum distance at which the character will be able to enter the vehicle.")]  
public float enterDistance
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## enterExitTag

Tag of the object representing the point from which the enter distance will be measured. Useful if you want to enable you character to enter only when near the door.

### Declaration

```
[Tooltip("Tag of the object representing the point from which the enter distance will be measured. Useful if you want to enable you character to enter only when near the door.")]  
public string enterExitTag
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string (https://learn.microsoft.com/dotnet/api/system.string)</a> .	

## location

When the location is Near, the player can enter the vehicle.

### Declaration

```
[Tooltip("When the location is Near, the player can enter the vehicle.")]  
public VehicleChanger.CharacterLocation location
```

### Field Value

Type	Description
<a href="#">VehicleChanger (NWH.Common.SceneManagement.VehicleChanger.html)</a> . <a href="#">CharacterLocation (NWH.Common.SceneManagement.VehicleChanger.CharacterLocation.html)</a> .	

## maxEnterExitVehicleSpeed

Maximum speed at which the character will be able to enter / exit the vehicle.

### Declaration

```
[Tooltip(" Maximum speed at which the character will be able to enter / exit the vehicle.")]  
public float maxEnterExitVehicleSpeed
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a> .	

## onDeactivateAll

Event invoked when all vehicles are deactivated (e.g., when exiting in character-based mode).

### Declaration

```
public UnityEvent onDeactivateAll
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ).	

## onVehicleChanged

Event invoked whenever the active vehicle changes.

### Declaration

```
public UnityEvent onVehicleChanged
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ).	

## putOtherVehiclesToSleep

Should the vehicles that the player is currently not using be put to sleep to improve performance?

### Declaration

```
[Tooltip(" Should the vehicles that the player is currently not using be put to sleep to improve performance?")]  
public bool putOtherVehiclesToSleep
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## startInVehicle

Should the player start inside the vehicle?

## Declaration

```
[Tooltip("Should the player start inside the vehicle?")]  
public bool startInVehicle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## vehicles

List of all of the vehicles that can be selected and driven in the scene.

## Declaration

```
[Tooltip("List of all of the vehicles that can be selected and driven in the scene.")]  
public List<Vehicle> vehicles
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> ), <a href="#">Vehicle</a> ( <a href="#">NWH.Common.Vehicles.Vehicle.html</a> )>	

## Properties

### Instance

## Declaration

```
public static VehicleChanger Instance { get; }
```

## Property Value

Type	Description
<a href="#">VehicleChanger</a> ( <a href="#">NWH.Common.SceneManagement.VehicleChanger.html</a> ).	

## Methods

### ChangeVehicle(Vehicle)

Switches to the specified vehicle if it exists in the vehicles list.

## Declaration

```
public void ChangeVehicle(Vehicle ac)
```

## Parameters

Type	Name	Description
<a href="#">Vehicle (NWH.Common.Vehicles.Vehicle.html)</a>	<i>ac</i>	Vehicle reference to switch to.

## ChangeVehicle(int)

Changes vehicle to requested vehicle.

## Declaration

```
public void ChangeVehicle(int index)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>index</i>	Index of a vehicle in Vehicles list.

## DeactivateAllExceptActive()

Enables the current active vehicle and optionally disables all others based on putOtherVehiclesToSleep setting.

## Declaration

```
public void DeactivateAllExceptActive()
```

## DeactivateAllIncludingActive()

Disables all managed vehicles including the currently active one. Used when exiting vehicles in character-based mode.

## Declaration

```
public void DeactivateAllIncludingActive()
```

## DeregisterVehicle(Vehicle)

Removes a vehicle from the managed vehicles list. If the vehicle was active, automatically switches to the next vehicle.

## Declaration

```
public void DeregisterVehicle(Vehicle v)
```

## Parameters

Type	Name	Description
<a href="#">Vehicle (NWH.Common.Vehicles.Vehicle.html)</a>	v	Vehicle to deregister.

## EnterVehicle(Vehicle)

Puts the player inside the specified vehicle and activates it. In character-based mode, stores the entry position for later exit.

## Declaration

```
public void EnterVehicle(Vehicle v)
```

## Parameters

Type	Name	Description
<a href="#">Vehicle (NWH.Common.Vehicles.Vehicle.html)</a>	v	Vehicle to enter.

## ExitVehicle(Vehicle)

Removes the player from the vehicle and spawns the character object nearby. Character is positioned at the stored entry location.

## Declaration

```
public void ExitVehicle(Vehicle v)
```

## Parameters

Type	Name	Description
<a href="#">Vehicle (NWH.Common.Vehicles.Vehicle.html)</a>	v	Vehicle to exit.

## NextVehicle()

Switches to the next vehicle in the list, wrapping to the first vehicle when reaching the end.

## Declaration

```
public void NextVehicle()
```

## PreviousVehicle()

Switches to the previous vehicle in the list, wrapping to the last vehicle when at the beginning.

### Declaration

```
public void PreviousVehicle()
```

## RegisterVehicle(Vehicle)

Adds a vehicle to the managed vehicles list if not already present. Newly registered vehicles are automatically disabled unless they are the active vehicle.

### Declaration

```
public void RegisterVehicle(Vehicle v)
```

### Parameters

Type	Name	Description
<a href="#">Vehicle (NWH.Common.Vehicles.Vehicle.html)</a>	v	Vehicle to register.

# Enum VehicleChanger.CharacterLocation

Represents the player's spatial relationship to vehicles.

**Namespace:** [NWH \(NWH.html\)](#), [Common \(NWH.Common.html\)](#), [SceneManagement \(NWH.Common.SceneManagement.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum VehicleChanger.CharacterLocation
```

## Fields

Name	Description
Inside	Player is currently inside a vehicle.
Near	Player is close enough to enter a vehicle.
OutOfRange	Player is too far from any vehicle to interact.

# Namespace NWH.Common.ShiftingOrigin

## Classes

### **ShiftingOrigin (NWH.Common.ShiftingOrigin.ShiftingOrigin.html)**

Prevents floating point precision errors by shifting all scene objects back toward world origin when the main camera exceeds the distance threshold.

# Class ShiftingOrigin

Prevents floating point precision errors by shifting all scene objects back toward world origin when the main camera exceeds the distance threshold.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>)
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>)
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>)
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>)
- ↳ ShiftingOrigin

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [ShiftingOrigin](#) ([NWH.Common.ShiftingOrigin.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class ShiftingOrigin : MonoBehaviour
```

## Remarks

As objects move far from world origin [0,0,0], floating point precision degrades causing physics jitter and rendering artifacts. ShiftingOrigin solves this by periodically moving all scene content back toward origin, keeping the player near [0,0,0] at all times.

The shift is transparent to gameplay - relative positions remain identical. Useful for open world games, flight simulators, or any scenario with large travel distances.

Only affects the current scene. For multi-scene setups, ensure one ShiftingOrigin instance per loaded scene set.

## Fields

### Instance

#### Declaration

```
public static ShiftingOrigin Instance
```

#### Field Value

Type	Description
<a href="#">ShiftingOrigin</a> ( <a href="#">NWH.Common.ShiftingOrigin.ShiftingOrigin.html</a> ).	

### distanceThreshold

Distance from world origin in meters that triggers an origin shift. Default 500m works well for most scenarios.

## Declaration

```
public float distanceThreshold
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## onAfterJump

Event invoked after the origin shift completes and physics is re-synced.

## Declaration

```
public UnityEvent onAfterJump
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ).	

## onBeforeJump

Event invoked before the origin shift begins. Rigidbody sleep thresholds are temporarily disabled.

## Declaration

```
public UnityEvent onBeforeJump
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ).	

# Properties

## TotalOffset

Cumulative offset applied to all objects since scene start. Useful for tracking absolute world position despite origin shifts.

## Declaration

```
public Vector3 Total10ffset { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

# Methods

## RefreshCaches()

Refreshes cached references to Rigidbodies and ParticleSystems. Call this if new physics objects or particle systems are added to the scene at runtime.

## Declaration

```
public void RefreshCaches()
```

# Namespace NWH.Common.Utility

## Classes

### **[AnimationCurveExtensions \(NWH.Common.Utility.AnimationCurveExtensions.html\)](#)**

Extension methods for AnimationCurve manipulation and processing.

### **[ArrayExtensions \(NWH.Common.Utility.ArrayExtensions.html\)](#)**

Extension methods for array manipulation.

### **[GameObjectExtensions \(NWH.Common.Utility.GameObjectExtensions.html\)](#)**

Extension methods for GameObject and Transform operations.

### **[GeomUtility \(NWH.Common.Utility.GeoUtility.html\)](#)**

Collection of geometric utility functions for 3D math operations. Includes vector math, mesh calculations, triangle operations, and spatial queries.

### **[PIDController \(NWH.Common.Utility.PIDController.html\)](#)**

Proportional-Integral-Derivative controller for smooth value regulation. Used for automated control systems like cruise control, stability systems, and steering assistance.

### **[QuaternionExtensions \(NWH.Common.Utility.QuaternionExtensions.html\)](#)**

Extension methods for advanced Quaternion operations. Provides interpolation methods with control over rotation direction.

### **[UnitConverter \(NWH.Common.Utility.UnitConverter.html\)](#)**

Static utility class for converting between various units of measurement. Includes conversions for distance, speed, fuel efficiency, and angular velocity.

# Class AnimationCurveExtensions

Extension methods for AnimationCurve manipulation and processing.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ AnimationCurveExtensions

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class AnimationCurveExtensions
```

## Methods

### GenerateCurveArray(AnimationCurve, int)

Samples an AnimationCurve at regular intervals and returns the values as an array. Useful for pre-calculating curve values for performance-critical code.

#### Declaration

```
public static float[] GenerateCurveArray(this AnimationCurve self, int resolution = 256)
```

#### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">AnimationCurve</a> ( <a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">https://docs.unity3d.com/ScriptReference/AnimationCurve.html</a> ).	<i>self</i>	The curve to sample.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	<i>resolution</i>	Number of samples to take. Higher values provide more precision.

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ),[]	Array of sampled values from 0 to 1.

### MakeSmooth(AnimationCurve)

Smooths out a scripting-generated AnimationCurve by calculating appropriate tangents. Creates smooth transitions between keyframes.

## Declaration

```
public static AnimationCurve MakeSmooth(this AnimationCurve inCurve)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">AnimationCurve</a> ( <a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">https://docs.unity3d.com/ScriptReference/AnimationCurve.html</a> ).	<i>inCurve</i>	The curve to smooth.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">AnimationCurve</a> ( <a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">https://docs.unity3d.com/ScriptReference/AnimationCurve.html</a> ).	A new smoothed AnimationCurve.

# Class ArrayExtensions

Extension methods for array manipulation.

## Inheritance

---

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ ArrayExtensions

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class ArrayExtensions
```

## Methods

### Fill<T>(T[], params T[])

Efficiently fills an array by repeating a pattern of values. Uses doubling strategy for performance.

#### Declaration

```
public static void Fill<T>(this T[] destinationArray, params T[] value)
```

#### Parameters

Type	Name	Description
T[]	<i>destinationArray</i>	Array to fill.
T[]	<i>value</i>	Pattern of values to repeat throughout the array.

#### Type Parameters

Name	Description
<i>T</i>	Type of array elements.

# Class GameObjectExtensions

Extension methods for GameObject and Transform operations.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ GameObjectExtensions

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class GameObjectExtensions
```

## Methods

### FindBoundsIncludeChildren(GameObject)

Calculates the combined bounds of all MeshRenderers in a GameObject and its children.

#### Declaration

```
public static Bounds FindBoundsIncludeChildren(this GameObject gameObject)
```

#### Parameters

Type	Name	Description
<a href="#">GameObject</a> ( <a href="https://docs.unity3d.com/ScriptReference/GameObject.html">https://docs.unity3d.com/ScriptReference/GameObject.html</a> ).	<i>gameObject</i>	GameObject to calculate bounds for.

#### Returns

Type	Description
<a href="#">Bounds</a> ( <a href="https://docs.unity3d.com/ScriptReference/Bounds.html">https://docs.unity3d.com/ScriptReference/Bounds.html</a> ).	Combined bounds encapsulating all child renderers.

### GetComponentInParent<T>(Transform, bool)

Searches for a component in parent GameObjects, with option to include inactive objects. More flexible than Unity's built-in GetComponentInParent.

## Declaration

```
public static T GetComponentInParent<T>(this Transform transform, bool includeInactive = true) where T : Component
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ),	<i>transform</i>	Starting transform.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>includeInactive</i>	Include inactive GameObjects in search.

## Returns

Type	Description
T	First component of type T found in parents, or null if none found.

## Type Parameters

Name	Description
<i>T</i>	Type of component to find.

## GetComponentInParentsOrChildren<T>(Transform, bool)

Searches for a component in parents first, then children if not found. Combines functionality of GetComponentInParent and GetComponentInChildren.

## Declaration

```
public static T GetComponentInParentsOrChildren<T>(this Transform transform, bool includeInactive = true) where T : Component
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ),	<i>transform</i>	Starting transform.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>includeInactive</i>	Include inactive GameObjects in search.

## Returns

Type	Description
T	First component of type T found, or null if none found.

## Type Parameters

Name	Description
<i>T</i>	Type of component to find.

# Class GeomUtility

Collection of geometric utility functions for 3D math operations. Includes vector math, mesh calculations, triangle operations, and spatial queries.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ GeomUtility

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class GeomUtility
```

## Methods

### AreaFromFourPoints(Vector3, Vector3, Vector3, Vector3)

Calculates the area of a quadrilateral from four points.

#### Declaration

```
public static float AreaFromFourPoints(Vector3 p1, Vector3 p2, Vector3 p3, Vector3 p4)
```

#### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p1</i>	First point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p2</i>	Second point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p3</i>	Third point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p4</i>	Fourth point.

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Area of the quadrilateral.

### AreaFromThreePoints(Vector3, Vector3, Vector3)

Calculates the area of a triangle from three points.

## Declaration

```
public static float AreaFromThreePoints(Vector3 p1, Vector3 p2, Vector3 p3)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p1</i>	First point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p2</i>	Second point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p3</i>	Third point.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Area of the triangle.

## ChangeLayersRecursively(Transform, string)

Changes the layer of a transform and all its children recursively.

## Declaration

```
public static void ChangeLayersRecursively(this Transform trans, string name)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	<i>trans</i>	Root transform.
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>name</i>	Layer name.

## ChangeObjectAlpha(GameObject, float)

Changes the alpha value of a GameObject's material color.

## Declaration

```
public static void ChangeObjectAlpha(GameObject gameObject, float alpha)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/GameObject.html">GameObject</a> ( <a href="https://docs.unity3d.com/ScriptReference/GameObject.html">https://docs.unity3d.com/ScriptReference/GameObject.html</a> ).	<i>gameObject</i>	GameObject to modify.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>alpha</i>	New alpha value (0-1).

## ChangeObjectColor(GameObject, Color)

Changes the color of a GameObject's material.

### Declaration

```
public static void ChangeObjectColor(GameObject gameObject, Color color)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/GameObject.html">GameObject</a> ( <a href="https://docs.unity3d.com/ScriptReference/GameObject.html">https://docs.unity3d.com/ScriptReference/GameObject.html</a> ).	<i>gameObject</i>	GameObject to modify.
<a href="https://docs.unity3d.com/ScriptReference/Color.html">Color</a> ( <a href="https://docs.unity3d.com/ScriptReference/Color.html">https://docs.unity3d.com/ScriptReference/Color.html</a> ).	<i>color</i>	New color.

## ClampMagnitude(Vector3, float, float)

Clamps the magnitude of a vector between minimum and maximum values.

### Declaration

```
public static Vector3 ClampMagnitude(this Vector3 v, float min, float max)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>v</i>	Vector to clamp.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>min</i>	Minimum magnitude.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>max</i>	Maximum magnitude.

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Vector with clamped magnitude.

## CopySign(float, float)

Copies the sign from one float to the magnitude of another.

### Declaration

```
public static float CopySign(float mag, float sgn)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>mag</i>	Magnitude value.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>sgn</i>	Sign donor value.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Magnitude with the sign of <i>sgn</i> .

## DistanceAlongNormal(Vector3, Vector3, Vector3)

Calculates the distance between two points projected along a normal vector.

### Declaration

```
public static float DistanceAlongNormal(Vector3 a, Vector3 b, Vector3 normal)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>a</i>	First point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>b</i>	Second point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>normal</i>	Normal vector to project along.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Distance along normal.

## Equal(Quaternion, Quaternion)

Checks if two Quaternion values are approximately equal.

### Declaration

```
public static bool Equal(this Quaternion a, Quaternion b)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>a</i>	First quaternion.
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>b</i>	Second quaternion.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if angle between quaternions is less than 0.1 degrees.

## FindArea(Vector3, Vector3, Vector3, Vector3)

Calculates the area of a quadrilateral defined by four points.

### Declaration

```
public static float FindArea(Vector3 A, Vector3 B, Vector3 C, Vector3 D)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>A</i>	First corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>B</i>	Second corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>C</i>	Third corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>D</i>	Fourth corner.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Area of the quad.

## FindCenter(Vector3, Vector3, Vector3, Vector3)

Finds the center point of a quad or triangle defined by 3 or 4 points.

### Declaration

```
public static Vector3 FindCenter(Vector3 a, Vector3 b, Vector3 c, Vector3 d)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>a</i>	First corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>b</i>	Second corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>c</i>	Third corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>d</i>	Fourth corner (can equal first corner for triangle).

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Center point.

## FindChordLine(Vector3, Vector3, Vector3, Vector3, float)

Finds a point along the chord line of a quad at the specified percentage.

## Declaration

```
public static Vector3 FindChordLine(Vector3 a, Vector3 b, Vector3 c, Vector3 d, float chordPercent)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>a</i>	First corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>b</i>	Second corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>c</i>	Third corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>d</i>	Fourth corner.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>chordPercent</i>	Position along chord (0-1).

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Point on chord line.

## FindDistanceToSegment(Vector3, Vector3, Vector3)

Calculates the distance between a point and a line segment.

## Declaration

```
public static float FindDistanceToSegment(Vector3 pt, Vector3 p1, Vector3 p2)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pt</i>	Point to measure from.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>p1</i>	First endpoint of segment.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>p2</i>	Second endpoint of segment.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Distance to the segment.

## FindMeshCenter(Mesh)

Find mesh center by averaging. Returns local center.

## Declaration

```
public static Vector3 FindMeshCenter(Mesh mesh)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh (https://docs.unity3d.com/ScriptReference/Mesh.html)</a>	<i>mesh</i>	

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## FindSpanLine(Vector3, Vector3, Vector3, Vector3, float)

Finds a point along the span line of a quad at the specified percentage.

## Declaration

```
public static Vector3 FindSpanLine(Vector3 a, Vector3 b, Vector3 c, Vector3 d, float spanPer cent)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>a</i>	First corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>b</i>	Second corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>c</i>	Third corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>d</i>	Fourth corner.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	<i>spanPercent</i>	Position along span (0-1).

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	Point on span line.

## InverseTransformPointUnscaled(Transform, Vector3)

Transforms a point from world to local space without applying scale.

### Declaration

```
public static Vector3 InverseTransformPointUnscaled(this Transform transform, Vector3 position)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform (https://docs.unity3d.com/ScriptReference/Transform.html)</a>	<i>transform</i>	Transform to use.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>position</i>	World position.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	Local position without scale.

## LinePlaneIntersection(Vector3, Vector3, Vector3, Vector3)

Finds the intersection point between a line and a plane.

### Declaration

```
public static Vector3 LinePlaneIntersection(Vector3 planePoint, Vector3 planeNormal, Vector3 linePoint, Vector3 lineDirection)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>planePoint</i>	Point on the plane.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>planeNormal</i>	Normal vector of the plane.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>linePoint</i>	Point on the line.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>lineDirection</i>	Direction of the line.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	Intersection point, or Vector3.zero if parallel.

## MeshArea(Mesh)

Calculates area of a complete mesh.

### Declaration

```
public static float MeshArea(Mesh mesh)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh (https://docs.unity3d.com/ScriptReference/Mesh.html)</a>	<i>mesh</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## NearEqual(Vector3, Vector3, float)

Checks if two Vector3 values are approximately equal within a threshold. Uses squared magnitude for performance.

### Declaration

```
public static bool NearEqual(this Vector3 a, Vector3 b, float threshold = 0.01)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>a</i>	First vector.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>b</i>	Second vector.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>threshold</i>	Maximum squared distance to consider equal.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if vectors are within threshold distance.

## NearestPointOnLine(Vector3, Vector3, Vector3)

Finds the nearest point on an infinite line to a given point.

### Declaration

```
public static Vector3 NearestPointOnLine(Vector3 linePnt, Vector3 lineDir, Vector3 pnt)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>linePnt</i>	Point on the line.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>lineDir</i>	Direction of the line.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>pnt</i>	Point to find nearest point from.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Nearest point on the line.

## NearlyEqual(float, float, double)

Checks if two float values are nearly equal within an epsilon threshold.

### Declaration

```
public static bool NearlyEqual(this float a, float b, double epsilon)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>a</i>	First value.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>b</i>	Second value.
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).	<i>epsilon</i>	Maximum difference to consider equal.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if values are within epsilon.

## Perpendicular(Vector3)

Calculates a perpendicular vector to the given vector.

### Declaration

```
public static Vector3 Perpendicular(this Vector3 v)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>v</i>	Input vector.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Perpendicular vector.

## PointInTriangle(Vector3, Vector3, Vector3, Vector3, float)

Checks if a point lies inside a triangle.

### Declaration

```
public static bool PointInTriangle(Vector3 A, Vector3 B, Vector3 C, Vector3 P, float dotThreshold = 0.001)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>A</i>	First triangle vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>B</i>	Second triangle vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>C</i>	Third triangle vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>P</i>	Point to test.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>dotThreshold</i>	Tolerance for point-on-plane test.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if point is inside triangle.

## PointIsInsideRect(Vector2)

Checks if a 2D point is inside the screen rectangle.

### Declaration

```
public static bool PointIsInsideRect(Vector2 point)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	<i>point</i>	Point to check.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if point is inside screen bounds.

## ProjectedMeshArea(Mesh, Vector3)

Calculates area of a mesh as viewed from the direction vector.

### Declaration

```
public static float ProjectedMeshArea(Mesh mesh, Vector3 direction)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>mesh</i>	
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>direction</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## QuadLerp(Vector3, Vector3, Vector3, Vector3, float, float)

Performs bilinear interpolation on a quad defined by four points.

### Declaration

```
public static Vector3 QuadLerp(Vector3 a, Vector3 b, Vector3 c, Vector3 d, float u, float v)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>a</i>	First corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>b</i>	Second corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>c</i>	Third corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>d</i>	Fourth corner.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>u</i>	U parameter (0-1).
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>v</i>	V parameter (0-1).

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Interpolated point.

## QuaternionMagnitude(Quaternion)

Calculates the magnitude of a quaternion.

### Declaration

```
public static float QuaternionMagnitude(Quaternion q)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>q</i>	Quaternion.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Magnitude.

## RectArea(Vector3, Vector3, Vector3, Vector3)

Calculates the area of a rectangle from four corner points.

### Declaration

```
public static float RectArea(Vector3 p1, Vector3 p2, Vector3 p3, Vector3 p4)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p1</i>	First corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p2</i>	Second corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p3</i>	Third corner.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p4</i>	Fourth corner.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Area of the rectangle.

## RotatePointAroundPivot(Vector3, Vector3, Vector3)

Rotates a point around a pivot by the specified angles.

### Declaration

```
public static Vector3 RotatePointAroundPivot(Vector3 point, Vector3 pivot, Vector3 angles)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>point</i>	Point to rotate.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>pivot</i>	Pivot point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>angles</i>	Euler angles for rotation.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Rotated point.

## RoundToStep(int, int)

Rounds a value to the nearest multiple of step.

### Declaration

```
public static float RoundToStep(int value, int step)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	<i>value</i>	Value to round.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	<i>step</i>	Step size.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Rounded value.

## RoundToStep(float, float)

Rounds a value to the nearest multiple of step.

### Declaration

```
public static float RoundToStep(float value, float step)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>value</i>	Value to round.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>step</i>	Step size.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Rounded value.

## RoundedMax(Vector3)

Returns a vector with only the largest component preserved (rounded to 1 or -1), others set to 0.

### Declaration

```
public static Vector3 RoundedMax(this Vector3 v)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>v</i>	Input vector.

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	Vector with dominant axis isolated.

## SignedVolumeOfTriangle(Vector3, Vector3, Vector3)

Calculates the signed volume contribution of a triangle relative to the origin.

### Declaration

```
public static float SignedVolumeOfTriangle(Vector3 p1, Vector3 p2, Vector3 p3)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>p1</i>	First vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>p2</i>	Second vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>p3</i>	Third vertex.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> )	Signed volume.

## SquareDistance(Vector3, Vector3)

Calculates squared distance between two points. Faster than regular distance.

### Declaration

```
public static float SquareDistance(Vector3 a, Vector3 b)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>a</i>	First point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>b</i>	Second point.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Squared distance.

## TransformPointUnscaled(Transform, Vector3)

Transforms a point from local to world space without applying scale.

### Declaration

```
public static Vector3 TransformPointUnscaled(this Transform transform, Vector3 position)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform (https://docs.unity3d.com/ScriptReference/Transform.html)</a>	<i>transform</i>	Transform to use.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>position</i>	Local position.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	World position without scale.

## TriArea(Vector3, Vector3, Vector3)

Calculates area of a single triangle from it's three points.

### Declaration

```
public static float TriArea(Vector3 p1, Vector3 p2, Vector3 p3)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>p1</i>	
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>p2</i>	
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>p3</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## TriArea(Vector3, Vector3, Vector3, Vector3)

### Declaration

```
public static float TriArea(Vector3 p1, Vector3 p2, Vector3 p3, Vector3 view)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p1</i>	
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p2</i>	
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p3</i>	
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>view</i>	

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Vector3Abs(Vector3)

Returns a vector with absolute values of all components.

### Declaration

```
public static Vector3 Vector3Abs(Vector3 v)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>v</i>	Input vector.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Vector with absolute values.

## Vector3Lerp(Vector3, Vector3, float)

Linear interpolation between two vectors with value clamping.

### Declaration

```
public static Vector3 Vector3Lerp(Vector3 v1, Vector3 v2, float value)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>v1</i>	Start vector.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>v2</i>	End vector.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> )	<i>value</i>	Interpolation value (0-1).

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	Interpolated vector.

## Vector3OneOver(Vector3)

Returns a vector with reciprocal values (1/x, 1/y, 1/z).

### Declaration

```
public static Vector3 Vector3OneOver(Vector3 v)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	<i>v</i>	Input vector.

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	Vector with reciprocal values.

## Vector3RoundToInt(Vector3)

Rounds all components of a vector to nearest integer.

### Declaration

```
public static Vector3 Vector3RoundToInt(Vector3 v)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>v</i>	Input vector.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	Rounded vector.

## VolumeOfMesh(Mesh)

Calculates the volume enclosed by a mesh.

### Declaration

```
public static float VolumeOfMesh(Mesh mesh)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>mesh</i>	Mesh to calculate volume for.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Volume of the mesh.

# Class PIDController

Proportional-Integral-Derivative controller for smooth value regulation. Used for automated control systems like cruise control, stability systems, and steering assistance.

## Inheritance

---

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ PIDController

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class PIDController
```

## Remarks

PID controllers combine three control strategies:

- Proportional: Reacts to current error
- Integral: Eliminates accumulated error over time
- Derivative: Anticipates future error based on rate of change Tune the three gain values to achieve desired response characteristics.

## Constructors

### **PIDController(float, float, float, float, float)**

Creates a new PID controller with specified gains and output limits.

## Declaration

```
public PIDController(float gainProportional, float gainIntegral, float gainDerivative, float outputMin, float outputMax)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>gainProportional</i>	Proportional gain (Kp). Higher values increase response to current error.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>gainIntegral</i>	Integral gain (Ki). Higher values eliminate steady-state error faster.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>gainDerivative</i>	Derivative gain (Kd). Higher values dampen oscillations.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>outputMin</i>	Minimum output value.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>outputMax</i>	Maximum output value.

## Fields

### maxValue

Maximum output value. Output will be clamped to this value.

#### Declaration

```
public float maxValue
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### minValue

Minimum output value. Output will be clamped to this value.

#### Declaration

```
public float minValue
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Properties

## GainDerivative

The derivative term is proportional to the rate of change of the error

### Declaration

```
public float GainDerivative { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## GainIntegral

The integral term is proportional to both the magnitude of the error and the duration of the error

### Declaration

```
public float GainIntegral { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## GainProportional

The proportional term produces an output value that is proportional to the current error value

### Declaration

```
public float GainProportional { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### Remarks

Tuning theory and industrial practice indicate that the proportional term should contribute the bulk of the output change.

## IntegralTerm

Adjustment made by considering the accumulated error over time

### Declaration

```
public float IntegralTerm { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

### Remarks

An alternative formulation of the integral action, is the proportional-summation-difference used in discrete-time systems

## ProcessVariable

The current value

### Declaration

```
public float ProcessVariable { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## ProcessVariableLast

The last reported value (used to calculate the rate of change)

### Declaration

```
public float ProcessVariableLast { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## SetPoint

The desired value

### Declaration

```
public float SetPoint { get; set; }
```

### Property Value

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Methods

### ControlVariable(float)

The controller output

### Declaration

```
public float ControlVariable(float timeSinceLastUpdate)
```

### Parameters

Type	Name	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>timeSinceLastUpdate</i>	timespan of the elapsed time since the previous time that ControlVariable was called

### Returns

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Value of the variable that needs to be controlled

# Class QuaternionExtensions

Extension methods for advanced Quaternion operations. Provides interpolation methods with control over rotation direction.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ QuaternionExtensions

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class QuaternionExtensions
```

## Methods

### Add(Quaternion, Quaternion)

Adds two quaternions component-wise.

#### Declaration

```
public static Quaternion Add(Quaternion p, Quaternion q)
```

#### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	$p$	First quaternion.
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	$q$	Second quaternion.

#### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	Component-wise sum.

### Lerp(Quaternion, Quaternion, float, bool)

Linear interpolation between two quaternions with optional short/long path control. Unlike Unity's Quaternion.Lerp, this allows choosing rotation direction.

## Declaration

```
public static Quaternion Lerp(Quaternion p, Quaternion q, float t, bool shortWay)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>p</i>	Starting rotation.
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>q</i>	Target rotation.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>t</i>	Interpolation factor (0 to 1).
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>shortWay</i>	True for shortest rotation path, false for longest.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	Interpolated quaternion.

## ScalarMultiply(Quaternion, float)

Multiplies all components of a quaternion by a scalar value.

## Declaration

```
public static Quaternion ScalarMultiply(Quaternion input, float scalar)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>input</i>	Input quaternion.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>scalar</i>	Scalar multiplier.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	Scaled quaternion.

## Slerp(Quaternion, Quaternion, float, bool)

Spherical linear interpolation between two quaternions with optional short/long path control. Provides smooth rotation interpolation with control over rotation direction.

### Declaration

```
public static Quaternion Slerp(Quaternion p, Quaternion q, float t, bool shortWay)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>p</i>	Starting rotation.
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	<i>q</i>	Target rotation.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>t</i>	Interpolation factor (0 to 1).
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>shortWay</i>	True for shortest rotation path, false for longest.

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">Quaternion</a> ( <a href="https://docs.unity3d.com/ScriptReference/Quaternion.html">https://docs.unity3d.com/ScriptReference/Quaternion.html</a> ).	Interpolated quaternion.

# Class UnitConverter

Static utility class for converting between various units of measurement. Includes conversions for distance, speed, fuel efficiency, and angular velocity.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ UnitConverter

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Utility](#) ([NWH.Common.Utility.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class UnitConverter
```

## Methods

### AngularVelocityToRPM(float)

Converts angular velocity (rad/s) to rotations per minute.

#### Declaration

```
public static float AngularVelocityToRPM(float angularVelocity)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>angularVelocity</i>	Angular velocity in rad/s.

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Rotations per minute (RPM).

### Inch\_To\_Meter(float)

Converts inches to meters.

#### Declaration

```
public static float Inch_To_Meter(float inch)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>inch</i>	Value in inches.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Value in meters.

## KmlToL100km(float)

km/l to l/100km

### Declaration

```
public static float KmlToL100km(float kml)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>kml</i>	Fuel efficiency in km/l.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Fuel efficiency in l/100km.

## KmlToMpg(float)

km/l to mpg

### Declaration

```
public static float KmlToMpg(float kml)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>kml</i>	Fuel efficiency in km/l.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Fuel efficiency in mpg.

## L100kmToKml(float)

l/100km to km/l

### Declaration

```
public static float L100kmToKml(float l100km)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	<i>l100km</i>	Fuel efficiency in l/100km.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Fuel efficiency in km/l.

## L100kmToMpg(float)

l/100km to mpg

### Declaration

```
public static float L100kmToMpg(float l100km)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	<i>l100km</i>	Fuel efficiency in l/100km.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Fuel efficiency in mpg.

## Meter\_To\_Inch(float)

Converts meters to inches.

### Declaration

```
public static float Meter_To_Inch(float meters)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>meters</i>	Value in meters.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Value in inches.

## MpgToKml(float)

mpg to km/l

### Declaration

```
public static float MpgToKml(float mpg)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>mpg</i>	Fuel efficiency in mpg.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Fuel efficiency in km/l.

## MpgToL100km(float)

mpg to l/100km

### Declaration

```
public static float MpgToL100km(float mpg)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>mpg</i>	Fuel efficiency in mpg.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Fuel efficiency in l/100km.

## MphToKph(float)

miles/h to km/h

### Declaration

```
public static float MphToKph(float value)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>value</i>	Speed in mph.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in km/h.

## MpsToKph(float)

m/s to km/h

### Declaration

```
public static float MpsToKph(float value)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>value</i>	Speed in m/s.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in km/h.

## MpsToMph(float)

m/s to miles/h

### Declaration

```
public static float MpsToMph(float value)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>value</i>	Speed in m/s.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in mph.

## RPMToAngularVelocity(float)

Converts rotations per minute to angular velocity (rad/s).

### Declaration

```
public static float RPMToAngularVelocity(float RPM)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>RPM</i>	Rotations per minute.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Angular velocity in rad/s.

## Speed\_kmhToMph(float)

Converts km/h to mph.

### Declaration

```
public static float Speed_kmhToMph(float kmh)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>kmh</i>	Speed in km/h.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in mph.

## Speed\_kmhToMs(float)

Converts km/h to m/s.

### Declaration

```
public static float Speed_kmhToMs(float kmh)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>kmh</i>	Speed in km/h.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in m/s.

## Speed\_mphToKmh(float)

Converts mph to km/h.

### Declaration

```
public static float Speed_mphToKmh(float mph)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>mph</i>	Speed in mph.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in km/h.

## Speed\_mphToMs(float)

Converts mph to m/s.

### Declaration

```
public static float Speed_mphToMs(float mph)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>mph</i>	Speed in mph.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in m/s.

## Speed\_msToKph(float)

Converts m/s to km/h.

### Declaration

```
public static float Speed_msToKph(float ms)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>ms</i>	Speed in m/s.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in km/h.

## Speed\_msToMph(float)

Converts m/s to mph.

### Declaration

```
public static float Speed_msToMph(float ms)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>ms</i>	Speed in m/s.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Speed in mph.



# Namespace NWH.Common.Vehicles

## Classes

### **FollowVehicleState (NWH.Common.Vehicles.FollowVehicleState.html)**

Automatically enables/disables a GameObject based on parent vehicle's active state. Useful for optimizing performance by disabling effects, audio, or visuals when a vehicle is inactive.

### **ShowInSettings (NWH.Common.Vehicles.ShowInSettings.html)**

Attribute that marks a field to be displayed in runtime settings UI. Allows players to adjust vehicle parameters during gameplay.

### **ShowInTelemetry (NWH.Common.Vehicles.ShowInTelemetry.html)**

Attribute that marks a field or property to be displayed in the runtime telemetry UI. Used for monitoring vehicle parameters during gameplay and debugging.

### **Vehicle (NWH.Common.Vehicles.Vehicle.html)**

Base class for all NWH vehicles including VehiclePhysics2.VehicleController and DWP2.AdvancedShipController.

### **VehicleReflectionProbe (NWH.Common.Vehicles.VehicleReflectionProbe.html)**

Manages vehicle reflection probe settings, switching between baked and realtime modes based on vehicle activity to optimize performance.

## Enums

### **VehicleReflectionProbe.ProbeType (NWH.Common.Vehicles.VehicleReflectionProbe.ProbeType.html)**

Type of reflection probe to use.

# Class FollowVehicleState

Automatically enables/disables a GameObject based on parent vehicle's active state. Useful for optimizing performance by disabling effects, audio, or visuals when a vehicle is inactive.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ FollowVehicleState

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Vehicles](#) ([NWH.Common.Vehicles.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[DefaultExecutionOrder(21)]  
public class FollowVehicleState : MonoBehaviour
```

## Remarks

Attach this component to child objects that should only be active when the vehicle is being simulated. When the vehicle is put to sleep (disabled), attached objects are also disabled, saving processing time for effects that wouldn't be visible anyway.

# Class ShowInSettings

Attribute that marks a field to be displayed in runtime settings UI. Allows players to adjust vehicle parameters during gameplay.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Attribute](https://learn.microsoft.com/dotnet/api/system.attribute) (<https://learn.microsoft.com/dotnet/api/system.attribute>).
- ↳ ShowInSettings

**Namespace:** [NWH \(NWH.html\)](#).[Common \(NWH.Common.html\)](#).[Vehicles \(NWH.Common.Vehicles.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
[AttributeUsage(AttributeTargets.Field)]  
public class ShowInSettings : Attribute
```

## Constructors

### ShowInSettings()

#### Declaration

```
public ShowInSettings()
```

### ShowInSettings(float, float, float)

Creates a settings attribute with specified min, max, and step values.

#### Declaration

```
public ShowInSettings(float min, float max, float step = 0.1)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>min</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>max</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>step</i>	

### ShowInSettings(string)

Creates a settings attribute with a custom display name.

## Declaration

```
public ShowInSettings(string name)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>name</i>	

## ShowInSettings(string, float, float, float)

Creates a settings attribute with custom name and value constraints.

## Declaration

```
public ShowInSettings(string name, float min, float max, float step = 0.1)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>name</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>min</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>max</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>step</i>	

## Fields

### max

Maximum value for the setting slider.

## Declaration

```
public float max
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### min

Minimum value for the setting slider.

## Declaration

```
public float min
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## name

Display name for the setting in the UI.

## Declaration

```
public string name
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	

## step

Increment step for the slider. Smaller values allow finer adjustment.

## Declaration

```
public float step
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Class ShowInTelemetry

Attribute that marks a field or property to be displayed in the runtime telemetry UI. Used for monitoring vehicle parameters during gameplay and debugging.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Attribute](https://learn.microsoft.com/dotnet/api/system.attribute) (<https://learn.microsoft.com/dotnet/api/system.attribute>).
- ↳ ShowInTelemetry

Namespace: [NWH \(NWH.html\)](#).[Common \(NWH.Common.html\)](#).[Vehicles \(NWH.Common.Vehicles.html\)](#)

Assembly: NWH.DWP2.dll

## Syntax

```
[AttributeUsage(AttributeTargets.All)]  
public class ShowInTelemetry : Attribute
```

## Constructors

### ShowInTelemetry(float, float, string, string, int)

Creates a ShowInTelemetry attribute with optional parameters.

#### Declaration

```
public ShowInTelemetry(float min = NaN, float max = NaN, string format = null, string unit =  
null, int priority = 1)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>min</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>max</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>format</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>unit</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	<i>priority</i>	

## Properties

### Format

Format string for displaying the value (e.g., "0.00", "0.0").

## Declaration

```
public string Format { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	

## Max

Maximum value for the field (used for progress bar visualization).

## Declaration

```
public float Max { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Min

Minimum value for the field (used for progress bar visualization).

## Declaration

```
public float Min { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Priority

Display priority. 0 = highest (always visible), 3 = lowest (detailed info).

## Declaration

```
public int Priority { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## Unit

Unit of measurement (e.g., "km/h", "RPM", "N", "").

## Declaration

```
public string Unit { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	

# Class Vehicle

Base class for all NWH vehicles including VehiclePhysics2.VehicleController and DWP2.AdvancedShipController.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ Vehicle
  - ↳ [AdvancedShipController](#) ([NWH.DWP2.ShipController.AdvancedShipController.html](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Vehicles](#) ([NWH.Common.Vehicles.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[DisallowMultipleComponent]
[RequireComponent(typeof(Rigidbody))]
public abstract class Vehicle : MonoBehaviour
```

## Fields

### ActiveVehicles

#### Declaration

```
public static List<Vehicle> ActiveVehicles
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> )< <a href="#">Vehicle</a> ( <a href="#">NWH.Common.Vehicles.Vehicle.html</a> )>	

### INPUT\_DEADZONE

Any input below this value will register as no input.

#### Declaration

```
public const float INPUT_DEADZONE = 0.02
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## KINDA\_SMALL\_NUMBER

Like SMALL\_NUMBER but a bit bigger.

### Declaration

```
public const float KINDA_SMALL_NUMBER = 0.01
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## SMALL\_NUMBER

Anything below this can be considered 0.

### Declaration

```
public const float SMALL_NUMBER = 1E-05
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## SPEED\_DEADZONE

Any speed below this value will register as no speed.

### Declaration

```
public const float SPEED_DEADZONE = 0.2
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## isPlayerControllable

True if the vehicle can be driven by the player. False if the vehicle is passive (such as a trailer). A vehicle that has isPlayerControllable can be the ActiveVehicle.

### Declaration

```
public bool isPlayerControllable
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## onActiveVehicleChanged

Called when active vehicle is changed. First parameter is the previously active vehicle and the second parameter is the currently active vehicle (at the time of the callback). Params can be null.

### Declaration

```
public static UnityEvent<Vehicle, Vehicle> onActiveVehicleChanged
```

### Field Value

Type	Description
<a href="#">UnityEvent&lt;Vehicle (NWH.Common.Vehicles.Vehicle.html), Vehicle (NWH.Common.Vehicles.Vehicle.html)&gt;</a>	

## onCameraEnterVehicle

Called when the camera enters the vehicle.

### Declaration

```
public UnityEvent onCameraEnterVehicle
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ).	

## onCameraExitVehicle

Called when the camera exits the vehicle.

## Declaration

```
public UnityEvent onCameraExitVehicle
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ),	

## onDisable

Called when vehicle is put to sleep.

## Declaration

```
[Tooltip("    Called when vehicle is put to sleep.")]  
[NonSerialized]  
public UnityEvent onDisable
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ),	

## onEnable

Called when vehicle is woken up.

## Declaration

```
[Tooltip("    Called when vehicle is woken up.")]  
[NonSerialized]  
public UnityEvent onEnable
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ),	

## onMultiplayerStatusChanged

Invoked when MultiplayerIsRemote value gets changed. Is true if remote.

## Declaration

```
public UnityEvent<bool> onMultiplayerStatusChanged
```

## Field Value

Type	Description
UnityEvent< <a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> >	

## vehicleRigidbody

Cached value of vehicle rigidbody.

### Declaration

```
[Tooltip("    Cached value of vehicle rigidbody.")]  
[NonSerialized]  
public Rigidbody vehicleRigidbody
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Rigidbody.html">Rigidbody</a>	

## vehicleTransform

Cached value of vehicle transform.

### Declaration

```
[Tooltip("    Cached value of vehicle transform.")]  
[NonSerialized]  
public Transform vehicleTransform
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a>	

# Properties

## ActiveVehicle

### Declaration

```
public static Vehicle ActiveVehicle { get; }
```

## Property Value

Type	Description
<a href="#">Vehicle (NWH.Common.Vehicles.Vehicle.html)</a>	

## AngularVelocity

Cached angular velocity of the vehicle.

### Declaration

```
public Vector3 AngularVelocity { get; protected set; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## AngularVelocityMagnitude

Cached angular velocity magnitude of the vehicle.

### Declaration

```
public float AngularVelocityMagnitude { get; protected set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## CameraInsideVehicle

True when camera is inside vehicle (cockpit, cabin, etc.). Set by the 'CameraInsideVehicle' component. Used for audio effects.

### Declaration

```
public bool CameraInsideVehicle { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	

## LocalAcceleration

Cached acceleration in local coordinates (z-forward)

### Declaration

```
public Vector3 LocalAcceleration { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## LocalForwardAcceleration

Cached acceleration in forward direction in local coordinates (z-forward).

### Declaration

```
public float LocalForwardAcceleration { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## LocalForwardVelocity

Cached velocity in forward direction in local coordinates (z-forward).

### Declaration

```
public float LocalForwardVelocity { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## LocalVelocity

Cached velocity in m/s in local coordinates.

## Declaration

```
[ShowInTelemetry(NaN, NaN, null, null, 1)]  
public Vector3 LocalVelocity { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## MultiplayerIsRemote

True if the vehicle is a client (remote) and not simulated. If true the input is expected to be synced through the network.

## Declaration

```
public bool MultiplayerIsRemote { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Speed

Cached speed of the vehicle in the forward direction. ALWAYS POSITIVE. For positive/negative version use SpeedSigned.

## Declaration

```
[ShowInTelemetry(NaN, NaN, "0.0", "m/s", 1)]  
public float Speed { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## SpeedSigned

Cached speed of the vehicle in the forward direction. Can be positive (forward) or negative (reverse). Equal to LocalForwardVelocity.

## Declaration

```
[ShowInTelemetry(NaN, NaN, "0.0", "m/s", 1)]  
public float SpeedSigned { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Velocity

Cached velocity of the vehicle in world coordinates.

## Declaration

```
public Vector3 Velocity { get; protected set; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## VelocityMagnitude

Cached velocity magnitude of the vehicle in world coordinates.

## Declaration

```
public float VelocityMagnitude { get; protected set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Methods

### Awake()

## Declaration

```
public virtual void Awake()
```

## FixedUpdate()

### Declaration

```
public virtual void FixedUpdate()
```

## OnDisable()

### Declaration

```
public virtual void OnDisable()
```

## OnEnable()

### Declaration

```
public virtual void OnEnable()
```

# Class VehicleReflectionProbe

Manages vehicle reflection probe settings, switching between baked and realtime modes based on vehicle activity to optimize performance.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ VehicleReflectionProbe

**Namespace:** [NWH](#) ([NWH.html](#)), [Common](#) ([NWH.Common.html](#)), [Vehicles](#) ([NWH.Common.Vehicles.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(ReflectionProbe))]  
[DefaultExecutionOrder(19)]  
public class VehicleReflectionProbe : MonoBehaviour
```

## Remarks

Realtime reflection probes are expensive. This component switches to cheaper baked probes when the vehicle is inactive, maintaining visual quality while improving performance. The probe is automatically re-baked when the vehicle becomes inactive to capture the current environment state.

## Fields

### asleepProbeType

Probe type to use when vehicle is inactive/sleeping. Default is Baked for performance.

#### Declaration

```
public VehicleReflectionProbe.ProbeType asleepProbeType
```

#### Field Value

Type	Description
<a href="#">VehicleReflectionProbe</a> ( <a href="#">NWH.Common.Vehicles.VehicleReflectionProbe.html</a> ), <a href="#">ProbeType</a> ( <a href="#">NWH.Common.Vehicles.VehicleReflectionProbe.ProbeType.html</a> ).	

### awakeProbeType

Probe type to use when vehicle is active. Default is Realtime for accurate reflections.

## Declaration

```
public VehicleReflectionProbe.ProbeType awakeProbeType
```

## Field Value

Type	Description
<a href="#">VehicleReflectionProbe</a> ( <a href="#">NWH.Common.Vehicles.VehicleReflectionProbe.html</a> ), <a href="#">ProbeType</a> ( <a href="#">NWH.Common.Vehicles.VehicleReflectionProbe.ProbeType.html</a> ).	

## bakeOnSleep

Automatically bake the probe when vehicle becomes inactive to capture environment state.

## Declaration

```
public bool bakeOnSleep
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## bakeOnStart

Bake the probe once on start for initial environment capture.

## Declaration

```
public bool bakeOnStart
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Enum VehicleReflectionProbe.ProbeType

Type of reflection probe to use.

**Namespace:** [NWH \(NWH.html\)](#), [Common \(NWH.Common.html\)](#), [Vehicles \(NWH.Common.Vehicles.html\)](#),

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum VehicleReflectionProbe.ProbeType
```

## Fields

Name	Description
Baked	Pre-rendered cubemap, low cost but static.
Realtime	Updates every frame, high cost but accurate.

# Namespace NWH.DWP2

## Classes

### **GeometryUtils (NWH.DWP2.GeometryUtils.html)**

Utility class for geometric calculations used in buoyancy simulation. Provides methods for calculating centroids, areas, and surface-weighted centers of triangles and quadrilaterals.

### **UnderwaterFog\_ (NWH.DWP2.UnderwaterFog.html)**

Simple utility script that enables Unity fog when the main camera goes underwater. Attach this script to any GameObject in the scene and assign the water surface transform.

# Class GeometryUtils

Utility class for geometric calculations used in buoyancy simulation. Provides methods for calculating centroids, areas, and surface-weighted centers of triangles and quadrilaterals.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)  
↳ GeometryUtils

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)),

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class GeometryUtils
```

## Methods

### CalculateCentroid(Vector3, Vector3, Vector3, Vector3)

Calculates the centroid of a quadrilateral defined by four points.

#### Declaration

```
public static Vector3 CalculateCentroid(Vector3 pointA, Vector3 pointB, Vector3 pointC, Vector3 pointD)
```

#### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>pointA</i>	First corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>pointB</i>	Second corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>pointC</i>	Third corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>pointD</i>	Fourth corner point.

#### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	The centroid position of the quadrilateral.

### CalculateQuadrilateralArea(Vector3, Vector3, Vector3, Vector3)

Calculates the surface area of a quadrilateral by dividing it into two triangles.

## Declaration

```
public static float CalculateQuadrilateralArea(Vector3 pointA, Vector3 pointB, Vector3 pointC, Vector3 pointD)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointA</i>	First corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointB</i>	Second corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointC</i>	Third corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointD</i>	Fourth corner point.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Total surface area of the quadrilateral.

## CalculateSurfaceWeightedCenter(Vector3, Vector3, Vector3, Vector3)

Calculates the surface-weighted center of a quadrilateral. The center is weighted by the area of the two triangles that make up the quadrilateral.

## Declaration

```
public static Vector3 CalculateSurfaceWeightedCenter(Vector3 pointA, Vector3 pointB, Vector3 pointC, Vector3 pointD)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointA</i>	First corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointB</i>	Second corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointC</i>	Third corner point.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointD</i>	Fourth corner point.

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	The surface-weighted center position.

## CalculateTriangleArea(Vector3, Vector3, Vector3)

Calculates the surface area of a triangle using the cross product method.

## Declaration

```
public static float CalculateTriangleArea(Vector3 pointA, Vector3 pointB, Vector3 pointC)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointA</i>	First vertex of the triangle.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointB</i>	Second vertex of the triangle.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>pointC</i>	Third vertex of the triangle.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Surface area of the triangle.

# Class UnderwaterFog

Simple utility script that enables Unity fog when the main camera goes underwater. Attach this script to any GameObject in the scene and assign the water surface transform.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ UnderwaterFog

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class UnderwaterFog : MonoBehaviour
```

## Fields

### waterTransform

Transform of the water surface. Used to determine if camera is underwater.

### Declaration

```
public Transform waterTransform
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

# Namespace NWH.DWP2.DemoContent

## Classes

### **CubeGridSpawner (NWH.DWP2.DemoContent.CubeGridSpawner.html)**

Demo script that spawns a 3D grid of cubes with WaterObjects attached. Used for stress-testing and demonstrating the buoyancy system with multiple objects.

### **WaterObjectFromScript (NWH.DWP2.DemoContent.WaterObjectFromScript.html)**

An example on how to add WaterObject to an existing object at runtime.

# Class CubeGridSpawner

Demo script that spawns a 3D grid of cubes with WaterObjects attached. Used for stress-testing and demonstrating the buoyancy system with multiple objects.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ CubeGridSpawner

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [DemoContent](#) ([NWH.DWP2.DemoContent.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class CubeGridSpawner : MonoBehaviour
```

## Fields

### depth

Spacing between cubes on the Z axis.

#### Declaration

```
public float depth
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### height

Spacing between cubes on the Y axis.

#### Declaration

```
public float height
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## width

Spacing between cubes on the X axis.

### Declaration

```
public float width
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## xResolution

Number of cubes to spawn along the X axis.

### Declaration

```
public int xResolution
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## yResolution

Number of cubes to spawn along the Y axis.

### Declaration

```
public int yResolution
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## zResolution

Number of cubes to spawn along the Z axis.

### Declaration

```
public int zResolution
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a> .	

# Class WaterObjectFromScript

An example on how to add WaterObject to an existing object at runtime.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ WaterObjectFromScript

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [DemoContent](#) ([NWH.DWP2.DemoContent.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class WaterObjectFromScript : MonoBehaviour
```

# Namespace NWH.DWP2.MeshDecimation

## Classes

### **Comparer (NWH.DWP2.MeshDecimation.Comparer.html)**

Comparer for sorting vertices by their edge collapse cost during mesh decimation.

### **History\_ (NWH.DWP2.MeshDecimation.History.html)**

Tracks mesh decimation history for undo/redo operations during progressive mesh simplification.

### **MeshDecimate (NWH.DWP2.MeshDecimation.MeshDecimate.html)**

Progressive mesh decimation implementation using edge collapse algorithm. Reduces mesh complexity while preserving overall shape and texture coordinates.

### **Tri (NWH.DWP2.MeshDecimation.Tri.html)**

Represents a triangle in the mesh decimation algorithm. Stores triangle vertices, normals, UVs, and adjacency information.

### **Vert (NWH.DWP2.MeshDecimation.Vert.html)**

Represents a vertex in the mesh decimation algorithm. Stores vertex data and relationships for edge collapse operations.

# Class Comparer

Comparer for sorting vertices by their edge collapse cost during mesh decimation.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ Comparer

## Implements

[IComparer](https://learn.microsoft.com/dotnet/api/system.collections.icomparer) (<https://learn.microsoft.com/dotnet/api/system.collections.icomparer>).

**Namespaces:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MeshDecimation](#) ([NWH.DWP2.MeshDecimation.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class Comparer : IComparer
```

## Methods

### Compare(object, object)

Compares two vertices based on their edge collapse cost.

#### Declaration

```
public int Compare(object x, object y)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.object">object</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.object">https://learn.microsoft.com/dotnet/api/system.object</a> ).	<i>x</i>	First vertex to compare.
<a href="https://learn.microsoft.com/dotnet/api/system.object">object</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.object">https://learn.microsoft.com/dotnet/api/system.object</a> ).	<i>y</i>	Second vertex to compare.

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	-1 if <i>x</i> has lower cost, 0 if equal, 1 if <i>x</i> has higher cost.

## Implements

[IComparer](https://learn.microsoft.com/dotnet/api/system.collections.icomparer) (<https://learn.microsoft.com/dotnet/api/system.collections.icomparer>).



# Class History

Tracks mesh decimation history for undo/redo operations during progressive mesh simplification.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ History

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MeshDecimation](#) ([NWH.DWP2.MeshDecimation.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class History
```

## Fields

### id

Unique identifier for this history entry.

#### Declaration

```
public int id
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

### removedTriangles

List of triangle indices that were removed during this step.

#### Declaration

```
public List<int> removedTriangles
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> )< <a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> )>	

## replacedVertex

List of vertex replacement operations performed during this step.

### Declaration

```
public List<ArrayList> replacedVertex
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> ).< <a href="https://learn.microsoft.com/dotnet/api/system.collections.arraylist">ArrayList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.arraylist">https://learn.microsoft.com/dotnet/api/system.collections.arraylist</a> ).>	

## Methods

### RemovedTriangle(int)

Records a triangle removal operation.

#### Declaration

```
public void RemovedTriangle(int f)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	<i>f</i>	Index of the triangle that was removed.

### ReplaceVertex(int, int, int, Vector3, Vector2, int, Vector3, Vector2)

Records a vertex replacement operation including original and new vertex data.

#### Declaration

```
public void ReplaceVertex(int f, int u, int v, Vector3 normal, Vector2 uv, int newV, Vector3 newNormal, Vector2 newUv)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>f</i>	Face index.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>u</i>	Original vertex index in the triangle.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>v</i>	Vertex ID being replaced.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>normal</i>	Original vertex normal.
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	<i>uv</i>	Original texture coordinates.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>newV</i>	New vertex ID.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>newNormal</i>	New vertex normal.
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	<i>newUv</i>	New texture coordinates.

# Class MeshDecimate

Progressive mesh decimation implementation using edge collapse algorithm. Reduces mesh complexity while preserving overall shape and texture coordinates.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ MeshDecimate

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MeshDecimation](#) ([NWH.DWP2.MeshDecimation.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class MeshDecimate
```

## Fields

### bRecalculateNormals

Whether to recalculate smooth normals after decimation.

#### Declaration

```
public bool bRecalculateNormals
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### finalNormals

Final vertex normals after decimation.

#### Declaration

```
public Vector3[] finalNormals
```

#### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ),[]	

## finalTriangles

Final triangle indices after decimation.

### Declaration

```
public int[] finalTriangles
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> (https://learn.microsoft.com/dotnet/api/system.int32),[]	

## finalUVs

Final texture coordinates after decimation.

### Declaration

```
public Vector2[] finalUVs
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> (https://docs.unity3d.com/ScriptReference/Vector2.html),[]	

## finalVertices

Final vertex positions after decimation.

### Declaration

```
public Vector3[] finalVertices
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> (https://docs.unity3d.com/ScriptReference/Vector3.html),[]	

## lastTarget

Last target vertex count from progressive mesh operation.

### Declaration

```
public int lastTarget
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## lockSelPoint

Whether to lock selected vertices from being collapsed.

### Declaration

```
public bool lockSelPoint
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## lodDataSize

Size in bytes of LOD history data for progressive mesh.

### Declaration

```
public float lodDataSize
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## preCalculateDone

Whether pre-calculation of decimation data has been completed.

### Declaration

```
public bool preCalculateDone
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## ratio

Target ratio of vertices to keep (0.0 to 1.0).

### Declaration

```
public float ratio
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## selectedVertices

List of vertices marked as selected (protected from collapse if locked).

### Declaration

```
public List<Vector3> selectedVertices
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List (https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1)</a> < <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> >	

## smoothAngle

Smoothing angle threshold in degrees for normal calculation.

### Declaration

```
public float smoothAngle
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## Methods

### Calculate(Mesh)

Calculates the decimated mesh at the current ratio. Applies progressive mesh simplification and outputs final geometry arrays. PreCalculate must be called first.

## Declaration

```
public void Calculate(Mesh tmpMesh)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ),	<i>tmpMesh</i>	Mesh reference (used for validation).

## PreCalculate(Mesh)

Pre-calculates all edge collapse operations and builds the progressive mesh history. Must be called once before Calculate can be used.

## Declaration

```
public void PreCalculate(Mesh tmpMesh)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ),	<i>tmpMesh</i>	Input mesh to decimate.

# Class Tri

Represents a triangle in the mesh decimation algorithm. Stores triangle vertices, normals, UVs, and adjacency information.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ Tri

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MeshDecimation](#) ([NWH.DWP2.MeshDecimation.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class Tri
```

## Constructors

### Tri(int, Vert, Vert, Vert, Vector2, Vector2, Vector2)

Initializes a new triangle with vertices, texture coordinates, and establishes vertex relationships.

## Declaration

```
public Tri(int id, Vert v0, Vert v1, Vert v2, Vector2 uv0, Vector2 uv1, Vector2 uv2)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	<i>id</i>	Unique identifier for this triangle.
<a href="#">Vert</a> ( <a href="#">NWH.DWP2.MeshDecimation.Vert.html</a> ).	<i>v0</i>	First vertex.
<a href="#">Vert</a> ( <a href="#">NWH.DWP2.MeshDecimation.Vert.html</a> ).	<i>v1</i>	Second vertex.
<a href="#">Vert</a> ( <a href="#">NWH.DWP2.MeshDecimation.Vert.html</a> ).	<i>v2</i>	Third vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	<i>uv0</i>	Texture coordinate for first vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	<i>uv1</i>	Texture coordinate for second vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	<i>uv2</i>	Texture coordinate for third vertex.

## Fields

### defaultIndex0

Original mesh vertex index for vertex 0.

## Declaration

```
public int defaultIndex0
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## defaultIndex1

Original mesh vertex index for vertex 1.

## Declaration

```
public int defaultIndex1
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## defaultIndex2

Original mesh vertex index for vertex 2.

## Declaration

```
public int defaultIndex2
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## deleted

Whether this triangle has been deleted.

## Declaration

```
public bool deleted
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## id

Unique identifier for this triangle.

### Declaration

```
public int id
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## normal

Face normal vector.

### Declaration

```
public Vector3 normal
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## uv0

Texture coordinate for vertex 0.

### Declaration

```
public Vector2 uv0
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## uv1

Texture coordinate for vertex 1.

### Declaration

```
public Vector2 uv1
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	

## uv2

Texture coordinate for vertex 2.

### Declaration

```
public Vector2 uv2
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	

## v0

First vertex of the triangle.

### Declaration

```
public Vert v0
```

### Field Value

Type	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	

## v1

Second vertex of the triangle.

### Declaration

```
public Vert v1
```

## Field Value

Type	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	

## v2

Third vertex of the triangle.

### Declaration

```
public Vert v2
```

## Field Value

Type	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	

## vn0

Vertex normal for vertex 0.

### Declaration

```
public Vector3 vn0
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## vn1

Vertex normal for vertex 1.

### Declaration

```
public Vector3 vn1
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## vn2

Vertex normal for vertex 2.

### Declaration

```
public Vector3 vn2
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## Methods

### HasVertex(Vert)

Checks if this triangle contains a given vertex.

### Declaration

```
public bool HasVertex(Vert v)
```

### Parameters

Type	Name	Description
<a href="http://NWH.DWP2.MeshDecimation.Vert.html">Vert</a> ( <a href="http://NWH.DWP2.MeshDecimation.Vert.html">NWH.DWP2.MeshDecimation.Vert.html</a> ).	v	Vertex to check.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if the triangle contains the vertex, false otherwise.

### RecalculateAvgNormals(float)

Recalculates averaged vertex normals based on adjacent face normals. Only called when normal recalculation is enabled. Smooths normals even at UV seams.

### Declaration

```
public void RecalculateAvgNormals(float smoothAngleDot)
```

## Parameters

Type	Name	Description
<code>float</code> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<code>smoothAngleDot</code>	Dot product threshold for normal smoothing.

## RecalculateNormal()

Recalculates the face normal using cross product of edge vectors.

### Declaration

```
public void RecalculateNormal()
```

## RemoveTriangle(History)

Removes this triangle and updates vertex relationships. Records the removal in history for potential undo operations.

### Declaration

```
public void RemoveTriangle(History his)
```

## Parameters

Type	Name	Description
<code>History</code> ( <a href="NWH.DWP2.MeshDecimation.History.html">NWH.DWP2.MeshDecimation.History.html</a> ).	<code>his</code>	History object to record the removal.

## ReplaceVertex(Vert, Vert, Vector2, Vector3, History)

Replaces a vertex in this triangle with a new vertex and updates all relationships. Records the replacement in history for potential undo operations.

### Declaration

```
public void ReplaceVertex(Vert vo, Vert vnew, Vector2 newUV, Vector3 newVN, History his)
```

## Parameters

Type	Name	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	<i>vo</i>	Old vertex to be replaced.
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	<i>vnew</i>	New vertex to replace with.
<a href="#">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	<i>newUV</i>	New texture coordinate.
<a href="#">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>newVN</i>	New vertex normal.
<a href="#">History (NWH.DWP2.MeshDecimation.History.html)</a>	<i>his</i>	History object to record the replacement.

## SetDefaultIndices(int, int, int)

Sets the original mesh vertex indices for this triangle.

### Declaration

```
public void SetDefaultIndices(int n0, int n1, int n2)
```

## Parameters

Type	Name	Description
<a href="#">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>n0</i>	Original index for vertex 0.
<a href="#">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>n1</i>	Original index for vertex 1.
<a href="#">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	<i>n2</i>	Original index for vertex 2.

## normalAt(Vert)

Gets the vertex normal for a given vertex.

### Declaration

```
public Vector3 normalAt(Vert v)
```

## Parameters

Type	Name	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	<i>v</i>	Vertex to query.

## Returns

Type	Description
<a href="#">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	Vertex normal for the vertex, or zero vector if not found.

## setUV(Vert, Vector2)

Sets the texture coordinate for a given vertex.

### Declaration

```
public void setUV(Vert v, Vector2 newuv)
```

### Parameters

Type	Name	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	<i>v</i>	Vertex to update.
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	<i>newuv</i>	New texture coordinate.

## setVN(Vert, Vector3)

Sets the vertex normal for a given vertex.

### Declaration

```
public void setVN(Vert v, Vector3 newNormal)
```

### Parameters

Type	Name	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	<i>v</i>	Vertex to update.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>newNormal</i>	New vertex normal.

## uvAt(Vert)

Gets the texture coordinate for a given vertex.

### Declaration

```
public Vector2 uvAt(Vert v)
```

### Parameters

Type	Name	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	<i>v</i>	Vertex to query.

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	Texture coordinate for the vertex, or zero vector if not found.



# Class Vert

Represents a vertex in the mesh decimation algorithm. Stores vertex data and relationships for edge collapse operations.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (https://learn.microsoft.com/dotnet/api/system.object)  
↳ Vert

**Namespace:** [NWH](#) (NWH.html), [DWP2](#) (NWH.DWP2.html), [MeshDecimation](#) (NWH.DWP2.MeshDecimation.html)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class Vert
```

## Constructors

### Vert(Vector3, int, bool)

Initializes a new vertex with position, ID, and selection status.

## Declaration

```
public Vert(Vector3 position, int id, bool selected)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> (https://docs.unity3d.com/ScriptReference/Vector3.html).	<i>position</i>	3D position of the vertex.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> (https://learn.microsoft.com/dotnet/api/system.int32).	<i>id</i>	Unique identifier.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> (https://learn.microsoft.com/dotnet/api/system.boolean).	<i>selected</i>	Whether the vertex is selected.

## Fields

### collapse

Target vertex for edge collapse operation.

## Declaration

```
public Vert collapse
```

## Field Value

Type	Description
<a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a>	

## cost

Edge collapse cost for this vertex.

### Declaration

```
public float cost
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## deleted

Whether this vertex has been deleted.

### Declaration

```
public bool deleted
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	

## face

List of triangles that use this vertex.

### Declaration

```
public List<Tri> face
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List (https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1)</a> ,< <a href="#">Tri (NWH.DWP2.MeshDecimation.Tri.html)</a> >	

## id

Unique identifier for this vertex.

### Declaration

```
public int id
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a> .	

## neighbor

List of neighboring vertices connected by edges.

### Declaration

```
public List<Vert> neighbor
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List (https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1)</a> .< <a href="#">Vert (NWH.DWP2.MeshDecimation.Vert.html)</a> >	

## position

3D position of the vertex.

### Declaration

```
public Vector3 position
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> .	

## selected

Whether this vertex is marked as selected (prevents collapse if locked).

## Declaration

```
public bool selected
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Methods

## AddFace(Tri)

Adds a triangle to this vertex's face list.

### Declaration

```
public void AddFace(Tri f)
```

### Parameters

Type	Name	Description
<a href="#">Tri</a> ( <a href="#">NWH.DWP2.MeshDecimation.Tri.html</a> ).	<i>f</i>	Triangle to add.

## AddNeighbor(Vert)

Adds a vertex to the neighbor list if not already present.

### Declaration

```
public void AddNeighbor(Vert v)
```

### Parameters

Type	Name	Description
<a href="#">Vert</a> ( <a href="#">NWH.DWP2.MeshDecimation.Vert.html</a> ).	<i>v</i>	Vertex to add as neighbor.

## IsBorder()

Checks if this vertex is on the mesh border. A vertex is on the border if any of its edges is shared by only one triangle.

## Declaration

```
public bool IsBorder()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if the vertex is on the border, false otherwise.

## RemoveFace(Tri)

Removes a triangle from this vertex's face list.

## Declaration

```
public void RemoveFace(Tri f)
```

## Parameters

Type	Name	Description
<a href="#">Tri</a> ( <a href="#">NWH.DWP2.MeshDecimation.Tri.html</a> )	<i>f</i>	Triangle to remove.

## RemoveIfNonNeighbor(Vert)

Removes a vertex from the neighbor list if they no longer share any faces.

## Declaration

```
public void RemoveIfNonNeighbor(Vert v)
```

## Parameters

Type	Name	Description
<a href="#">Vert</a> ( <a href="#">NWH.DWP2.MeshDecimation.Vert.html</a> ).	<i>v</i>	Vertex to potentially remove from neighbors.

## RemoveVert()

Removes this vertex and breaks all neighbor connections.

## Declaration

```
public void RemoveVert()
```



# Namespace NWH.DWP2.MiConvexHull

## Classes

### **[ConvexFace<TVertex, TFace> \(NWH.DWP2.MiConvexHull.ConvexFace-2.html\)](#)**

A convex face representation containing adjacency information.

### **[ConvexHull \(NWH.DWP2.MiConvexHull.ConvexHull.html\)](#)**

Factory class for computing convex hulls.

### **[ConvexHull<TVertex, TFace> \(NWH.DWP2.MiConvexHull.ConvexHull-2.html\)](#)**

Representation of a convex hull.

### **[DefaultConvexFace<TVertex> \(NWH.DWP2.MiConvexHull.DefaultConvexFace-1.html\)](#)**

A default convex face representation that inherits from ConvexFace with self-referencing type parameter.

### **[DefaultTriangulationCell<TVertex> \(NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html\)](#)**

Default triangulation cell that inherits from TriangulationCell with self-referencing type parameter.

### **[DefaultVertex \(NWH.DWP2.MiConvexHull.DefaultVertex.html\)](#)**

"Default" vertex.

### **[DelaunayTriangulation<TVertex, TCell> \(NWH.DWP2.MiConvexHull.DelaunayTriangulation-2.html\)](#)**

Calculation and representation of Delaunay triangulation.

### **[Triangulation \(NWH.DWP2.MiConvexHull.Triangulation.html\)](#)**

Factory class for creating triangulations.

### **[TriangulationCell<TVertex, TCell> \(NWH.DWP2.MiConvexHull.TriangulationCell-2.html\)](#)**

Representation of the triangulation cell. Pretty much the same as ConvexFace, just wanted to distinguish the two.  
To declare your own face type, use class Face : DelaunayFace(of Vertex, of Face)

### **[Vertex \(NWH.DWP2.MiConvexHull.Vertex.html\)](#)**

Unity-specific vertex implementation for convex hull calculations.

### **VoronoiEdge<TVertex, TCell> (NWH.DWP2.MiConvexHull.VoronoiEdge-2.html)**

A class representing an (undirected) edge of the Voronoi graph.

### **VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh.html)**

A factory class for creating a Voronoi mesh.

### **VoronoiMesh<TVertex, TCell, TEdge> (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html)**

A representation of a voronoi mesh.

## Interfaces

### **ITriangulation<TVertex, TCell> (NWH.DWP2.MiConvexHull.ITriangulation-2.html)**

Simple interface to unify different types of triangulations in the future.

### **IVertex (NWH.DWP2.MiConvexHull.IVertex.html)**

An interface for a structure with nD position.

# Class ConvexFace<TVertex, TFace>

A convex face representation containing adjacency information.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ ConvexFace<TVertex, TFace>

↳ [DefaultConvexFace<TVertex>](#) ([NWH.DWP2.MiConvexHull.DefaultConvexFace-1.html](#)).

↳ [TriangulationCell<TVertex, TCell>](#) ([NWH.DWP2.MiConvexHull.TriangulationCell-2.html](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public abstract class ConvexFace<TVertex, TFace> where TVertex : IVertex where TFace : ConvexFace<TVertex, TFace>
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TFace</i>	The type of the t face.

## Properties

### Adjacency

Adjacency. Array of length "dimension". If F = Adjacency[i] then the vertices shared with F are Vertices[j] where j != i. In the context of triangulation, can be null (indicates the cell is at boundary).

### Declaration

```
public TFace[] Adjacency { get; set; }
```

### Property Value

Type	Description
TFace[]	The adjacency.

### Normal

The normal vector of the face. Null if used in triangulation.

## Declaration

```
public double[] Normal { get; set; }
```

## Property Value

Type	Description
<code>double</code> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> .)	The normal.

## Vertices

The vertices stored in clockwise order for dimensions 2 - 4, in higher dimensions the order is arbitrary. Unless I accidentally switch some index somewhere in which case the order is CCW. Either way, it is consistent. 3D Normal =  $(V[1] - V[0]) \times (V[2] - V[0])$ .

## Declaration

```
public TVertex[] Vertices { get; set; }
```

## Property Value

Type	Description
<code>TVertex[]</code>	The vertices.

# Class ConvexHull

Factory class for computing convex hulls.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ ConvexHull

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class ConvexHull
```

## Methods

### Create(IList<double[]>, double)

Creates a convex hull of the input data.

#### Declaration

```
public static ConvexHull<DefaultVertex, DefaultConvexFace<DefaultVertex>> Create(IList<double[]> data, double PlaneDistanceTolerance = 1E-10)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> )[]>	<i>data</i>	The data.
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).	<i>PlaneDistanceTolerance</i>	The plane distance tolerance.

#### Returns

Type	Description
<a href="#">ConvexHull</a> ( <a href="#">NWH.DWP2.MiConvexHull.ConvexHull-2.html</a> ), <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> ), <a href="#">DefaultConvexFace</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultConvexFace-1.html</a> ), <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> )>>	<a href="#">ConvexHull</a> < <a href="#">DefaultVertex</a> , <a href="#">DefaultConvexFace</a> < <a href="#">DefaultVertex</a> >>>.

## Create<TVertex>(IList<TVertex>, double)

Creates a convex hull of the input data.

### Declaration

```
public static ConvexHull<TVertex, DefaultConvexFace<TVertex>> Create<TVertex>(IList<TVertex> data, double PlaneDistanceTolerance = 1E-10) where TVertex : IVertex
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	The data.
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ),	<i>PlaneDistanceTolerance</i>	The plane distance tolerance.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.convexhull-2.html">ConvexHull</a> ( <a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.convexhull-2.html">NWH.DWP2.MiConvexHull.ConvexHull-2.html</a> ), <TVertex, <a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.defaultconvexface-1.html">DefaultConvexFace</a> ( <a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.defaultconvexface-1.html">NWH.DWP2.MiConvexHull.DefaultConvexFace-1.html</a> ), <TVertex>>	ConvexHull<TVertex, DefaultConvexFace<TVertex>>.

### Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.

## Create<TVertex, TFace>(IList<TVertex>, double)

Creates a convex hull of the input data.

### Declaration

```
public static ConvexHull<TVertex, TFace> Create<TVertex, TFace>(IList<TVertex> data, double PlaneDistanceTolerance = 1E-10) where TVertex : IVertex where TFace : ConvexFace<TVertex, TFace>, new()
```

## Parameters

Type	Name	Description
<u><a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a></u> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	The data.
<u><a href="https://learn.microsoft.com/dotnet/api/system.double">double</a></u> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ),	<i>PlaneDistanceTolerance</i>	The plane distance tolerance.

## Returns

Type	Description
<u><a href="https://learn.microsoft.com/dotnet/api/microsoft.geometry.convexhullconvexhull-2">ConvexHull (NWH.DWP2.MiConvexHull.ConvexHull-2.html)</a></u> , <TVertex, TFace>	ConvexHull<TVertex, TFace>.

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TFace</i>	The type of the t face.

# Class ConvexHull<TVertex, TFace>

Representation of a convex hull.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ ConvexHull<TVertex, TFace>

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class ConvexHull<TVertex, TFace> where TVertex : IVertex where TFace : ConvexFace<TVertex, TFace>, new()
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TFace</i>	The type of the t face.

## Properties

### Faces

Faces of the convex hull.

#### Declaration

```
public IEnumerable<TFace> Faces { get; }
```

#### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> ). <TFace>	The faces.

### Points

Vertices of the convex hull.

## Declaration

```
public IEnumerable<TVertex> Points { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> ), <TVertex>	The points.

## Methods

### Create(IList<TVertex>, double)

Creates the convex hull.

## Declaration

```
public static ConvexHull<TVertex, TFace> Create(IList<TVertex> data, double PlaneDistanceTolerance)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	The data.
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).	<i>PlaneDistanceTolerance</i>	The plane distance tolerance.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.convexhull-2.html">ConvexHull</a> ( <a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.convexhull-2.html">NWH.DWP2.MiConvexHull.ConvexHull-2.html</a> ), <TVertex, TFace>	ConvexHull<TVertex, TFace>.

## Exceptions

Type	Condition
<a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">ArgumentNullException</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">https://learn.microsoft.com/dotnet/api/system.argumentnullexception</a> ).	The supplied data is null.
<a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">ArgumentNullException</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">https://learn.microsoft.com/dotnet/api/system.argumentnullexception</a> ).	data



# Class DefaultConvexFace<TVertex>

A default convex face representation that inherits from ConvexFace with self-referencing type parameter.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [ConvexFace \(NWH.DWP2.MiConvexHull.ConvexFace-2.html\)](#), [DefaultConvexFace \(NWH.DWP2.MiConvexHull.DefaultConvexFace-1.html\)](#), [DefaultConvexFace<TVertex>](#)

## Inherited Members

---

[ConvexFace<TVertex, DefaultConvexFace<TVertex>>.Adjacency\\_ \(NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Adjacency\\_\)](#).

[ConvexFace<TVertex, DefaultConvexFace<TVertex>>.Vertices \(NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Vertices\)](#).

[ConvexFace<TVertex, DefaultConvexFace<TVertex>>.Normal \(NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Normal\)](#).

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [MiConvexHull \(NWH.DWP2.MiConvexHull.html\)](#).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DefaultConvexFace<TVertex> : ConvexFace<TVertex, DefaultConvexFace<TVertex>> where TVertex : IVertex
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the vertex.

# Class DefaultTriangulationCell<TVertex>

Default triangulation cell that inherits from TriangulationCell with self-referencing type parameter.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [ConvexFace](#) ([NWH.DWP2.MiConvexHull.ConvexFace-2.html](#)), <TVertex, [DefaultTriangulationCell](#) ([NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html](#)), <TVertex>>
- ↳ [TriangulationCell](#) ([NWH.DWP2.MiConvexHull.TriangulationCell-2.html](#)), <TVertex, [DefaultTriangulationCell](#) ([NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html](#)), <TVertex>>
- ↳ [DefaultTriangulationCell](#) <TVertex>

## Inherited Members

[ConvexFace](#)<TVertex, [DefaultTriangulationCell](#)<TVertex>>.Adjacency ([NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Adjacency](#)).

[ConvexFace](#)<TVertex, [DefaultTriangulationCell](#)<TVertex>>.Vertices ([NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Vertices](#)).

[ConvexFace](#)<TVertex, [DefaultTriangulationCell](#)<TVertex>>.Normal ([NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Normal](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DefaultTriangulationCell<TVertex> : TriangulationCell<TVertex, DefaultTriangulationCell<TVertex>> where TVertex : IVertex
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the vertex.

# Class DefaultVertex

"Default" vertex.

## Inheritance

---

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ DefaultVertex

## Implements

[IVertex](#) ([NWH.DWP2.MiConvexHull.IVertex.html](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DefaultVertex : IVertex
```

## Properties

### Position

Position of the vertex.

### Declaration

```
public double[] Position { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).[]	The position.

## Implements

[IVertex](#) ([NWH.DWP2.MiConvexHull.IVertex.html](#)).

## See Also

[IVertex](#) ([NWH.DWP2.MiConvexHull.IVertex.html](#)).

# Class DelaunayTriangulation<TVertex, TCell>

Calculation and representation of Delaunay triangulation.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ DelaunayTriangulation<TVertex, TCell>

## Implements

[ITriangulation](#) ([NWH.DWP2.MiConvexHull.ITriangulation-2.html](#))<TVertex, TCell>

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class DelaunayTriangulation<TVertex, TCell> : ITriangulation<TVertex, TCell> where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>, new()
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.

## Properties

### Cells

Cells of the triangulation.

#### Declaration

```
public IEnumerable<TCell> Cells { get; }
```

#### Property Value

Type	Description
<a href="#">IEnumerable</a> ( <a href="#">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> )<TCell>	The cells.

## Methods

## Create(IList<TVertex>)

Creates the Delaunay triangulation of the input data.

### Declaration

```
public static DelaunayTriangulation<TVertex, TCell> Create(IList<TVertex> data)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.iling-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.iling-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.iling-1</a> ), <TVertex>	<i>data</i>	The data.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.delaunaytriangulation-2">DelaunayTriangulation</a> ( <a href="https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.delaunaytriangulation-2">NWH.DWP2.MiConvexHull.DelaunayTriangulation-2.html</a> ), <TVertex, TCell>	DelaunayTriangulation<TVertex, TCell>.

### Exceptions

Type	Condition
<a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">ArgumentNullException</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">https://learn.microsoft.com/dotnet/api/system.argumentnullexception</a> ).	<i>data</i>

## Implements

[ITriangulation<TVertex, TCell>](https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.itriangulation-2) ([NWH.DWP2.MiConvexHull.ITriangulation-2.html](https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.itriangulation-2)).

## See Also

[ITriangulation](https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.itriangulation-2) ([NWH.DWP2.MiConvexHull.ITriangulation-2.html](https://learn.microsoft.com/dotnet/api/nwh.dwp2.miconvexhull.itriangulation-2)), <TVertex, TCell>

# Interface ITriangulation<TVertex, TCell>

Simple interface to unify different types of triangulations in the future.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [MiConvexHull \(NWH.DWP2.MiConvexHull.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public interface ITriangulation<TVertex, TCell> where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>, new()
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.

## Properties

### Cells

Triangulation simplexes. For 2D - triangles, 3D - tetrahedrons, etc ...

#### Declaration

```
IEnumerable<TCell> Cells { get; }
```

#### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> ), <TCell>	The cells.

# Interface IVertex

An interface for a structure with nD position.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [MiConvexHull \(NWH.DWP2.MiConvexHull.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public interface IVertex
```

## Properties

### Position

Position of the vertex.

### Declaration

```
double[] Position { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.double">double (https://learn.microsoft.com/dotnet/api/system.double)</a> []	The position.

# Class Triangulation

Factory class for creating triangulations.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ Triangulation

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class Triangulation
```

## Methods

### CreateDelaunay(IList<double[]>)

Creates the Delaunay triangulation of the input data.

#### Declaration

```
public static ITriangulation<DefaultVertex, DefaultTriangulationCell<DefaultVertex>> CreateDelaunay(IList<double[]> data)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ), []>	<i>data</i>	The data.

#### Returns

Type	Description
<a href="#">ITriangulation</a> ( <a href="#">NWH.DWP2.MiConvexHull.ITriangulation-2.html</a> ), <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> ), <a href="#">DefaultTriangulationCell</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html</a> ), <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> ), >>	ITriangulation<DefaultVertex, DefaultTriangulationCell<DefaultVertex>>.

## CreateDelaunay<TVertex> (IList<TVertex>)

Creates the Delaunay triangulation of the input data.

### Declaration

```
public static ITriangulation<TVertex, DefaultTriangulationCell<TVertex>> CreateDelaunay<TVertex>(IList<TVertex> data) where TVertex : IVertex
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	The data.

### Returns

Type	Description
<a href="#">ITriangulation</a> ( <a href="#">NWH.DWP2.MiConvexHull.ITriangulation-2.html</a> ), <TVertex, <a href="#">DefaultTriangulationCell</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html</a> ), <TVertex>>	ITriangulation<TVertex, DefaultTriangulationCell<TVertex>>.

### Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.

## CreateDelaunay<TVertex, TFace> (IList<TVertex>)

Creates the Delaunay triangulation of the input data.

### Declaration

```
public static ITriangulation<TVertex, TFace> CreateDelaunay<TVertex, TFace>(IList<TVertex> data) where TVertex : IVertex where TFace : TriangulationCell<TVertex, TFace>, new()
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	

### Returns

Type	Description
<a href="#">ITriangulation</a> ( <a href="#">NWH.DWP2.MiConvexHull.ITriangulation-2.html</a> ), <TVertex, TFace>	

## Type Parameters

Name	Description
<i>TVertex</i>	
<i>TFace</i>	

## CreateVoronoi(IList<double[]>)

Create the voronoi mesh.

### Declaration

```
public static VoronoiMesh<DefaultVertex, DefaultTriangulationCell<DefaultVertex>, VoronoiEdge<DefaultVertex, DefaultTriangulationCell<DefaultVertex>>> CreateVoronoi(IList<double[]> data)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), < <a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> )[] >	<i>data</i>	

### Returns

Type	Description
<a href="#">VoronoiMesh</a> ( <a href="#">NWH.DWP2.MiConvexHull.VoronoiMesh-3.html</a> ), < <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> ), <a href="#">DefaultTriangulationCell</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html</a> ), < <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> )>, <a href="#">VoronoiEdge</a> ( <a href="#">NWH.DWP2.MiConvexHull.VoronoiEdge-2.html</a> ), < <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> ), <a href="#">DefaultTriangulationCell</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html</a> ), < <a href="#">DefaultVertex</a> ( <a href="#">NWH.DWP2.MiConvexHull.DefaultVertex.html</a> )> > >	

## CreateVoronoi<TVertex>(IList<TVertex>)

Create the voronoi mesh.

### Declaration

```
public static VoronoiMesh<TVertex, DefaultTriangulationCell<TVertex>, VoronoiEdge<TVertex, DefaultTriangulationCell<TVertex>>> CreateVoronoi<TVertex>(IList<TVertex> data) where TVertex : IVertex
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	

## Returns

Type	Description
<a href="#">VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html)</a> <TVertex, <a href="#">DefaultTriangulationCell (NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html)</a> <TVertex>, <a href="#">VoronoiEdge (NWH.DWP2.MiConvexHull.VoronoiEdge-2.html)</a> <TVertex, <a href="#">DefaultTriangulationCell (NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html)</a> <TVertex>>>	

## Type Parameters

Name	Description
<i>TVertex</i>	

## CreateVoronoi<TVertex, TCell>(IList<TVertex>)

Create the voronoi mesh.

### Declaration

```
public static VoronoiMesh<TVertex, TCell, VoronoiEdge<TVertex, TCell>> CreateVoronoi<TVertex, TCell>(IList<TVertex> data) where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>, new()
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList (https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1)</a> <TVertex>	<i>data</i>	

## Returns

Type	Description
<a href="#">VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html)</a> <TVertex, TCell, <a href="#">VoronoiEdge (NWH.DWP2.MiConvexHull.VoronoiEdge-2.html)</a> <TVertex, TCell>>	

## Type Parameters

Name	Description
<i>TVertex</i>	
<i>TCell</i>	

## CreateVoronoi<TVertex, TCell, TEdge>(IList<TVertex>)

Create the voronoi mesh.

## Declaration

```
public static VoronoiMesh<TVertex, TCell, TEdge> CreateVoronoi<TVertex, TCell, TEdge>(IList<TVertex> data) where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>, new() where TEdge : VoronoiEdge<TVertex, TCell>, new()
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	

## Returns

Type	Description
<a href="#">VoronoiMesh</a> ( <a href="#">NWH.DWP2.MiConvexHull.VoronoiMesh-3.html</a> ), <TVertex, TCell, TEdge>	

## Type Parameters

Name	Description
<i>TVertex</i>	
<i>TCell</i>	
<i>TEdge</i>	

# Class TriangulationCell<TVertex, TCell>

Representation of the triangulation cell. Pretty much the same as ConvexFace, just wanted to distinguish the two. To declare your own face type, use class Face : DelaunayFace(of Vertex, of Face)

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [ConvexFace \(NWH.DWP2.MiConvexHull.ConvexFace-2.html\)](#)<TVertex, TCell>
- ↳ TriangulationCell<TVertex, TCell>
- ↳ [DefaultTriangulationCell<TVertex>](#) ([NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html](#)).

## Inherited Members

[ConvexFace<TVertex, TCell>.Adjacency](#) ([NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Adjacency](#)).

[ConvexFace<TVertex, TCell>.Vertices](#) ([NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Vertices](#)).

[ConvexFace<TVertex, TCell>.Normal](#) ([NWH.DWP2.MiConvexHull.ConvexFace-2.html#NWH\\_DWP2\\_MiConvexHull\\_ConvexFace\\_2\\_Normal](#)).

**Namespace:** [NWH \(NWH.html\)](#).[DWP2 \(NWH.DWP2.html\)](#).[MiConvexHull \(NWH.DWP2.MiConvexHull.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public abstract class TriangulationCell<TVertex, TCell> : ConvexFace<TVertex, TCell> where T
Vertex : IVertex where TCell : ConvexFace<TVertex, TCell>
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.

## See Also

[ConvexFace \(NWH.DWP2.MiConvexHull.ConvexFace-2.html\)](#)<TVertex, TFace>

# Class Vertex

Unity-specific vertex implementation for convex hull calculations.

## Inheritance

---

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ Vertex

## Implements

[IVertex](#) ([NWH.DWP2.MiConvexHull.IVertex.html](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class Vertex : IVertex
```

## Constructors

### Vertex(double, double, double)

Initializes a new vertex with specified coordinates.

#### Declaration

```
public Vertex(double x, double y, double z)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).	x	X coordinate.
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).	y	Y coordinate.
<a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ).	z	Z coordinate.

### Vertex(Vector3)

Initializes a new vertex from a Unity Vector3.

#### Declaration

```
public Vertex(Vector3 ver)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	<i>ver</i>	Unity Vector3 position.

# Properties

## Position

Position of the vertex in 3D space.

### Declaration

```
public double[] Position { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.double">double (https://learn.microsoft.com/dotnet/api/system.double)</a>	

# Methods

## ToVec()

Converts the vertex position to a Unity Vector3.

### Declaration

```
public Vector3 ToVec()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	Unity Vector3 representation of the vertex position.

# Implements

[IVertex \(NWH.DWP2.MiConvexHull.IVertex.html\)](#)

# Class VoronoiEdge<TVertex, TCell>

A class representing an (undirected) edge of the Voronoi graph.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ VoronoiEdge<TVertex, TCell>

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class VoronoiEdge<TVertex, TCell> where TVertex : IVertex where TCell : Triangulation
    Cell<TVertex, TCell>
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.

## Constructors

### VoronoiEdge()

Create an instance of the edge.

#### Declaration

```
public VoronoiEdge()
```

### VoronoiEdge(TCell, TCell)

Create an instance of the edge.

#### Declaration

```
public VoronoiEdge(TCell source, TCell target)
```

## Parameters

Type	Name	Description
TCell	<i>source</i>	The source.
TCell	<i>target</i>	The target.

# Properties

## Source

Source of the edge.

### Declaration

```
public TCell Source { get; }
```

### Property Value

Type	Description
TCell	The source.

## Target

Target of the edge.

### Declaration

```
public TCell Target { get; }
```

### Property Value

Type	Description
TCell	The target.

# Methods

## Equals(object)

...

### Declaration

```
public override bool Equals(object obj)
```

### Parameters

Type	Name	Description
<u>object</u> ( <a href="https://learn.microsoft.com/dotnet/api/system.object">https://learn.microsoft.com/dotnet/api/system.object</a> ).	<i>obj</i>	The object to compare with the current object.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	true if the specified <a href="https://learn.microsoft.com/dotnet/api/system.object">object</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.object">https://learn.microsoft.com/dotnet/api/system.object</a> ) is equal to this instance; otherwise, false .

## Overrides

[object.Equals\(object\)](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

## GetHashCode()

...

## Declaration

```
public override int GetHashCode()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	A hash code for this instance, suitable for use in hashing algorithms and data structures like a hash table.

## Overrides

[object.GetHashCode\(\)](https://learn.microsoft.com/dotnet/api/system.object)

# Class VoronoiMesh

A factory class for creating a Voronoi mesh.

## Inheritance

---

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ VoronoiMesh

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class VoronoiMesh
```

## Methods

### Create(IList<double[]>)

Create the voronoi mesh.

#### Declaration

```
public static VoronoiMesh<DefaultVertex, DefaultTriangulationCell<DefaultVertex>, VoronoiEdge<DefaultVertex, DefaultTriangulationCell<DefaultVertex>>> Create(IList<double[]> data)
```

#### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <a href="https://learn.microsoft.com/dotnet/api/system.double">double</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.double">https://learn.microsoft.com/dotnet/api/system.double</a> ), []>	<i>data</i>	The data.

## Returns

Type	Description
<pre>VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html) &lt; DefaultVertex (NWH.DWP2.MiConvexHull.DefaultVertex.html) , DefaultTriangulationCell (NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html) &lt; DefaultVertex (NWH.DWP2.MiConvexHull.DefaultVertex.html) &gt;, VoronoiEdge (NWH.DWP2.MiConvexHull.VoronoiEdge-2.html) &lt; DefaultVertex (NWH.DWP2.MiConvexHull.DefaultVertex.html) , DefaultTriangulationCell (NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html) &lt; DefaultVertex (NWH.DWP2.MiConvexHull.DefaultVertex.html) &gt;&gt;&gt;</pre>	<pre>VoronoiMesh&lt;DefaultVertex, DefaultTriangulationCell&lt;DefaultVertex&gt;, VoronoiEdge&lt;DefaultVertex, DefaultTriangulationCell&lt;DefaultVertex&gt;&gt;&gt;.</pre>

## Create<TVertex>(IList<TVertex>)

Create the voronoi mesh.

### Declaration

```
public static VoronoiMesh<TVertex, DefaultTriangulationCell<TVertex>, VoronoiEdge<TVertex, DefaultTriangulationCell<TVertex>>> Create<TVertex>(IList<TVertex> data) where TVertex : IVertex
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ),<TVertex>	<i>data</i>	The data.

## Returns

Type	Description
<a href="#">VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html)</a> , <TVertex, <a href="#">DefaultTriangulationCell (NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html)</a> , <TVertex>, <a href="#">VoronoiEdge (NWH.DWP2.MiConvexHull.VoronoiEdge-2.html)</a> , <TVertex, <a href="#">DefaultTriangulationCell (NWH.DWP2.MiConvexHull.DefaultTriangulationCell-1.html)</a> , <TVertex>>>	VoronoiMesh<TVertex, DefaultTriangulationCell<TVertex>, VoronoiEdge<TVertex, DefaultTriangulationCell<TVertex>>>.

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.

## Create<TVertex, TCell>(IList<TVertex>)

Create the voronoi mesh.

## Declaration

```
public static VoronoiMesh<TVertex, TCell, VoronoiEdge<TVertex, TCell>> Create<TVertex, TCell>  
>(IList<TVertex> data) where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>  
>, new()
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList (https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1)</a> .<TVertex>	<i>data</i>	The data.

## Returns

Type	Description
<a href="#">VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html)</a> .<TVertex, TCell, <a href="#">VoronoiEdge (NWH.DWP2.MiConvexHull.VoronoiEdge-2.html)</a> , <TVertex, TCell>>	VoronoiMesh<TVertex, TCell, VoronoiEdge<TVertex, TCell>>.

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.

## Create<TVertex, TCell, TEdge>(IList<TVertex>)

Create the voronoi mesh.

### Declaration

```
public static VoronoiMesh<TVertex, TCell, TEdge> Create<TVertex, TCell, TEdge>(IList<TVertex> data) where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>, new() where TEdge : VoronoiEdge<TVertex, TCell>, new()
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ).<TVertex>	<i>data</i>	The data.

### Returns

Type	Description
<a href="#">VoronoiMesh (NWH.DWP2.MiConvexHull.VoronoiMesh-3.html)</a> .<TVertex, TCell, TEdge>	VoronoiMesh<TVertex, TCell, TEdge>.

### Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.
<i>TEdge</i>	The type of the t edge.

# Class VoronoiMesh<TVertex, TCell, TEdge>

A representation of a voronoi mesh.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ VoronoiMesh<TVertex, TCell, TEdge>

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [MiConvexHull](#) ([NWH.DWP2.MiConvexHull.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class VoronoiMesh<TVertex, TCell, TEdge> where TVertex : IVertex where TCell : TriangulationCell<TVertex, TCell>, new() where TEdge : VoronoiEdge<TVertex, TCell>, new()
```

## Type Parameters

Name	Description
<i>TVertex</i>	The type of the t vertex.
<i>TCell</i>	The type of the t cell.
<i>TEdge</i>	The type of the t edge.

## Properties

### Edges

Edges connecting the cells. The same information can be retrieved Cells' Adjacency.

#### Declaration

```
public IEnumerable<TEdge> Edges { get; }
```

#### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> )<TEdge>	The edges.

### Vertices

Vertices of the diagram.

## Declaration

```
public IEnumerable<TCell> Vertices { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> ), <TCell>	The vertices.

## Methods

### Create(IList<TVertex>)

Create a Voronoi diagram of the input data.

## Declaration

```
public static VoronoiMesh<TVertex, TCell, TEdge> Create(IList<TVertex> data)
```

## Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">IList</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1</a> ), <TVertex>	<i>data</i>	The data.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">VoronoiMesh</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ilist-1">NWH.DWP2.MiConvexHull.VoronoiMesh-3.html</a> ), <TVertex, TCell, TEdge>	VoronoiMesh<TVertex, TCell, TEdge>.

## Exceptions

Type	Condition
<a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">ArgumentNullException</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.argumentnullexception">https://learn.microsoft.com/dotnet/api/system.argumentnullexception</a> ).	<i>data</i>

# Namespace NWH.DWP2.SailController

## Classes

### **HullWindApplicator (NWH.DWP2.SailController.HullWindApplicator.html)**

Applies wind drag forces to the hull of a sailing vessel based on the global wind conditions. Calculates the projected area of the hull facing the wind and applies an appropriate drag force. Does not account for the waterline - dimensions should represent only the hull portion above water. Requires a WindGenerator to be present in the scene.

### **SailController (NWH.DWP2.SailController.SailController.html)**

Manages sail physics by calculating and applying lift and drag forces based on sail geometry, orientation, and wind conditions. Uses four corner transforms (a, b, c, d) to define sail shape, enabling dynamic sail configurations including furling and multi-part sails. Calculates apparent wind from true wind and vessel velocity, then applies aerodynamic forces at the sail's surface-weighted center. The corner transforms follow a clockwise pattern: a (bottom left/front), b (top left/front), c (top right/rear), d (bottom right/rear). Corner transforms can be attached to different parents to enable sail furling or complex rigging systems. Use SailRotator for user-controlled sail rotation. Requires a WindGenerator in the scene and a SailPreset for aerodynamic coefficients.

### **SailPreset (NWH.DWP2.SailController.SailPreset.html)**

Defines the aerodynamic characteristics of a sail through lift and drag coefficient curves. Contains the relationship between angle of attack and force generation. Different sail types (square, lateen, bermuda, etc.) can be represented by different presets. Can be created via Assets > Create > NWH > DWP2 > SailPreset.

### **SailRotator (NWH.DWP2.SailController.SailRotator.html)**

Rotates a transform based on player input from the AdvancedShipController. Used to control sail orientation in response to the RotateSail input axis. Typically attached to a sail boom or mast that rotates horizontally. Requires an AdvancedShipController component on a parent GameObject.

### **WindGenerator (NWH.DWP2.SailController.WindGenerator.html)**

Generates procedural wind with randomized gusts for sail simulation. Creates realistic wind conditions by varying speed and direction over time. Provides a singleton instance accessible to all sail and wind-related components. Wind direction uses world coordinates where 0 degrees points along the positive Z-axis. Only one WindGenerator should exist per scene.

### **WindIndicator (NWH.DWP2.SailController.WindIndicator.html)**

Visual indicator that rotates to show wind direction. Displays apparent wind when attached as a child of a SailController. Displays true wind from the WindGenerator when not under a SailController. Useful for debugging sail setup and helping players understand wind conditions. The transform's forward direction will point into the wind.



# Class HullWindApplicator

Applies wind drag forces to the hull of a sailing vessel based on the global wind conditions. Calculates the projected area of the hull facing the wind and applies an appropriate drag force. Does not account for the waterline - dimensions should represent only the hull portion above water. Requires a WindGenerator to be present in the scene.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)
  - ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>)
    - ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>)
      - ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>)
        - ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>)
          - ↳ HullWindApplicator

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [SailController](#) ([NWH.DWP2.SailController.html](#)),

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class HullWindApplicator : MonoBehaviour
```

## Fields

### dimensions

Physical dimensions of the hull above the waterline. X represents width, Y represents height, Z represents length. These dimensions are used to calculate the projected area when wind hits the hull from different angles.

### Declaration

```
[Tooltip("The dimensions of the object (x = width, y = height, z = length).")]  
[SerializeField]  
public Vector3 dimensions
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	

### dragCoefficient

Drag coefficient applied to the wind force calculation. Higher values result in stronger wind resistance. Typical values range from 0.5 to 2.0 depending on hull shape and surface characteristics.

## Declaration

```
[Tooltip("The drag coefficient of the object.")]  
[SerializeField]  
public float dragCoefficient
```

## Field Value

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Class SailController

Manages sail physics by calculating and applying lift and drag forces based on sail geometry, orientation, and wind conditions. Uses four corner transforms (a, b, c, d) to define sail shape, enabling dynamic sail configurations including furling and multi-part sails. Calculates apparent wind from true wind and vessel velocity, then applies aerodynamic forces at the sail's surface-weighted center. The corner transforms follow a clockwise pattern: a (bottom left/front), b (top left/front), c (top right/rear), d (bottom right/rear). Corner transforms can be attached to different parents to enable sail furling or complex rigging systems. Use `SailRotator` for user-controlled sail rotation. Requires a `WindGenerator` in the scene and a `SailPreset` for aerodynamic coefficients.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ `SailController`

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [SailController](#) ([NWH.DWP2.SailController.html](#)).

**Assembly:** `NWH.DWP2.dll`

## Syntax

```
public class SailController : MonoBehaviour
```

## Fields

### a

Bottom left corner of the sail for square sails, or bottom front corner for triangular sails. First point in the clockwise corner definition pattern. Can be attached to any parent transform to enable dynamic sail configurations.

### Declaration

```
[Tooltip("Bottom left sail corner if square sail.\r\nOtherwise bottom front.")]  
public Transform a
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## airDensity

Air density in  $\text{kg/m}^3$  used in aerodynamic force calculations. Standard sea level value is  $1.225 \text{ kg/m}^3$ . Can be adjusted as a multiplier to scale all sail forces uniformly without modifying the preset.

## Declaration

```
[Tooltip("The air density. Can also be used\r\nas a force coefficient as this affects both lift and drag forces equally.")]  
public float airDensity
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## b

Top left corner of the sail for square sails, or top front corner for triangular sails. Second point in the clockwise corner definition pattern. Can be attached to any parent transform to enable dynamic sail configurations.

## Declaration

```
[Tooltip("Top left sail corner if square sail.\r\nOtherwise top front.")]  
public Transform b
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## c

Top right corner of the sail for square sails, or top rear corner for triangular sails. Third point in the clockwise corner definition pattern. Can be attached to any parent transform to enable dynamic sail configurations.

## Declaration

```
[Tooltip("Top right sail corner if square sail.\r\nOtherwise top rear.")]  
public Transform c
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## d

Bottom right corner of the sail for square sails, or bottom rear corner for triangular sails. Fourth point in the clockwise corner definition pattern. Can be attached to any parent transform to enable dynamic sail configurations.

## Declaration

```
[Tooltip("Bottom right sail corner if square sail.\r\nOtherwise bottom rear.")]  
public Transform d
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## sailPreset

Defines the aerodynamic characteristics of the sail through lift and drag coefficient curves. Contains the relationship between angle of attack and force coefficients.

## Declaration

```
public SailPreset sailPreset
```

## Field Value

Type	Description
<a href="NWH.DWP2.SailController.SailPreset.html">SailPreset</a> ( <a href="NWH.DWP2.SailController.SailPreset.html">NWH.DWP2.SailController.SailPreset.html</a> ).	

# Properties

## AngleOfAttack

Angle in degrees between the sail's forward direction and the apparent wind direction. Measured on the horizontal plane using `Vector3.up` as the reference axis. Used to determine lift and drag coefficients from the `SailPreset` curves. Positive values indicate wind from the starboard side, negative values from port side.

## Declaration

```
public float AngleOfAttack { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## ApparentWind

Wind experienced by the sail relative to the moving vessel. Calculated as the vector difference between true wind and vessel velocity. This is the effective wind that generates aerodynamic forces on the sail. Measured in meters per second.

### Declaration

```
public Vector3 ApparentWind { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## SailArea

Total surface area of the sail in square meters. Calculated from the quadrilateral formed by corner points a, b, c, and d. Used in aerodynamic force calculations along with dynamic pressure.

### Declaration

```
public float SailArea { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## SailCenter

Surface-weighted center point of the sail in world space. All aerodynamic forces are applied at this position. Calculated from the quadrilateral formed by corner points a, b, c, and d.

### Declaration

```
public Vector3 SailCenter { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## SailForce

Total aerodynamic force vector applied to the vessel at the sail center point. Combines lift and drag forces based on sail geometry, apparent wind, and aerodynamic coefficients. Measured in Newtons.

## Declaration

```
public Vector3 SailForce { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## SailForward

Forward direction vector of the sail in world space. Determined by the vector from corner point d to corner point a. Used to calculate the angle of attack relative to the apparent wind.

## Declaration

```
public Vector3 SailForward { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## SailRight

Right direction vector of the sail in world space. Derived from the cross product of SailUp and SailForward. Defines the direction of lift force generation perpendicular to the sail plane.

## Declaration

```
public Vector3 SailRight { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## SailUp

Up direction vector of the sail in world space. Calculated from the average of the top edge to the average of the bottom edge. Used to determine sail orientation and compensate for heel angle.

## Declaration

```
public Vector3 SailUp { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## ShipVelocity

Current velocity of the vessel's Rigidbody in world space. Used to calculate apparent wind by combining with true wind. Measured in meters per second.

### Declaration

```
public Vector3 ShipVelocity { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## TrueWind

True wind vector from the WindGenerator, representing the actual environmental wind. Does not account for vessel motion. Measured in meters per second.

### Declaration

```
public Vector3 TrueWind { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

# Class SailPreset

Defines the aerodynamic characteristics of a sail through lift and drag coefficient curves. Contains the relationship between angle of attack and force generation. Different sail types (square, lateen, bermuda, etc.) can be represented by different presets. Can be created via Assets > Create > NWH > DWP2 > SailPreset.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).  
↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).  
↳ [ScriptableObject](https://docs.unity3d.com/ScriptReference/ScriptableObject.html) (<https://docs.unity3d.com/ScriptReference/ScriptableObject.html>).  
↳ SailPreset

**Namespaces:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [SailController \(NWH.DWP2.SailController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
[CreateAssetMenu(fileName = "SailPreset", menuName = "NWH/DWP2/SailPreset", order = 1)]  
public class SailPreset : ScriptableObject
```

## Fields

### description

Optional description of the sail type and its characteristics.

### Declaration

```
public string description
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	

### dragCoefficientVsAoACurve

Defines how drag coefficient varies with angle of attack. X-axis represents angle of attack in degrees (-180 to 180). Y-axis represents the drag coefficient multiplier. Drag acts in the direction of the apparent wind.

### Declaration

```
public AnimationCurve dragCoefficientVsAoACurve
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">AnimationCurve</a> ( <a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">https://docs.unity3d.com/ScriptReference/AnimationCurve.html</a> ).	

## dragScale

Global multiplier for all drag forces. Values greater than 1 increase drag, values less than 1 reduce it. Does not affect the shape of the drag curve.

### Declaration

```
public float dragScale
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## liftCoefficientVsAoACurve

Defines how lift coefficient varies with angle of attack. X-axis represents angle of attack in degrees (-180 to 180). Y-axis represents the lift coefficient multiplier. Lift acts perpendicular to the sail plane.

### Declaration

```
public AnimationCurve liftCoefficientVsAoACurve
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">AnimationCurve</a> ( <a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">https://docs.unity3d.com/ScriptReference/AnimationCurve.html</a> ).	

## liftScale

Global multiplier for all lift forces. Values greater than 1 increase lift, values less than 1 reduce it. Does not affect the shape of the lift curve.

### Declaration

```
public float liftScale
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	



# Class SailRotator

Rotates a transform based on player input from the AdvancedShipController. Used to control sail orientation in response to the RotateSail input axis. Typically attached to a sail boom or mast that rotates horizontally. Requires an AdvancedShipController component on a parent GameObject.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ SailRotator

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [SailController](#) ([NWH.DWP2.SailController.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class SailRotator : MonoBehaviour
```

## Fields

### rotationAxis

Local axis around which the transform rotates. Default (0, 1, 0) rotates around the Y-axis. Use negative values to reverse rotation direction. Magnitude is ignored - only direction matters.

#### Declaration

```
[Tooltip("Rotation axis of this transform.\r\nUse -1 to reverse the rotation.")]  
public Vector3 rotationAxis
```

#### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )	

### rotationSpeed

Maximum rotation speed in degrees per second when input is at full deflection. Higher values allow faster sail adjustment. Combined with rotationAxis and player input to determine final rotation.

## Declaration

```
[Tooltip("Rotation speed of this transform in deg/s.\r\nMultiplied by the rotationAxis to get the final rotation.")]  
public float rotationSpeed
```

## Field Value

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Class WindGenerator

Generates procedural wind with randomized gusts for sail simulation. Creates realistic wind conditions by varying speed and direction over time. Provides a singleton instance accessible to all sail and wind-related components. Wind direction uses world coordinates where 0 degrees points along the positive Z-axis. Only one WindGenerator should exist per scene.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>)
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>)
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>)
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>)
- ↳ WindGenerator

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [SailController](#) ([NWH.DWP2.SailController.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class WindGenerator : MonoBehaviour
```

## Fields

## Instance

Singleton instance accessible globally. Used by SailController and HullWindApplicator to get current wind conditions.

## Declaration

```
public static WindGenerator Instance
```

## Field Value

Type	Description
<a href="#">WindGenerator</a> ( <a href="#">NWH.DWP2.SailController.WindGenerator.html</a> )	

## baseDirection

Primary wind direction in degrees on the horizontal plane. 0 degrees corresponds to positive Z-axis (north in Unity coordinates). Rotation follows the right-hand rule around the Y-axis. Wind will vary around this base direction within the limits of maxDirectionVariation.

## Declaration

```
[Tooltip("Base wind direction in degrees with 0 degrees indicating Z-forward ('north').")]  
public float baseDirection
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## baseSpeed

Average wind speed in meters per second. Wind will vary around this base speed within the limits of maxSpeedVariation. Typical sailing winds range from 5 m/s (light breeze) to 20 m/s (strong wind).

## Declaration

```
[Tooltip("Base wind speed in m/s.")]  
public float baseSpeed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## maxDirectionVariation

Maximum angular deviation from baseDirection during wind gusts. Measured in degrees. Higher values create more unpredictable wind shifts. Realistic values range from 15 to 45 degrees.

## Declaration

```
[Tooltip("Maximum possible variation of the direction in degrees from the\r\nbaseDirectio  
n.")]  
public float maxDirectionVariation
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## maxSpeedVariation

Maximum speed deviation from baseSpeed during wind gusts. Measured in meters per second. Higher values create stronger variations between lulls and gusts. Can be positive or negative relative to base speed.

## Declaration

```
[Tooltip("Maximum possible variation/deviation of the wind from the baseSpeed.")]  
public float maxSpeedVariation
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## maxVariationInterval

Longest possible duration between wind condition changes. Measured in seconds. New wind conditions are selected randomly between minVariationInterval and this value.

## Declaration

```
[Tooltip("Maximum interval between the wind variations / changes.")]  
public float maxVariationInterval
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## minVariationInterval

Shortest possible duration between wind condition changes. Measured in seconds. New wind conditions are selected randomly between this value and maxVariationInterval.

## Declaration

```
[Tooltip("Minimum interval between the wind variations / changes.")]  
public float minVariationInterval
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## Properties

## CurrentDirection

Current wind direction in degrees on the horizontal plane. Smoothly interpolates between randomized target directions. 0 degrees corresponds to positive Z-axis.

### Declaration

```
public float CurrentDirection { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## CurrentSpeed

Current wind speed magnitude in meters per second. Smoothly interpolates between randomized target speeds.

### Declaration

```
public float CurrentSpeed { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## CurrentWind

Current wind vector in world space. Combines CurrentDirection and CurrentSpeed into a directional velocity vector. Updated every FixedUpdate with smooth damping between gust transitions. Measured in meters per second.

### Declaration

```
public Vector3 CurrentWind { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

# Class WindIndicator

Visual indicator that rotates to show wind direction. Displays apparent wind when attached as a child of a SailController. Displays true wind from the WindGenerator when not under a SailController. Useful for debugging sail setup and helping players understand wind conditions. The transform's forward direction will point into the wind.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>)
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>)
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>)
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>)
- ↳ WindIndicator

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [SailController](#) ([NWH.DWP2.SailController.html](#)),

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class WindIndicator : MonoBehaviour
```

# Namespace NWH.DWP2.ShipController

## Classes

### **AdvancedShipController (NWH.DWP2.ShipController.AdvancedShipController.html)**

Main controller for ships, boats and other water vessels. Manages propulsion through engines and propellers, steering via rudders, and additional control through bow/stern thrusters. Includes stabilization systems, anchor functionality, and multiplayer support. Can be used for everything from small boats to large ships.

### **Anchor (NWH.DWP2.ShipController.Anchor.html)**

Approximates the behavior of a real anchor by keeping the object near the anchored position, but allowing for some movement.

### **Engine (NWH.DWP2.ShipController.Engine.html)**

Represents a ship engine and propeller system that generates thrust. Simulates RPM-based thrust generation with start/stop sequences and sound effects. Includes propeller efficiency modeling through thrust curves and support for reverse thrust. Multiple engines can be used per ship for differential thrust control.

### **InputManagerShipInputProvider (NWH.DWP2.ShipController.InputManagerShipInputProvider.html)**

Ship input provider for Unity's legacy Input Manager. Handles keyboard and gamepad input through `Input.GetAxis` and `Input.GetButton`. Requires proper axis and button setup in Project Settings > Input Manager. Falls back to hardcoded keys if input bindings are not configured.

### **InputSystemShipInputProvider (NWH.DWP2.ShipController.InputSystemShipInputProvider.html)**

Ship input provider for Unity's new Input System. Uses `ShipInputActions` asset for input binding configuration. Supports keyboard, gamepad, and custom input devices through the Input System. Input bindings can be modified by editing the `ShipInputActions` asset.

### **MobileShipInputProvider (NWH.DWP2.ShipController.MobileShipInputProvider.html)**

Ship input provider for mobile devices using on-screen UI controls. Reads input from Unity UI Sliders and `MobileInputButtons` placed in the scene. All control assignments are optional - assign only the controls you need for your ship.

### **Rudder (NWH.DWP2.ShipController.Rudder.html)**

Represents a ship rudder that rotates based on steering input. Provides visual rotation only - actual steering forces are applied by `WaterObject` components on the rudder itself. Multiple rudders can be used on a single ship.

### **ShipInputActions (NWH.DWP2.ShipController.ShipInputActions.html)**

Provides programmatic access to `UnityEngine.InputSystem.InputActionAsset`, `UnityEngine.InputSystem.InputActionMap`, `UnityEngine.InputSystem.InputAction` and `UnityEngine.InputSystem.InputControlScheme` instances defined in asset "`Packages/com.nwh.dynamicwaterphysics/Runtime/ShipController/Input/InputProviders/InputSystemProvider/ShipInputActions.inputactions`".

### **ShipInputHandler (NWH.DWP2.ShipController.ShipInputHandler.html)**

Manages ship input by retrieving values from active `ShipInputProviders` and storing them in `ShipInputStates`. Automatically polls all registered input providers and combines their inputs. Can be disabled for manual input control via scripting or AI.

### **ShipInputProvider (NWH.DWP2.ShipController.ShipInputProvider.html)**

Base class for all ship input providers. Inherit from this to create custom input systems for ship controls. Provides virtual methods for all ship control inputs including throttle, steering, thrusters, and submarine depth control.

### **Sink (NWH.DWP2.ShipController.Sink.html)**

Simulates a ship taking on water and sinking by gradually increasing mass over time. Works with `VariableCenterOfMass` component to affect buoyancy and cause the ship to sink. Can be triggered to simulate hull breaches or flooding.

### **Submarine (NWH.DWP2.ShipController.Submarine.html)**

Enables submarine functionality by controlling ballast mass for diving and surfacing. Manages depth control through variable mass and can automatically maintain horizontal orientation. Works with VariableCenterOfMass to adjust buoyancy for depth changes.

### **Thruster (NWH.DWP2.ShipController.Thruster.html)**

Lateral thruster for sideways ship movement. Bow thrusters are mounted at the front for tight turning and docking, stern thrusters at the rear. Multiple thrusters of each type can be added for increased lateral control.

## Structs

### **ShipInputActions.ShipControlsActions (NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html)**

Provides access to input actions defined in input action map "ShipControls".

### **ShipInputStates (NWH.DWP2.ShipController.ShipInputStates.html)**

Container for all ship input states. Stores current values for all ship controls including throttle, steering, thrusters, and special inputs.

## Interfaces

### **ShipInputActions.IShipControlsActions (NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html)**

Interface to implement callback methods for all input action callbacks associated with input actions defined by "ShipControls" which allows adding and removing callbacks.

## Enums

### **Engine.RotationDirection (NWH.DWP2.ShipController.Engine.RotationDirection.html)**

Visual rotation direction of the propeller.

### **Engine.State (NWH.DWP2.ShipController.Engine.State.html)**

Current operational state of the engine.

### **Engine.ThrottleBinding (NWH.DWP2.ShipController.Engine.ThrottleBinding.html)**

Which throttle input channel this engine responds to. Allows independent control of multiple engines on the same ship.

### **Thruster.RotationDirection (NWH.DWP2.ShipController.Thruster.RotationDirection.html)**

Visual rotation direction of the thruster propeller.

### **Thruster.ThrusterPosition (NWH.DWP2.ShipController.Thruster.ThrusterPosition.html)**

Position of the thruster on the ship. Determines which input controls it and the direction of thrust application.

# Class AdvancedShipController

Main controller for ships, boats and other water vessels. Manages propulsion through engines and propellers, steering via rudders, and additional control through bow/stern thrusters. Includes stabilization systems, anchor functionality, and multiplayer support. Can be used for everything from small boats to large ships.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [Vehicle](#) ([NWH.Common.Vehicles.Vehicle.html](#)).
- ↳ AdvancedShipController

## Inherited Members

---

[Vehicle.INPUT DEADZONE](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle INPUT DEADZONE](#))

[Vehicle.SPEED DEADZONE](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle SPEED DEADZONE](#))

[Vehicle.SMALL NUMBER](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle SMALL NUMBER](#)).

[Vehicle.KINDA SMALL NUMBER](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle KINDA SMALL NUMBER](#)).

[Vehicle.ActiveVehicles](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle ActiveVehicles](#)).

[Vehicle.onActiveVehicleChanged](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle onActiveVehicleChanged](#)).

[Vehicle.isPlayerControllable](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle isPlayerControllable](#)).

[Vehicle.vehicleRigidbody](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle vehicleRigidbody](#)).

[Vehicle.vehicleTransform](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle vehicleTransform](#)).

[Vehicle.ActiveVehicle](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle ActiveVehicle](#)).

[Vehicle.Awake\(\)](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle Awake](#)).

[Vehicle.CameraInsideVehicle](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle CameraInsideVehicle](#)).

[Vehicle.onCameraEnterVehicle](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle onCameraEnterVehicle](#)).

[Vehicle.onCameraExitVehicle](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle onCameraExitVehicle](#)).

[Vehicle.onDisable](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle onDisable](#)).

[Vehicle.onEnable](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle onEnable](#)).

[Vehicle.MultiplayerIsRemote](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle MultiplayerIsRemote](#)).

[Vehicle.onMultiplayerStatusChanged](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle onMultiplayerStatusChanged](#)).

[Vehicle.LocalAcceleration](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle LocalAcceleration](#)).

[Vehicle.LocalForwardAcceleration](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle LocalForwardAcceleration](#)).

[Vehicle.LocalForwardVelocity](#)

([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle LocalForwardVelocity](#)).

[Vehicle.LocalVelocity](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle LocalVelocity](#)). 292 / 454

[Vehicle.Speed](#) (NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle Speed),  
[Vehicle.SpeedSigned](#) (NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle SpeedSigned),  
[Vehicle.Velocity](#) (NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle Velocity),  
[Vehicle.VelocityMagnitude](#)  
(NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle VelocityMagnitude),  
[Vehicle.AngularVelocity](#) (NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle AngularVelocity),  
[Vehicle.AngularVelocityMagnitude](#)  
(NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle AngularVelocityMagnitude).

**Namespace:** [NWH](#) (NWH.html), [DWP2](#) (NWH.DWP2.html), [ShipController](#) (NWH.DWP2.ShipController.html)

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(Anchor))]  
[Serializable]  
[DefaultExecutionOrder(90)]  
public class AdvancedShipController : Vehicle
```

## Fields

### dropAnchorWhenInactive

Should the anchor be dropped when the ship is deactivated?

#### Declaration

```
[Tooltip("Should the anchor be dropped when the ship is deactivated?")]  
public bool dropAnchorWhenInactive
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> (https://learn.microsoft.com/dotnet/api/system.boolean).	

## engines

Ship's engines.

#### Declaration

```
[Tooltip("List of engines. Each engine is a propulsion system in itself consisting of the engine and the propeller.")]  
[SerializeField]  
public List<Engine> engines
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> ) < <a href="#">Engine</a> ( <a href="#">NWH.DWP2.ShipController.Engine.html</a> )>	

## input

Class that handles all of the user input.

### Declaration

```
[SerializeField]  
[Tooltip("Class that handles all of the user input.")]  
public ShipInputHandler input
```

## Field Value

Type	Description
<a href="#">ShipInputHandler</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputHandler.html</a> ).	

## maxStabilizationTorqueAngle

Angle at which roll stabilization torque reaches maximum.

### Declaration

```
[Tooltip("Angle at which roll stabilization torque reaches maximum.")]  
public float maxStabilizationTorqueAngle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## onShipInitialized

Called after ship initialization.

### Declaration

```
[Tooltip("Called after ship initialization.")]  
public UnityEvent onShipInitialized
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> ).	

## pitchStabilizationMaxTorque

Torque that will be applied to stabilize pitch when the ship pitch angle reaches maxStabilizationTorqueAngle.

### Declaration

```
[Tooltip("Torque that will be applied to stabilize pitch when the ship pitch angle reaches m  
axStabilizationTorqueAngle.")]  
public float pitchStabilizationMaxTorque
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## referenceWaterObject

### Declaration

```
[FormerlySerializedAs("ReferenceWaterObject")]  
public WaterObject referenceWaterObject
```

## Field Value

Type	Description
<a href="NWH.DWP2.WaterObjects.WaterObject.html">WaterObject</a> ( <a href="NWH.DWP2.WaterObjects.WaterObject.html">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	

## rollStabilizationMaxTorque

Torque that will be applied to stabilize roll when the ship roll angle reaches maxStabilizationTorqueAngle.

### Declaration

```
[Tooltip("Torque that will be applied to stabilize roll when the ship roll angle reaches max  
StabilizationTorqueAngle.")]  
public float rollStabilizationMaxTorque
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## rudders

Ship's rudders.

### Declaration

```
[SerializeField]
[Tooltip("Ship's rudders.")]
public List<Rudder> rudders
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> ) < <a href="#">Rudder</a> ( <a href="#">NWH.DWP2.ShipController.Rudder.html</a> ), >	

## stabilizePitch

Should the ship pitch be stabilized?

### Declaration

```
[Tooltip("Should the ship pitch be stabilized?")]
public bool stabilizePitch
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## stabilizeRoll

Should the ship roll be stabilized?

### Declaration

```
[Tooltip("Should the ship roll be stabilized?")]
public bool stabilizeRoll
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## thrusters

Bow or stern thrusters that a ship has.

## Declaration

```
[SerializeField]
[Tooltip("Bow or stern thrusters that a ship has.")]
public List<Thruster> thrusters
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">List</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.list-1</a> ), <a href="#">Thruster</a> ( <a href="#">NWH.DWP2.ShipController.Thruster.html</a> )>	

## weighAnchorWhenActive

Should the anchor be weighed/lifted when the ship is activated?

## Declaration

```
[Tooltip("Should the anchor be weighed/lifted when the ship is activated?")]
public bool weighAnchorWhenActive
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Properties

### Anchor

Anchor script.

## Declaration

```
public Anchor Anchor { get; }
```

## Property Value

Type	Description
<a href="#">Anchor</a> ( <a href="#">NWH.DWP2.ShipController.Anchor.html</a> ).	

### SpeedKnots

Speed in knots.

## Declaration

```
public float SpeedKnots { get; }
```

## Property Value

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Methods

## FixedUpdate()

### Declaration

```
public override void FixedUpdate()
```

### Overrides

[Vehicle.FixedUpdate\(\)](#) ([NWH.Common.Vehicles.Vehicle.html#NWH\\_Common\\_Vehicles\\_Vehicle\\_FixedUpdate](#))

## GetPitchAngle()

Returns pitch angle of the ship in degrees. Positive values indicate bow up, negative values indicate bow down.

### Declaration

```
public float GetPitchAngle()
```

### Returns

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Pitch angle in degrees.

## GetRollAngle()

Returns roll angle of the ship in degrees. Positive values indicate starboard side down, negative values indicate port side down.

### Declaration

```
public float GetRollAngle()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Roll angle in degrees.

## OnDisable()

### Declaration

```
public override void OnDisable()
```

### Overrides

[Vehicle.OnDisable\(\)](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle OnDisable](#)).

## OnEnable()

### Declaration

```
public override void OnEnable()
```

### Overrides

[Vehicle.OnEnable\(\)](#) ([NWH.Common.Vehicles.Vehicle.html#NWH Common Vehicles Vehicle OnEnable](#)).

## Start()

### Declaration

```
public void Start()
```

## Update()

### Declaration

```
public void Update()
```

## See Also

[Engine](#) ([NWH.DWP2.ShipController.Engine.html](#)).

[Rudder](#) ([NWH.DWP2.ShipController.Rudder.html](#)).

[Thruster](#) ([NWH.DWP2.ShipController.Thruster.html](#)).

[Anchor](#)

([NWH.DWP2.ShipController.AdvancedShipController.html#NWH DWP2 ShipController AdvancedShipController Anchor](#)).

[ShipInputHandler](#) ([NWH.DWP2.ShipController.ShipInputHandler.html](#)).

[WaterObject](#) ([NWH.DWP2.WaterObjects.WaterObject.html](#)).

[Vehicle](#) ([NWH.Common.Vehicles.Vehicle.html](#)).



# Class Anchor

Approximates the behavior of a real anchor by keeping the object near the anchored position, but allowing for some movement.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ Anchor

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class Anchor : MonoBehaviour
```

## Fields

### dragForce

Maximum force that can be applied to anchor before it starts to drag.

#### Declaration

```
[Tooltip("Maximum force that can be applied to anchor before it starts to drag.")]  
public float dragForce
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### dropOnStart

Should the anchor be dropped at start?

#### Declaration

```
[Tooltip("Should the anchor be dropped at start?")]  
public bool dropOnStart
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## forceCoefficient

Coefficient by which the force will be multiplied when the object starts pulling on the anchor.

### Declaration

```
[Tooltip("Coefficient by which the force will be multiplied when the object starts pulling on the anchor.")]  
public float forceCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## localAnchorPoint

Point in coordinates local to the object this script is attached to.

### Declaration

```
[Tooltip("Point in coordinates local to the object this script is attached to.")]  
public Vector3 localAnchorPoint
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## zeroForceRadius

Radius around anchor in which the chain/rope is slack and in which no force will be applied.

### Declaration

```
[Tooltip("Radius around anchor in which the chain/rope is slack and in which no force will be applied.")]  
public float zeroForceRadius
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

# Properties

## AnchorPoint

World space position of the anchor attachment point on the ship.

### Declaration

```
public Vector3 AnchorPoint { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a>	

## AnchorPosition

Position of the anchor.

### Declaration

```
public Vector3 AnchorPosition { get; set; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a>	

## Dropped

Has the anchor been dropped?

### Declaration

```
public bool Dropped { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a>	

## IsDragging

Is the anchor dragging on the floor?

### Declaration

```
public bool IsDragging { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## ParentRigidbody

Rigidbody to which the force will be applied.

### Declaration

```
public Rigidbody ParentRigidbody { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Rigidbody.html">Rigidbody</a> ( <a href="https://docs.unity3d.com/ScriptReference/Rigidbody.html">https://docs.unity3d.com/ScriptReference/Rigidbody.html</a> ).	

## Methods

### Drop()

Drops the anchor. Opposite of Weigh()

### Declaration

```
public void Drop()
```

### Weigh()

Weighs (retracts) the anchor.

### Declaration

```
public void Weigh()
```



# Class Engine

Represents a ship engine and propeller system that generates thrust. Simulates RPM-based thrust generation with start/stop sequences and sound effects. Includes propeller efficiency modeling through thrust curves and support for reverse thrust. Multiple engines can be used per ship for differential thrust control.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).  
↳ Engine

**Namespace:** [NWH \(NWH.html\)](#).[DWP2 \(NWH.DWP2.html\)](#).[ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(AdvancedShipController))]  
[Serializable]  
public class Engine
```

## Fields

### applyThrustWhenAboveWater

Should thrust be applied when above water?

#### Declaration

```
[Tooltip("Should thrust be applied when above water?")]  
public bool applyThrustWhenAboveWater
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### isOn

Is the engine currently on?

#### Declaration

```
[FormerlySerializedAs("_isOn")]  
[Tooltip("Is the engine currently on?")]  
public bool isOn
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## maxRPM

Max RPM of the engine.

### Declaration

```
[FormerlySerializedAs("_maxRPM")]  
[Tooltip("Max RPM of the engine.")]  
public float maxRPM
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## maxSpeed

Ship speed in m/s at which the propeller thrust drops to zero due to water flow matching propeller speed. Used with thrustCurve to determine thrust efficiency at different ship speeds.

### Declaration

```
[Tooltip("Ship speed at which propeller will reach its maximum rotational speed.")]  
public float maxSpeed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## maxThrust

Thrust at max RPM.

### Declaration

```
[FormerlySerializedAs("_maxThrust")]  
[Tooltip("Thrust at max RPM.")]  
public float maxThrust
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## minRPM

Min RPM of the engine.

### Declaration

```
[FormerlySerializedAs("_minRPM")]  
[Tooltip("Min RPM of the engine.")]  
public float minRPM
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## name

Display name for this engine.

### Declaration

```
public string name
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string (https://learn.microsoft.com/dotnet/api/system.string)</a>	

## pitch

Idle pitch of the engine

### Declaration

```
[Range(0, 2)]  
[Tooltip("Idle pitch of the engine")]  
public float pitch
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## pitchRange

Pitch range of the engine.

### Declaration

```
[Tooltip("Pitch range of the engine.")]  
[Range(0, 2)]  
public float pitchRange
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## propellerRpmRatio

Engine RPM will be multiplied by this value to get rotation speed of the propeller. Animation only.

### Declaration

```
[Tooltip("Engine RPM will be multiplied by this value to get rotation speed of the propelle  
r. Animation only.")]  
public float propellerRpmRatio
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## propellerTransform

Optional. Propeller transform. Visual rotation only, does not affect physics.

### Declaration

```
[Tooltip("Optional. Propeller transform. Visual rotation only, does not affect physics.")]  
public Transform propellerTransform
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## reverseThrustCoefficient

Amount of thrust that will be applied if ship is reversing

## Declaration

```
[Tooltip("Amount of thrust that will be applied if ship is reversing")]  
public float reverseThrustCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## rotationDirection

Direction of propeller rotation. Affects animation only.

## Declaration

```
[Tooltip("Direction of propeller rotation. Affects animation only.")]  
public Engine.RotationDirection rotationDirection
```

## Field Value

Type	Description
<a href="#">Engine (NWH.DWP2.ShipController.Engine.html)</a> . <a href="#">RotationDirection (NWH.DWP2.ShipController.Engine.RotationDirection.html)</a>	

## rudderTransform

Optional. Only use if you vessel has propeller mounted to the rudder (as in outboard engines). Propulsion force direction will be rotated with rudder if assigned.

## Declaration

```
[Tooltip("Optional. Only use if you vessel has propeller mounted to the rudder (as in outboard engines). Propulsion force direction will be rotated with rudder if assigned.")]  
public Transform rudderTransform
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform (https://docs.unity3d.com/ScriptReference/Transform.html)</a>	

## runningSource

Engine running audio source.

## Declaration

```
[Tooltip("Engine running audio source.")]  
public AudioSource runningSource
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AudioSource.html">AudioSource (https://docs.unity3d.com/ScriptReference/AudioSource.html)</a>	

## spinUpTime

Time needed to spin up the engines up to max RPM

## Declaration

```
[FormerlySerializedAs("_spinUpTime")]  
[Tooltip("Time needed to spin up the engines up to max RPM")]  
public float spinUpTime
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## startDuration

How long the engine starting phase take?

## Declaration

```
[Tooltip("How long the engine starting phase take?")]  
public float startDuration
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## startOnThrottle

Should the engine start when the throttle is applied?

## Declaration

```
[Tooltip("Should the engine start when the throttle is applied?")]  
public bool startOnThrottle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## startingRPM

Engine RPM when turning over. Used to determine starting sound pitch.

## Declaration

```
[FormerlySerializedAs("startingRpm")]  
[Tooltip("Engine RPM when turning over. Used to determine starting sound pitch.")]  
public float startingRPM
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## startingSource

Engine starting source.

## Declaration

```
[Tooltip("Engine starting source.")]  
public AudioSource startingSource
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AudioSource.html">AudioSource</a> ( <a href="https://docs.unity3d.com/ScriptReference/AudioSource.html">https://docs.unity3d.com/ScriptReference/AudioSource.html</a> ).	

## stopDuration

How long will the engine stopping phase take?

## Declaration

```
[Tooltip("How long will the engine stopping phase take?")]  
public float stopDuration
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## stoppingSource

Engine stopping source.

## Declaration

```
[Tooltip("Engine stopping source.")]  
public AudioSource stoppingSource
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AudioSource.html">AudioSource</a> ( <a href="https://docs.unity3d.com/ScriptReference/AudioSource.html">https://docs.unity3d.com/ScriptReference/AudioSource.html</a> ).	

## throttleBinding

Which throttle input this engine responds to.

## Declaration

```
public Engine.ThrottleBinding throttleBinding
```

## Field Value

Type	Description
<a href="#">Engine</a> ( <a href="#">NWH.DWP2.ShipController.Engine.html</a> ).	
<a href="#">ThrottleBinding</a> ( <a href="#">NWH.DWP2.ShipController.Engine.ThrottleBinding.html</a> ).	

## thrustCurve

Thrust curve of the propeller. X axis is speed in m/s and y axis is efficiency.

## Declaration

```
[Tooltip("Thrust curve of the propeller. X axis is speed in m/s and y axis is efficiency.")]  
public AnimationCurve thrustCurve
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">AnimationCurve</a> ( <a href="https://docs.unity3d.com/ScriptReference/AnimationCurve.html">https://docs.unity3d.com/ScriptReference/AnimationCurve.html</a> ).	

## thrustDirection

Local direction in which the force will be applied. Does not affect the rotation of the propeller, which always happens around the local Z-axis of the propeller transform.

### Declaration

```
[Tooltip("Local direction in which the force will be applied. Does not affect the rotation of the propeller, which always happens around the local Z-axis of the propeller transform.")]  
public Vector3 thrustDirection
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## thrustPosition

Local position where the thrust is applied, relative to ship.

### Declaration

```
[Tooltip("Local position where the thrust is applied, relative to ship.")]  
public Vector3 thrustPosition
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## volume

Base volume of the engine

### Declaration

```
[Range(0, 2)]  
[Tooltip("Base volume of the engine")]  
public float volume
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> (https://learn.microsoft.com/dotnet/api/system.single).	

## volumeRange

Volume range of the engine.

### Declaration

```
[Tooltip("Volume range of the engine.")]  
[Range(0, 2)]  
public float volumeRange
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> (https://learn.microsoft.com/dotnet/api/system.single).	

# Properties

## EngineState

Current state of the engine (On, Off, Starting, or Stopping).

### Declaration

```
public Engine.State EngineState { get; set; }
```

## Property Value

Type	Description
<a href="#">Engine</a> (NWH.DWP2.ShipController.Engine.html). <a href="#">State</a> (NWH.DWP2.ShipController.Engine.State.html).	

## RPM

Current RPM of the engine

### Declaration

```
public float RPM { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## RpmPercent

Current RPM as a normalized value between 0 (minRPM) and 1 (maxRPM). Used for sound pitch and volume calculations.

### Declaration

```
public float RpmPercent { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## Submerged

True if the engine's thrust position is currently underwater. When false, the engine will not generate thrust unless `applyThrustWhenAboveWater` is enabled.

### Declaration

```
public bool Submerged { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a>	

## Thrust

Current thrust being generated by the engine and propeller in Newtons.

### Declaration

```
public float Thrust { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## ThrustDirection

Direction of thrust force in world coordinates.

### Declaration

```
public Vector3 ThrustDirection { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## ThrustPosition

Point at which thrust will be applied to the Rigidbody, in world coordinates.

### Declaration

```
public Vector3 ThrustPosition { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## Methods

### Initialize(AdvancedShipController)

Initializes the engine with a reference to its parent ship controller.

### Declaration

```
public void Initialize(AdvancedShipController sc)
```

### Parameters

Type	Name	Description
<a href="#">AdvancedShipController</a> ( <a href="#">NWH.DWP2.ShipController.AdvancedShipController.html</a> ).	sc	The ship controller this engine belongs to.

### SetDefaults()

Sets all engine parameters to default values suitable for most ships.

## Declaration

```
public void SetDefaults()
```

## SoundInit()

Initializes engine sound sources.

## Declaration

```
public virtual void SoundInit()
```

## SoundUpdate()

Updates engine sound pitch and volume based on RPM and state.

## Declaration

```
public virtual void SoundUpdate()
```

## StartEngine()

Starts the ship engine.

## Declaration

```
public void StartEngine()
```

## StopEngine()

Stops the ship engine.

## Declaration

```
public void StopEngine()
```

## Update()

## Declaration

```
public virtual void Update()
```



# Enum Engine.RotationDirection

Visual rotation direction of the propeller.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum Engine.RotationDirection
```

## Fields

Name	Description
Left	
Right	

# Enum Engine.State

Current operational state of the engine.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum Engine.State
```

## Fields

Name	Description
Off	
On	
Starting	
Stopping	

# Enum Engine.ThrottleBinding

Which throttle input channel this engine responds to. Allows independent control of multiple engines on the same ship.

**Namespace:** [NWH \(NWH.html\)](#).[DWP2 \(NWH.DWP2.html\)](#).[ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum Engine.ThrottleBinding
```

## Fields

Name	Description
Throttle	
Throttle2	
Throttle3	
Throttle4	

# Class InputManagerShipInputProvider

Ship input provider for Unity's legacy Input Manager. Handles keyboard and gamepad input through `Input.GetAxis` and `Input.GetButton`. Requires proper axis and button setup in Project Settings > Input Manager. Falls back to hardcoded keys if input bindings are not configured.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](NWH.Common.Input.InputProvider.html) (<NWH.Common.Input.InputProvider.html>).
- ↳ [ShipInputProvider](NWH.DWP2.ShipController.ShipInputProvider.html) (<NWH.DWP2.ShipController.ShipInputProvider.html>).
- ↳ `InputManagerShipInputProvider`

## Inherited Members

---

- [ShipInputProvider.Steering\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Steering)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Steering](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Steering)).
- [ShipInputProvider.Throttle\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle)).
- [ShipInputProvider.Throttle2\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle2)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle2](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle2)).
- [ShipInputProvider.Throttle3\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle3)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle3](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle3)).
- [ShipInputProvider.Throttle4\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle4)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle4](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Throttle4)).
- [ShipInputProvider.SternThruster\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_SternThruster)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_SternThruster](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_SternThruster)).
- [ShipInputProvider.BowThruster\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_BowThruster)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_BowThruster](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_BowThruster)).
- [ShipInputProvider.SubmarineDepth\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_SubmarineDepth)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_SubmarineDepth](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_SubmarineDepth)).
- [ShipInputProvider.EngineStartStop\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_EngineStartStop)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_EngineStartStop](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_EngineStartStop)).
- [ShipInputProvider.Anchor\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Anchor)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Anchor](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_Anchor)).
- [ShipInputProvider.RotateSail\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_RotateSail)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_RotateSail](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_RotateSail)).
- [ShipInputProvider.DragObjectPosition\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_DragObjectPosition)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_DragObjectPosition](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_DragObjectPosition)).
- [ShipInputProvider.DragObjectModifier\(\)](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_DragObjectModifier)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_DragObjectModifier](NWH.DWP2.ShipController.ShipInputProvider.html#NWH_DWP2_ShipController_ShipInputProvider_DragObjectModifier)).
- [InputProvider.Instances](NWH.Common.Input.InputProvider.html#NWH_Common_Input_InputProvider_Instances) ([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_Instances](NWH.Common.Input.InputProvider.html#NWH_Common_Input_InputProvider_Instances)).
- [InputProvider.Awake\(\)](NWH.Common.Input.InputProvider.html#NWH_Common_Input_InputProvider_Awake) ([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_Awake](NWH.Common.Input.InputProvider.html#NWH_Common_Input_InputProvider_Awake)).
- [InputProvider.OnDestroy\(\)](NWH.Common.Input.InputProvider.html#NWH_Common_Input_InputProvider_OnDestroy)  
([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_OnDestroy](NWH.Common.Input.InputProvider.html#NWH_Common_Input_InputProvider_OnDestroy)).

[InputProvider.CombinedInput<T>\(Func<T, int>\)](#)

[\(NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32 \)](#)

[InputProvider.CombinedInput<T>\(Func<T, float>\)](#)

[\(NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single \)](#)

[InputProvider.CombinedInput<T>\(Func<T, bool>\)](#)

[\(NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean \)](#)

[InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#)

[\(NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2 \)](#)

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

### Syntax

```
[DisallowMultipleComponent]
public class InputManagerShipInputProvider : ShipInputProvider
```

# Class InputSystemShipInputProvider

Ship input provider for Unity's new Input System. Uses ShipInputActions asset for input binding configuration. Supports keyboard, gamepad, and custom input devices through the Input System. Input bindings can be modified by editing the ShipInputActions asset.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [ShipInputProvider](#) ([NWH.DWP2.ShipController.ShipInputProvider.html](#)).
- ↳ InputSystemShipInputProvider

## Inherited Members

---

[InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Instances](#)).

[InputProvider.OnDestroy\(\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider OnDestroy](#)).

[InputProvider.CombinedInput<T>\(Func<T, int>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32](#)).

[InputProvider.CombinedInput<T>\(Func<T, float>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single](#)).

[InputProvider.CombinedInput<T>\(Func<T, bool>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean](#)).

[InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#)

([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class InputSystemShipInputProvider : ShipInputProvider
```

## Fields

### shipInputActions

Input action asset containing all ship control bindings.

## Declaration

```
public ShipInputActions shipInputActions
```

## Field Value

Type	Description
<a href="#">ShipInputActions (NWH.DWP2.ShipController.ShipInputActions.html)</a>	

# Methods

## Anchor()

Toggle anchor drop/weigh state.

### Declaration

```
public override bool Anchor()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	True if anchor toggle was triggered this frame.

### Overrides

[ShipInputProvider.Anchor\(\)](#)

[\(NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Anchor\)](#)

## Awake()

### Declaration

```
public void Awake()
```

## BowThruster()

Bow thruster input from -1 to 1 for lateral movement at the front.

### Declaration

```
public override float BowThruster()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Bow thruster input value.

## Overrides

[ShipInputProvider.BowThruster\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_BowThruster](#)).

## DragObjectModifier()

Modifier key for object dragging.

### Declaration

```
public override bool DragObjectModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if drag modifier is held.

## Overrides

[ShipInputProvider.DragObjectModifier\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_DragObjectModifier](#)).

## DragObjectPosition()

Mouse or touch position for object dragging in demo scenes.

### Declaration

```
public override Vector2 DragObjectPosition()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	Drag position delta.

## Overrides

[ShipInputProvider.DragObjectPosition\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_DragObjectPosition](#)).

## EngineStartStop()

Toggle engine start/stop state.

## Declaration

```
public override bool EngineStartStop()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if engine start/stop was triggered this frame.

## Overrides

[ShipInputProvider.EngineStartStop\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_EngineStartStop](#)).

## RotateSail()

Sail rotation input for sailing vessels.

## Declaration

```
public override float RotateSail()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Sail rotation input value.

## Overrides

[ShipInputProvider.RotateSail\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_RotateSail](#)).

## Steering()

Horizontal steering input from -1 (port/left) to 1 (starboard/right).

## Declaration

```
public override float Steering()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Steering input value.

## Overrides

[ShipInputProvider.Steering\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Steering](#)).

## SternThruster()

Stern thruster input from -1 to 1 for lateral movement at the rear.

### Declaration

```
public override float SternThruster()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a> .	Stern thruster input value.

### Overrides

[ShipInputProvider.SternThruster\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_SternThruster](#)).

## SubmarineDepth()

Submarine depth control from -1 (surface) to 1 (dive).

### Declaration

```
public override float SubmarineDepth()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a> .	Submarine depth input value.

### Overrides

[ShipInputProvider.SubmarineDepth\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_SubmarineDepth](#)).

## Throttle()

Primary throttle input from -1 (full reverse) to 1 (full forward).

### Declaration

```
public override float Throttle()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a> .	Throttle input value.

## Overrides

[ShipInputProvider.Throttle\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle](#)).

## Throttle2()

Secondary throttle input for independent engine control.

### Declaration

```
public override float Throttle2()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle2 input value.

## Overrides

[ShipInputProvider.Throttle2\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle2](#)).

## Throttle3()

Tertiary throttle input for independent engine control.

### Declaration

```
public override float Throttle3()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle3 input value.

## Overrides

[ShipInputProvider.Throttle3\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle3](#)).

## Throttle4()

Quaternary throttle input for independent engine control.

### Declaration

```
public override float Throttle4()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle4 input value.

## Overrides

[ShipInputProvider.Throttle4\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle4](#)).

## Update()

### Declaration

```
public void Update()
```

# Class MobileShipInputProvider

Ship input provider for mobile devices using on-screen UI controls. Reads input from Unity UI Sliders and MobileInputButtons placed in the scene. All control assignments are optional - assign only the controls you need for your ship.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [ShipInputProvider](#) ([NWH.DWP2.ShipController.ShipInputProvider.html](#)).
- ↳ MobileShipInputProvider

## Inherited Members

---

- [ShipInputProvider.RotateSail\(\)](#)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_RotateSail](#)).
- [ShipInputProvider.DragObjectPosition\(\)](#)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_DragObjectPosition](#)).
- [ShipInputProvider.DragObjectModifier\(\)](#)  
([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_DragObjectModifier](#)).
- [InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_Instances](#)).
- [InputProvider.Awake\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_Awake](#)).
- [InputProvider.OnDestroy\(\)](#)  
([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_OnDestroy](#)).
- [InputProvider.CombinedInput<T>\(Func<T, int>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_CombinedInput\\_1\\_System\\_Func\\_0\\_System\\_Int32\\_](#)).
- [InputProvider.CombinedInput<T>\(Func<T, float>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_CombinedInput\\_1\\_System\\_Func\\_0\\_System\\_Single\\_](#)).
- [InputProvider.CombinedInput<T>\(Func<T, bool>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_CombinedInput\\_1\\_System\\_Func\\_0\\_System\\_Boolean\\_](#)).
- [InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#)  
([NWH.Common.Input.InputProvider.html#NWH\\_Common\\_Input\\_InputProvider\\_CombinedInput\\_1\\_System\\_Func\\_0\\_UnityEngine\\_Vector2\\_](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class MobileShipInputProvider : ShipInputProvider
```

# Fields

## anchorButton

Button for toggling anchor.

### Declaration

```
public MobileInputButton anchorButton
```

### Field Value

Type	Description
<a href="#">MobileInputButton (NWH.Common.Input.MobileInputButton.html)</a>	

## bowThrusterSlider

Slider for bow thruster control.

### Declaration

```
public Slider bowThrusterSlider
```

### Field Value

Type	Description
Slider	

## changeCameraButton

Button for changing camera in demo scenes.

### Declaration

```
public MobileInputButton changeCameraButton
```

### Field Value

Type	Description
<a href="#">MobileInputButton (NWH.Common.Input.MobileInputButton.html)</a>	

## changeShipButton

Button for changing ship in demo scenes.

## Declaration

```
public MobileInputButton changeShipButton
```

## Field Value

Type	Description
<a href="#">MobileInputButton (NWH.Common.Input.MobileInputButton.html)</a>	

## engineStartStopButton

Button for starting/stopping engines.

## Declaration

```
public MobileInputButton engineStartStopButton
```

## Field Value

Type	Description
<a href="#">MobileInputButton (NWH.Common.Input.MobileInputButton.html)</a>	

## steeringSlider

Slider for steering control.

## Declaration

```
public Slider steeringSlider
```

## Field Value

Type	Description
Slider	

## sternThrusterSlider

Slider for stern thruster control.

## Declaration

```
public Slider sternThrusterSlider
```

## Field Value

Type	Description
Slider	

## submarineDepthSlider

Slider for submarine depth control.

### Declaration

```
public Slider submarineDepthSlider
```

## Field Value

Type	Description
Slider	

## throttleSlider

Slider for primary throttle control.

### Declaration

```
public Slider throttleSlider
```

## Field Value

Type	Description
Slider	

## throttleSlider2

Slider for secondary throttle control.

### Declaration

```
public Slider throttleSlider2
```

## Field Value

Type	Description
Slider	

## throttleSlider3

Slider for tertiary throttle control.

### Declaration

```
public Slider throttleSlider3
```

### Field Value

Type	Description
Slider	

## throttleSlider4

Slider for quaternary throttle control.

### Declaration

```
public Slider throttleSlider4
```

### Field Value

Type	Description
Slider	

## Methods

### Anchor()

Toggle anchor drop/weigh state.

### Declaration

```
public override bool Anchor()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if anchor toggle was triggered this frame.

### Overrides

[ShipInputProvider.Anchor\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Anchor](#)).

## BowThruster()

Bow thruster input from -1 to 1 for lateral movement at the front.

### Declaration

```
public override float BowThruster()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Bow thruster input value.

### Overrides

[ShipInputProvider.BowThruster\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_BowThruster](#)).

## EngineStartStop()

Toggle engine start/stop state.

### Declaration

```
public override bool EngineStartStop()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	True if engine start/stop was triggered this frame.

### Overrides

[ShipInputProvider.EngineStartStop\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_EngineStartStop](#)).

## Steering()

Horizontal steering input from -1 (port/left) to 1 (starboard/right).

### Declaration

```
public override float Steering()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Steering input value.

## Overrides

[ShipInputProvider.Steering\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Steering](#)).

## SternThruster()

Stern thruster input from -1 to 1 for lateral movement at the rear.

### Declaration

```
public override float SternThruster()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Stern thruster input value.

## Overrides

[ShipInputProvider.SternThruster\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_SternThruster](#)).

## SubmarineDepth()

Submarine depth control from -1 (surface) to 1 (dive).

### Declaration

```
public override float SubmarineDepth()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Submarine depth input value.

## Overrides

[ShipInputProvider.SubmarineDepth\(\)](#)

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_SubmarineDepth](#)).

## Throttle()

Primary throttle input from -1 (full reverse) to 1 (full forward).

### Declaration

```
public override float Throttle()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> (https://learn.microsoft.com/dotnet/api/system.single).	Throttle input value.

## Overrides

[ShipInputProvider.Throttle\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle](#)).

## Throttle2()

Secondary throttle input for independent engine control.

### Declaration

```
public override float Throttle2()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> (https://learn.microsoft.com/dotnet/api/system.single).	Throttle2 input value.

## Overrides

[ShipInputProvider.Throttle2\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle2](#)).

## Throttle3()

Tertiary throttle input for independent engine control.

### Declaration

```
public override float Throttle3()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> (https://learn.microsoft.com/dotnet/api/system.single).	Throttle3 input value.

## Overrides

[ShipInputProvider.Throttle3\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle3](#)).

## Throttle4()

Quaternary throttle input for independent engine control.

## Declaration

```
public override float Throttle4()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle4 input value.

## Overrides

[ShipInputProvider.Throttle4\(\)](#).

([NWH.DWP2.ShipController.ShipInputProvider.html#NWH\\_DWP2\\_ShipController\\_ShipInputProvider\\_Throttle4](#)).

# Class Rudder

Represents a ship rudder that rotates based on steering input. Provides visual rotation only - actual steering forces are applied by WaterObject components on the rudder itself. Multiple rudders can be used on a single ship.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)  
↳ Rudder

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
[Serializable]  
public class Rudder
```

## Fields

### localRotationAxis

Axis around which the rudder will be rotated.

#### Declaration

```
[Tooltip("Axis around which the rudder will be rotated.")]  
public Vector3 localRotationAxis
```

#### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

### maxAngle

Max angle in degrees rudder will be able to reach.

#### Declaration

```
[Tooltip("Max angle in degrees rudder will be able to reach.")]  
public float maxAngle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## name

Name of the rudder. Can be any string.

### Declaration

```
[Tooltip("Name of the rudder. Can be any string.")]  
public string name
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a>	

## rotationSpeed

Rotation speed in degrees per second.

### Declaration

```
[Tooltip("Rotation speed in degrees per second.")]  
public float rotationSpeed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## rudderTransform

Transform representing the rudder.

### Declaration

```
[Tooltip("Transform representing the rudder.")]  
public Transform rudderTransform
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a>	

# Properties

## Angle

Current angle of the rudder in degrees. Positive angles indicate starboard turn, negative angles indicate port turn.

### Declaration

```
public float Angle { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## AnglePercent

Current rudder angle as a normalized value between -1 and 1.

### Declaration

```
public float AnglePercent { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

# Methods

## Initialize(AdvancedShipController)

Initializes the rudder with a reference to its parent ship controller.

### Declaration

```
public void Initialize(AdvancedShipController sc)
```

### Parameters

Type	Name	Description
<a href="http://NWH.DWP2.ShipController.AdvancedShipController.html">AdvancedShipController (NWH.DWP2.ShipController.AdvancedShipController.html)</a>	sc	The ship controller this rudder belongs to.

## Update()

### Declaration

```
public virtual void Update()
```

# Class ShipInputActions

Provides programmatic access to UnityEngine.InputSystem.InputActionAsset, UnityEngine.InputSystem.InputActionMap, UnityEngine.InputSystem.InputAction and UnityEngine.InputSystem.InputControlScheme instances defined in asset  
"Packages/com.nwh.dynamicwaterphysics/Runtime/ShipController/Input/InputProviders/InputSystemProvider/ShipInputActions.inputactions".

## Inheritance

---

↳ [object \(https://learn.microsoft.com/dotnet/api/system.object\)](https://learn.microsoft.com/dotnet/api/system.object)  
↳ ShipInputActions

## Implements

IInputActionCollection2

IInputActionCollection

[IEnumerable \(https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1\)](https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1).<InputAction>

[IEnumerable \(https://learn.microsoft.com/dotnet/api/system.collections.ienumerable\)](https://learn.microsoft.com/dotnet/api/system.collections.ienumerable).

[IDisposable \(https://learn.microsoft.com/dotnet/api/system.idisposable\)](https://learn.microsoft.com/dotnet/api/system.idisposable).

**Namespace:** [NWH \(NWH.html\)](#).[DWP2 \(NWH.DWP2.html\)](#).[ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class ShipInputActions : IInputActionCollection2, IInputActionCollection, IEnumerable<InputAction>, IEnumerable, IDisposable
```

## Remarks

This class is source generated and any manual edits will be discarded if the associated asset is reimported or modified.

## Examples

```
using namespace UnityEngine;
using UnityEngine.InputSystem;

// Example of using an InputActionMap named "Player" from a UnityEngine.MonoBehaviour implementing callback interface.
public class Example : MonoBehaviour, MyActions.IPlayerActions
{
    private MyActions_Actions m_Actions;           // Source code representation of asset.
    private MyActions_Actions.PlayerActions m_Player; // Source code representation of action map.

    void Awake()
    {
        m_Actions = new MyActions_Actions(); // Create asset object.
        m_Player = m_Actions.Player; // Extract action map object.
        m_Player.AddCallbacks(this); // Register callback interface IPlayerActions.
    }

    void OnDestroy()
    {
        m_Actions.Dispose(); // Destroy asset object.
    }

    void OnEnable()
    {
        m_Player.Enable(); // Enable all actions within map.
    }

    void OnDisable()
    {
        m_Player.Disable(); // Disable all actions within map.
    }

    #region Interface implementation of MyActions.IPlayerActions

    // Invoked when "Move" action is either started, performed or canceled.
    public void OnMove(InputAction.CallbackContext context)
    {
        Debug.Log($"OnMove: {context.ReadValue<Vector2>}");
    }

    // Invoked when "Attack" action is either started, performed or canceled.
    public void OnAttack(InputAction.CallbackContext context)
    {
        Debug.Log($"OnAttack: {context.ReadValue<float>}");
    }

    #endregion
}
```

## Constructors

### ShipInputActions()

Constructs a new instance.

#### Declaration

```
public ShipInputActions()
```

## Properties

## ShipControls

Provides a new [ShipInputActions.ShipControlsActions \(NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html\)](#) instance referencing this action map.

### Declaration

```
public ShipInputActions.ShipControlsActions ShipControls { get; }
```

### Property Value

Type	Description
<a href="#">ShipInputActions (NWH.DWP2.ShipController.ShipInputActions.html)</a> .	
<a href="#">ShipControlsActions (NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html)</a> .	

## asset

Provides access to the underlying asset instance.

### Declaration

```
public InputActionAsset asset { get; }
```

### Property Value

Type	Description
InputActionAsset	

## bindingMask

### Declaration

```
public InputBinding? bindingMask { get; set; }
```

### Property Value

Type	Description
InputBinding?	

## bindings

### Declaration

```
public IEnumerable<InputBinding> bindings { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">IEnumerable</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1</a> ) <InputBinding>	

## controlSchemes

## Declaration

```
public ReadOnlyArray<InputControlScheme> controlSchemes { get; }
```

## Property Value

Type	Description
ReadOnlyArray<InputControlScheme>	

## devices

### Declaration

```
public ReadOnlyArray<InputDevice>? devices { get; set; }
```

### Property Value

Type	Description
ReadOnlyArray<InputDevice>?	

## Methods

### Contains(InputAction)

#### Declaration

```
public bool Contains(InputAction action)
```

#### Parameters

Type	Name	Description
InputAction	<i>action</i>	

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### Disable()

#### Declaration

```
public void Disable()
```

### Dispose()

Destroys this asset and all associated UnityEngine.InputSystem.InputAction instances.

#### Declaration

```
public void Dispose()
```

## Enable()

### Declaration

```
public void Enable()
```

## ~ShipInputActions()

### Declaration

```
protected ~ShipInputActions()
```

## FindAction(string, bool)

### Declaration

```
public InputAction FindAction(string actionNameOrId, bool throwIfNotFound = false)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	<i>actionNameOrId</i>	
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>throwIfNotFound</i>	

### Returns

Type	Description
InputAction	

## FindBinding(InputBinding, out InputAction)

### Declaration

```
public int FindBinding(InputBinding bindingMask, out InputAction action)
```

### Parameters

Type	Name	Description
InputBinding	<i>bindingMask</i>	
InputAction	<i>action</i>	

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## GetEnumerator()

Returns an enumerator that iterates through the collection.

## Declaration

```
public IEnumerator<InputAction> GetEnumerator()
```

## Returns

Type	Description
<u><a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerator-1">IEnumerator</a></u> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerator-1">https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerator-1</a> ). <InputAction>	An enumerator that can be used to iterate through the collection.

## Implements

UnityEngine.InputSystem.IInputActionCollection2

UnityEngine.InputSystem.IInputActionCollection

[IEnumerable<T>](https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1) (<https://learn.microsoft.com/dotnet/api/system.collections.generic.ienumerable-1>).

[IEnumerable](https://learn.microsoft.com/dotnet/api/system.collections.ienumerable) (<https://learn.microsoft.com/dotnet/api/system.collections.ienumerable>).

[IDisposable](https://learn.microsoft.com/dotnet/api/system.idisposable) (<https://learn.microsoft.com/dotnet/api/system.idisposable>).

# Interface ShipInputActions.IShipControlsActions

Interface to implement callback methods for all input action callbacks associated with input actions defined by "ShipControls" which allows adding and removing callbacks.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public interface ShipInputActions.IShipControlsActions
```

## Methods

### OnAnchor(CallbackContext)

Method invoked when associated input action "Anchor" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

#### Declaration

```
void OnAnchor(InputAction.CallbackContext context)
```

#### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

#### See Also

[started](#)  
[performed](#)  
[canceled](#)

### OnBowThruster(CallbackContext)

Method invoked when associated input action "BowThruster" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

#### Declaration

```
void OnBowThruster(InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnEngineStartStop(CallbackContext)

Method invoked when associated input action "EngineStartStop" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

## Declaration

```
void OnEngineStartStop(UnityEngine.InputSystem.InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnRotateSail(CallbackContext)

Method invoked when associated input action "RotateSail" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

## Declaration

```
void OnRotateSail(UnityEngine.InputSystem.InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
UnityEngine.InputSystem.InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnSteering(CallbackContext)

Method invoked when associated input action "Steering" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnSteering(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)  
[performed](#)  
[canceled](#)

## OnSternThruster(CallbackContext)

Method invoked when associated input action "SternThruster" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnSternThruster(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)  
[performed](#)  
[canceled](#)

## OnSubmarineDepth(CallbackContext)

Method invoked when associated input action "SubmarineDepth" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnSubmarineDepth(InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnThrottle(CallbackContext)

Method invoked when associated input action "Throttle" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

## Declaration

```
void OnThrottle(InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnThrottle2(CallbackContext)

Method invoked when associated input action "Throttle2" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

## Declaration

```
void OnThrottle2(InputAction.CallbackContext context)
```

## Parameters

Type	Name	Description
InputAction.CallbackContext	<i>context</i>	

## See Also

started  
performed  
canceled

## OnThrottle3(CallbackContext)

Method invoked when associated input action "Throttle3" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnThrottle3(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)  
[performed](#)  
[canceled](#)

## OnThrottle4(CallbackContext)

Method invoked when associated input action "Throttle4" is either `UnityEngine.InputSystem.InputAction.started`, `UnityEngine.InputSystem.InputAction.performed` or `UnityEngine.InputSystem.InputAction.canceled`.

### Declaration

```
void OnThrottle4(InputAction.CallbackContext context)
```

### Parameters

Type	Name	Description
<code>InputAction.CallbackContext</code>	<i>context</i>	

### See Also

[started](#)  
[performed](#)  
[canceled](#)

## See Also

### [AddCallbacks](#)

[\(NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html#NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_ShipControlsActions\\_AddCallbacks\\_NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_IShipControlsActions\\_\)\(IShipControlsActions \(NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html\)\)](#)

### [RemoveCallbacks](#)

[\(NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html#NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_ShipControlsActions\\_RemoveCallbacks\\_NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_IShipControlsActions\\_\)\(IShipControlsActions \(NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html\)\)](#)



# Struct ShipInputActions.ShipControlsActions

Provides access to input actions defined in input action map "ShipControls".

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public struct ShipInputActions.ShipControlsActions
```

## Constructors

### ShipControlsActions(ShipInputActions)

Construct a new instance of the input action map wrapper class.

#### Declaration

```
public ShipControlsActions(ShipInputActions wrapper)
```

#### Parameters

Type	Name	Description
<a href="#">ShipInputActions (NWH.DWP2.ShipController.ShipInputActions.html)</a>	<i>wrapper</i>	

## Properties

### Anchor

Provides access to the underlying input action "ShipControls/Anchor".

#### Declaration

```
public InputAction Anchor { get; }
```

#### Property Value

Type	Description
InputAction	

## BowThruster

Provides access to the underlying input action "ShipControls/BowThruster".

### Declaration

```
public InputAction BowThruster { get; }
```

### Property Value

Type	Description
InputAction	

## EngineStartStop

Provides access to the underlying input action "ShipControls/EngineStartStop".

### Declaration

```
public InputAction EngineStartStop { get; }
```

### Property Value

Type	Description
InputAction	

## RotateSail

Provides access to the underlying input action "ShipControls/RotateSail".

### Declaration

```
public InputAction RotateSail { get; }
```

### Property Value

Type	Description
InputAction	

## Steering

Provides access to the underlying input action "ShipControls/Steering".

### Declaration

```
public InputAction Steering { get; }
```

## Property Value

Type	Description
InputAction	

## SternThruster

Provides access to the underlying input action "ShipControls/SternThruster".

### Declaration

```
public InputAction SternThruster { get; }
```

## Property Value

Type	Description
InputAction	

## SubmarineDepth

Provides access to the underlying input action "ShipControls/SubmarineDepth".

### Declaration

```
public InputAction SubmarineDepth { get; }
```

## Property Value

Type	Description
InputAction	

## Throttle

Provides access to the underlying input action "ShipControls/Throttle".

### Declaration

```
public InputAction Throttle { get; }
```

## Property Value

Type	Description
InputAction	

## Throttle2

Provides access to the underlying input action "ShipControls/Throttle2".

### Declaration

```
public InputAction Throttle2 { get; }
```

### Property Value

Type	Description
InputAction	

## Throttle3

Provides access to the underlying input action "ShipControls/Throttle3".

### Declaration

```
public InputAction Throttle3 { get; }
```

### Property Value

Type	Description
InputAction	

## Throttle4

Provides access to the underlying input action "ShipControls/Throttle4".

### Declaration

```
public InputAction Throttle4 { get; }
```

### Property Value

Type	Description
InputAction	

## enabled

### Declaration

```
public bool enabled { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Methods

### AddCallbacks(IShipControlsActions)

Adds UnityEngine.InputSystem.InputAction.started, UnityEngine.InputSystem.InputAction.performed and Unity Engine.InputSystem.InputAction.canceled callbacks provided via on all input actions contained in this map.

#### Declaration

```
public void AddCallbacks(ShipInputActions.IShipControlsActions instance)
```

#### Parameters

Type	Name	Description
<a href="#">ShipInputActions</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputActions.html</a> ), <a href="#">IShipControlsActions</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html</a> ).	<i>instance</i>	Callback instance.

#### Remarks

If instance is null or instance have already been added this method does nothing.

#### See Also

[ShipInputActions](#) ([NWH.DWP2.ShipController.ShipInputActions.html](#)), [ShipControlsActions](#) ([NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html](#)).

### Disable()

#### Declaration

```
public void Disable()
```

### Enable()

#### Declaration

```
public void Enable()
```

### Get()

Provides access to the underlying input action map instance.

## Declaration

```
public InputActionMap Get()
```

## Returns

Type	Description
InputActionMap	

## RemoveCallbacks(IShipControlsActions)

Unregisters and unregisters all input action callbacks via [UnregisterCallbacks\(IShipControlsActions\)](#) ([NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html](#)).

## Declaration

```
public void RemoveCallbacks(ShipInputActions.IShipControlsActions instance)
```

## Parameters

Type	Name	Description
<a href="#">ShipInputActions</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputActions.html</a> ), <a href="#">IShipControlsActions</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html</a> )	<i>instance</i>	

## See Also

[UnregisterCallbacks](#) ([NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html](#))([IShipControlsActions](#) ([NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html](#)))

## SetCallbacks(IShipControlsActions)

Replaces all existing callback instances and previously registered input action callbacks associated with them with callbacks provided via .

## Declaration

```
public void SetCallbacks(ShipInputActions.IShipControlsActions instance)
```

## Parameters

Type	Name	Description
<a href="#">ShipInputActions</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputActions.html</a> ), <a href="#">IShipControlsActions</a> ( <a href="#">NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html</a> )	<i>instance</i>	

## Remarks

If `instance` is `null`, calling this method will only unregister all existing callbacks but not register any new callbacks.

## See Also

[AddCallbacks\(IShipControlsActions\)](#)

[\(NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html#NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_ShipControlsActions\\_AddCallbacks\\_NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_IShipControlsActions\\_\)](#)

[RemoveCallbacks\(IShipControlsActions\)](#)

[\(NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html#NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_ShipControlsActions\\_RemoveCallbacks\\_NWH\\_DWP2\\_ShipController\\_ShipInputActions\\_IShipControlsActions\\_\)](#)

[UnregisterCallbacks \(NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html\)\(IShipControlsActions \(NWH.DWP2.ShipController.ShipInputActions.IShipControlsActions.html\)\)](#)

# Operators

## implicit operator InputActionMap(ShipControlsActions)

Implicitly converts an to an instance.

### Declaration

```
public static implicit operator InputActionMap(ShipInputActions.ShipControlsActions set)
```

### Parameters

Type	Name	Description
<a href="#">ShipInputActions (NWH.DWP2.ShipController.ShipInputActions.html)</a> . <a href="#">ShipControlsActions (NWH.DWP2.ShipController.ShipInputActions.ShipControlsActions.html)</a> .	set	

### Returns

Type	Description
InputActionMap	

# Class ShipInputHandler

Manages ship input by retrieving values from active ShipInputProviders and storing them in ShipInputStates. Automatically polls all registered input providers and combines their inputs. Can be disabled for manual input control via scripting or AI.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (https://learn.microsoft.com/dotnet/api/system.object).  
↳ ShipInputHandler

**Namespace:** [NWH](#) (NWH.html). [DWP2](#) (NWH.DWP2.html). [ShipController](#) (NWH.DWP2.ShipController.html).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[Serializable]  
public class ShipInputHandler
```

## Fields

### autoSetInput

When enabled input will be auto-retrieved from the InputProviders present in the scene. Disable to manually set the input through external scripts, i.e. AI controller.

#### Declaration

```
[Tooltip("When enabled input will be auto-retrieved from the InputProviders present in the scene.\r\nDisable to manually set the input through external scripts, i.e. AI controller.")]  
public bool autoSetInput
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> (https://learn.microsoft.com/dotnet/api/system.boolean).	

### modifyInputCallback

Callback invoked after input is processed each frame. Use this to modify input values programmatically before they are used.

#### Declaration

```
public UnityEvent modifyInputCallback
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">UnityEvent</a> ( <a href="https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html">https://docs.unity3d.com/ScriptReference/Events.UnityEvent.html</a> )	

## states

All the input states of the vehicle. Can be used to set input through scripting or copy the inputs over from other vehicle, such as truck to trailer.

### Declaration

```
[Tooltip("All the input states of the vehicle. Can be used to set input through scripting or copy the inputs\r\nover from other vehicle, such as truck to trailer.")]  
public ShipInputStates states
```

## Field Value

Type	Description
<a href="NWH.DWP2.ShipController.ShipInputStates.html">ShipInputStates</a> ( <a href="NWH.DWP2.ShipController.ShipInputStates.html">NWH.DWP2.ShipController.ShipInputStates.html</a> )	

# Properties

## Anchor

Anchor toggle state. True for one frame when anchor input is pressed.

### Declaration

```
public bool Anchor { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> )	

## BowThruster

Bow thruster input from -1 to 1.

### Declaration

```
public float BowThruster { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## EngineStartStop

Engine start/stop toggle state. True for one frame when toggle input is pressed.

### Declaration

```
public bool EngineStartStop { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## RotateSail

Sail rotation input for sailing vessels.

### Declaration

```
public float RotateSail { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Steering

Steering input from -1 (port/left) to 1 (starboard/right).

### Declaration

```
public float Steering { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## SternThruster

Stern thruster input from -1 to 1.

### Declaration

```
public float SternThruster { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## SubmarineDepth

Submarine depth control from -1 (surface) to 1 (dive).

### Declaration

```
public float SubmarineDepth { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## Throttle

Primary throttle input from -1 (full reverse) to 1 (full forward).

### Declaration

```
public float Throttle { get; set; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## Throttle2

Secondary throttle for independent engine control.

### Declaration

```
public float Throttle2 { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Throttle3

Tertiary throttle for independent engine control.

### Declaration

```
public float Throttle3 { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Throttle4

Quaternary throttle for independent engine control.

### Declaration

```
public float Throttle4 { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Methods

### Update()

Updates all input values from registered input providers. Called automatically by AdvancedShipController.

### Declaration

```
public void Update()
```



# Class ShipInputProvider

Base class for all ship input providers. Inherit from this to create custom input systems for ship controls. Provides virtual methods for all ship control inputs including throttle, steering, thrusters, and submarine depth control.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [InputProvider](#) ([NWH.Common.Input.InputProvider.html](#)).
- ↳ [ShipInputProvider](#)
  - ↳ [InputManagerShipInputProvider](#) ([NWH.DWP2.ShipController.InputManagerShipInputProvider.html](#)).
  - ↳ [InputSystemShipInputProvider](#) ([NWH.DWP2.ShipController.InputSystemShipInputProvider.html](#)).
  - ↳ [MobileShipInputProvider](#) ([NWH.DWP2.ShipController.MobileShipInputProvider.html](#)).

## Inherited Members

---

- [InputProvider.Instances](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Instances](#)).
- [InputProvider.Awake\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider Awake](#)).
- [InputProvider.OnDestroy\(\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider OnDestroy](#)).
- [InputProvider.CombinedInput<T>\(Func<T, int>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Int32](#)).
- [InputProvider.CombinedInput<T>\(Func<T, float>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Single](#)).
- [InputProvider.CombinedInput<T>\(Func<T, bool>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 System Boolean](#)).
- [InputProvider.CombinedInput<T>\(Func<T, Vector2>\)](#) ([NWH.Common.Input.InputProvider.html#NWH Common Input InputProvider CombinedInput 1 System Func 0 UnityEngine Vector2](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#))

**Assembly:** [NWH.DWP2.dll](#)

## Syntax

```
public abstract class ShipInputProvider : InputProvider
```

## Methods

### Anchor()

Toggle anchor drop/weight state.

## Declaration

```
public virtual bool Anchor()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if anchor toggle was triggered this frame.

## BowThruster()

Bow thruster input from -1 to 1 for lateral movement at the front.

## Declaration

```
public virtual float BowThruster()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Bow thruster input value.

## DragObjectModifier()

Modifier key for object dragging.

## Declaration

```
public virtual bool DragObjectModifier()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if drag modifier is held.

## DragObjectPosition()

Mouse or touch position for object dragging in demo scenes.

## Declaration

```
public virtual Vector2 DragObjectPosition()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2 (https://docs.unity3d.com/ScriptReference/Vector2.html)</a>	Drag position delta.

## EngineStartStop()

Toggle engine start/stop state.

### Declaration

```
public virtual bool EngineStartStop()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	True if engine start/stop was triggered this frame.

## RotateSail()

Sail rotation input for sailing vessels.

### Declaration

```
public virtual float RotateSail()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Sail rotation input value.

## Steering()

Horizontal steering input from -1 (port/left) to 1 (starboard/right).

### Declaration

```
public virtual float Steering()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Steering input value.

## SternThruster()

Stern thruster input from -1 to 1 for lateral movement at the rear.

### Declaration

```
public virtual float SternThruster()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Stern thruster input value.

## SubmarineDepth()

Submarine depth control from -1 (surface) to 1 (dive).

### Declaration

```
public virtual float SubmarineDepth()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Submarine depth input value.

## Throttle()

Primary throttle input from -1 (full reverse) to 1 (full forward).

### Declaration

```
public virtual float Throttle()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	Throttle input value.

## Throttle2()

Secondary throttle input for independent engine control.

### Declaration

```
public virtual float Throttle2()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle2 input value.

## Throttle3()

Tertiary throttle input for independent engine control.

### Declaration

```
public virtual float Throttle3()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle3 input value.

## Throttle4()

Quaternary throttle input for independent engine control.

### Declaration

```
public virtual float Throttle4()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Throttle4 input value.

# Struct ShipInputStates

Container for all ship input states. Stores current values for all ship controls including throttle, steering, thrusters, and special inputs.

**Namespace:** [NWH \(NWH.html\)](#).[DWP2 \(NWH.DWP2.html\)](#).[ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
[Serializable]
public struct ShipInputStates
```

## Fields

### anchor

Anchor drop/weigh toggle state.

#### Declaration

```
public bool anchor
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

### bowThruster

Bow thruster input from -1 to 1.

#### Declaration

```
[Range(-1, 1)]
public float bowThruster
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## changeCamera

Change camera input for demo scenes.

### Declaration

```
public bool changeCamera
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## changeShip

Change ship input for demo scenes.

### Declaration

```
public bool changeShip
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## engineStartStop

Engine start/stop toggle state.

### Declaration

```
public bool engineStartStop
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## rotateSail

Sail rotation input for sailing vessels.

## Declaration

```
[Range(-1, 1)]  
public float rotateSail
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## steering

Steering input from -1 (port/left) to 1 (starboard/right).

## Declaration

```
[Range(-1, 1)]  
public float steering
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## sternThruster

Stern thruster input from -1 to 1.

## Declaration

```
[Range(-1, 1)]  
public float sternThruster
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## submarineDepth

Submarine depth control from 0 (surface) to 1 (dive).

## Declaration

```
[Range(0, 1)]  
public float submarineDepth
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## throttle

Primary throttle from -1 (full reverse) to 1 (full forward).

### Declaration

```
[Range(-1, 1)]  
public float throttle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## throttle2

Secondary throttle for independent engine control.

### Declaration

```
[Range(-1, 1)]  
public float throttle2
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## throttle3

Tertiary throttle for independent engine control.

### Declaration

```
[Range(-1, 1)]  
public float throttle3
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a>	

## throttle4

Quaternary throttle for independent engine control.

### Declaration

```
[Range(-1, 1)]  
public float throttle4
```

### Field Value

Type	Description
float ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Methods

### Reset()

Resets all input states to default values.

### Declaration

```
public void Reset()
```

# Class Sink

Simulates a ship taking on water and sinking by gradually increasing mass over time. Works with VariableCenterOfMass component to affect buoyancy and cause the ship to sink. Can be triggered to simulate hull breaches or flooding.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ Sink

## Implements

[IMassAffector](https://docs.unity3d.com/ScriptReference/NWH.Common.CoM.IMassAffector.html) ([NWH.Common.CoM.IMassAffector.html](https://docs.unity3d.com/ScriptReference/NWH.Common.CoM.IMassAffector.html)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class Sink : MonoBehaviour, IMassAffector
```

## Fields

### addedMassPercentPerSecond

Rate at which mass is added per second as a percentage of maxAdditionalMass. Higher values cause faster sinking.

#### Declaration

```
[Tooltip("Percentage of initial mass that will be added each second to imitate water ingres  
s")]  
public float addedMassPercentPerSecond
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### maxAdditionalMass

Maximum mass in kg that can be added through flooding. This represents the total water mass that can enter the ship.

## Declaration

```
[Tooltip("Maximum added mass after water ingress. 1f = 100% of original mass, 2f = 200% of original mass, etc.")]  
public float maxAdditionalMass
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## Methods

### GetMass()

Current mass of this affector in kilograms. Should return variable values for fuel tanks, cargo, etc.

#### Declaration

```
public float GetMass()
```

#### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Mass in kg

### GetTransform()

Returns transform of the mass affector.

#### Declaration

```
public Transform GetTransform()
```

#### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

### GetWorldCenterOfMass()

World position of this affector's center of mass. Used for weighted center of mass calculations.

## Declaration

```
public Vector3 GetWorldCenterOfMass()
```

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## ResetMass()

Resets the added mass to zero, returning the ship to its original mass.

## Declaration

```
public void ResetMass()
```

## SinkCoroutine()

Coroutine that gradually increases mass to simulate water ingress.

## Declaration

```
public IEnumerator SinkCoroutine()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.collections.ienumerator">IEnumerator</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.collections.ienumerator">https://learn.microsoft.com/dotnet/api/system.collections.ienumerator</a> ).	

## StartSinking()

Begins the sinking process by starting mass increase over time.

## Declaration

```
public void StartSinking()
```

## StopSinking()

Stops the sinking process. Added mass remains until reset.

## Declaration

```
public void StopSinking()
```

# Implements

[IMassAffector \(NWH.Common.CoM.IMassAffector.html\)](#)

# Class Submarine

Enables submarine functionality by controlling ballast mass for diving and surfacing. Manages depth control through variable mass and can automatically maintain horizontal orientation. Works with `VariableCenterOfMass` to adjust buoyancy for depth changes.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ Submarine

## Implements

[IMassAffector](https://docs.unity3d.com/ScriptReference/NWH.Common.CoM.IMassAffector.html) ([NWH.Common.CoM.IMassAffector.html](https://docs.unity3d.com/ScriptReference/NWH.Common.CoM.IMassAffector.html)).

**Namespace:** [NWH](https://docs.unity3d.com/ScriptReference/NWH.html) ([NWH.html](https://docs.unity3d.com/ScriptReference/NWH.html)), [DWP2](https://docs.unity3d.com/ScriptReference/NWH.DWP2.html) ([NWH.DWP2.html](https://docs.unity3d.com/ScriptReference/NWH.DWP2.html)), [ShipController](https://docs.unity3d.com/ScriptReference/NWH.DWP2.ShipController.html) ([NWH.DWP2.ShipController.html](https://docs.unity3d.com/ScriptReference/NWH.DWP2.ShipController.html)).

**Assembly:** `NWH.DWP2.dll`

## Syntax

```
[RequireComponent(typeof(AdvancedShipController))]  
[RequireComponent(typeof(VariableCenterOfMass))]  
[DefaultExecutionOrder(500)]  
public class Submarine : MonoBehaviour, IMassAffector
```

## Fields

### ReferenceWaterObject

Reference to the `WaterObject` used for water level detection.

#### Declaration

```
public WaterObject ReferenceWaterObject
```

#### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/NWH.DWP2.WaterObjects.WaterObject.html">WaterObject</a> ( <a href="https://docs.unity3d.com/ScriptReference/NWH.DWP2.WaterObjects.WaterObject.html">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	

### ballastChangeSpeed

Speed of change of the ballast mass, as a percentage of `maxBallastMass`.

## Declaration

```
[Tooltip("Speed of change of the ballast mass, as a percentage of maxBallastMass.")]  
public float ballastChangeSpeed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## keepHorizontal

If enabled submarine will try to keep horizontal by shifting the center of mass.

## Declaration

```
[Tooltip("If enabled submarine will try to keep horizontal by shifting the center of mass.")]  
public bool keepHorizontal
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## keepHorizontalSensitivity

Sensitivity of calculation trying to keep the submarine horizontal. Higher number will mean faster reaction.

## Declaration

```
[Tooltip("Sensitivity of calculation trying to keep the submarine horizontal. Higher number will mean faster reaction.")]  
public float keepHorizontalSensitivity
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## maxBallastMass

Maximum ballast mass in kg that can be added to make the submarine sink. Higher values allow diving deeper and faster but require more time to surface.

## Declaration

```
[FormerlySerializedAs("maxAdditionalMass")]  
[FormerlySerializedAs("maxMassFactor")]  
[Tooltip("Maximum additional mass that can be added (taking on water) to the base mass of the rigidbody to make submarine sink.")]  
public float maxBallastMass
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## maxMassOffset

Maximum rigidbody center of mass offset that can be used to keep the submarine level.

## Declaration

```
[Tooltip("Maximum rigidbody center of mass offset that can be used to keep the submarine level.")]  
public float maxMassOffset
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

# Properties

## DepthInput

Input for depth control from -1 (surface) to 1 (dive). Positive values add ballast mass to sink, negative values reduce it to surface.

## Declaration

```
public float DepthInput { get; set; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

# Methods

## GetMass()

Current mass of this affector in kilograms. Should return variable values for fuel tanks, cargo, etc.

### Declaration

```
public float GetMass()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Mass in kg

## GetTransform()

Returns transform of the mass affector.

### Declaration

```
public Transform GetTransform()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## GetWorldCenterOfMass()

World position of this affector's center of mass. Used for weighted center of mass calculations.

### Declaration

```
public Vector3 GetWorldCenterOfMass()
```

### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## Implements

[IMassAffector](#) ([NWH.Common.CoM.IMassAffector.html](#)).



# Class Thruster

Lateral thruster for sideways ship movement. Bow thrusters are mounted at the front for tight turning and docking, stern thrusters at the rear. Multiple thrusters of each type can be added for increased lateral control.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).

↳ Thruster

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [ShipController](#) ([NWH.DWP2.ShipController.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[Serializable]
public class Thruster
```

## Fields

### maxThrust

Maximum thrust force in Newtons.

#### Declaration

```
[Tooltip("Max thrust in [N].")]
public float maxThrust
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### name

Display name for this thruster.

#### Declaration

```
[Tooltip("Name of the thruster - can be any string.")]
public string name
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.string">string</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.string">https://learn.microsoft.com/dotnet/api/system.string</a> ).	

## position

Position relative to ship transform where thrust force is applied.

### Declaration

```
[Tooltip("Relative force application position.")]  
public Vector3 position
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## propellerRotationDirection

### Declaration

```
[FormerlySerializedAs("rotationDirection")]  
[Tooltip("Rotation direction of the propeller. Visual only.")]  
public Thruster.RotationDirection propellerRotationDirection
```

## Field Value

Type	Description
<a href="#">Thruster</a> ( <a href="#">NWH.DWP2.ShipController.Thruster.html</a> ).	
<a href="#">RotationDirection</a> ( <a href="#">NWH.DWP2.ShipController.Thruster.RotationDirection.html</a> ).	

## propellerRotationSpeed

### Declaration

```
[Tooltip("Rotation speed of the propeller if assigned. Visual only.")]  
public float propellerRotationSpeed
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## propellerTransform

### Declaration

```
[Tooltip("Optional. Transform representing a propeller. Visual only.")]  
public Transform propellerTransform
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	

## spinUpSpeed

### Declaration

```
[Tooltip("Time needed to reach maxThrust.")]  
public float spinUpSpeed
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## thrusterPosition

Whether this is a bow or stern thruster.

### Declaration

```
public Thruster.ThrusterPosition thrusterPosition
```

### Field Value

Type	Description
<a href="#">Thruster</a> ( <a href="#">NWH.DWP2.ShipController.Thruster.html</a> ).	
<a href="#">ThrusterPosition</a> ( <a href="#">NWH.DWP2.ShipController.Thruster.ThrusterPosition.html</a> ).	

## Properties

### Input

Current input value for this thruster from -1 to 1. Automatically retrieves from the appropriate input channel based on thrusterPosition.

## Declaration

```
public float Input { get; }
```

## Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## WorldPosition

World space position where thrust force is applied.

## Declaration

```
public Vector3 WorldPosition { get; }
```

## Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## Methods

### Initialize(AdvancedShipController)

Initializes the thruster with a reference to its parent ship controller.

## Declaration

```
public void Initialize(AdvancedShipController sc)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/AdvancedShipController.html">AdvancedShipController</a> ( <a href="https://docs.unity3d.com/ScriptReference/AdvancedShipController.html">NWH.DWP2.ShipController.AdvancedShipController.html</a> ).	sc	The ship controller this thruster belongs to.

### Update()

## Declaration

```
public virtual void Update()
```



# Enum Thruster.RotationDirection

Visual rotation direction of the thruster propeller.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum Thruster.RotationDirection
```

## Fields

Name	Description
Left	
Right	

# Enum Thruster.ThrusterPosition

Position of the thruster on the ship. Determines which input controls it and the direction of thrust application.

**Namespace:** [NWH \(NWH.html\)](#), [DWP2 \(NWH.DWP2.html\)](#), [ShipController \(NWH.DWP2.ShipController.html\)](#)

**Assembly:** NWH.DWP2.dll

## Syntax

```
public enum Thruster.ThrusterPosition
```

## Fields

Name	Description
BowThruster	
SternThruster	

# Namespace NWH.DWP2.WaterData

## Classes

### **FlatWaterDataProvider (NWH.DWP2.WaterData.FlatWaterDataProvider.html)**

Simple water data provider for flat, static water surfaces. Uses a constant water height based on the transform's Y position. Does not support water height queries, waves, normals, or flow.

### **RaycastWaterDataProvider (NWH.DWP2.WaterData.RaycastWaterDataProvider.html)**

Water data provider that uses raycasting to detect water surface. Works with any water system that has a collider. Supports water height and normal queries through raycasting. Uses Unity's job system for parallel raycasts.

### **WaterDataProvider (NWH.DWP2.WaterData.WaterDataProvider.html)**

Base class for providing water surface data to WaterObjects. Implementations provide water height, flow velocity, and surface normal information. Uses a trigger collider to automatically detect and register WaterObjects that enter the water. Inherit from this class to create adapters for different water systems.

# Class FlatWaterDataProvider

Simple water data provider for flat, static water surfaces. Uses a constant water height based on the transform's Y position. Does not support water height queries, waves, normals, or flow.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>)
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>)
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>)
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>)
- ↳ [WaterDataProvider](#) ([NWH.DWP2.WaterData.WaterDataProvider.html](#))
- ↳ FlatWaterDataProvider

## Inherited Members

---

[WaterDataProvider.singleHeightArray](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_singleHeightArray](#)).

[WaterDataProvider.singlePointArray](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_singlePointArray](#)).

[WaterDataProvider.triggerCollider](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_triggerCollider](#)).

[WaterDataProvider.Awake\(\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_Awake](#)).

[WaterDataProvider.GetWaterFlows\(WaterObject, ref Vector3\[\], ref Vector3\[\]\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterFlows\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.GetWaterNormals\(WaterObject, ref Vector3\[\], ref Vector3\[\]\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterNormals\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.GetWaterHeightsFlowsNormals\(WaterObject, ref Vector3\[\], ref float\[\], ref Vector3\[\], ref Vector3\[\], bool, bool, bool\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeightsFlowsNormals\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_System\\_Single\\_UnityEngine\\_Vector3\\_UnityEngine\\_Vector3\\_System\\_Boolean\\_System\\_Boolean\\_System\\_Boolean\\_](#)).

[WaterDataProvider.GetWaterHeightSingle\(WaterObject, Vector3\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeightSingle\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.PointInWater\(WaterObject, Vector3\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_PointInWater\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.GetWaterHeight\(WaterObject, Vector3\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeight\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterData](#) ([NWH.DWP2.WaterData.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class FlatWaterDataProvider : WaterDataProvider
```

# Methods

## GetWaterHeights(WaterObject, ref Vector3[], ref float[])

Returns water height at each given point. Override this method to provide water height data from your water system.

### Declaration

```
public override void GetWaterHeights(WaterObject waterObject, ref Vector3[] points, ref float[] waterHeights)
```

### Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ), []	<i>points</i>	Position array in world coordinates.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ), []	<i>waterHeights</i>	Water height array in world coordinates. Corresponds to positions.

### Overrides

[WaterDataProvider.GetWaterHeights\(WaterObject, ref Vector3\[\], ref float\[\]\)](#).  
([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeights\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_System\\_Single\\_](#)).

## SupportsWaterFlowQueries()

Does this water system support water velocity queries?

### Declaration

```
public override bool SupportsWaterFlowQueries()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

### Overrides

[WaterDataProvider.SupportsWaterFlowQueries\(\)](#).  
([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_SupportsWaterFlowQueries](#)).

## SupportsWaterHeightQueries()

Does this water system support water height queries?

### Declaration

```
public override bool SupportsWaterHeightQueries()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

### Overrides

[WaterDataProvider.SupportsWaterHeightQueries\(\)](#).

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_SupportsWaterHeightQueries](#)).

## SupportsWaterNormalQueries()

Does this water system support water normal queries?

### Declaration

```
public override bool SupportsWaterNormalQueries()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

### Overrides

[WaterDataProvider.SupportsWaterNormalQueries\(\)](#).

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_SupportsWaterNormalQueries](#)).

# Class RaycastWaterDataProvider

Water data provider that uses raycasting to detect water surface. Works with any water system that has a collider. Supports water height and normal queries through raycasting. Uses Unity's job system for parallel raycasts.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ [WaterDataProvider](#) ([NWH.DWP2.WaterData.WaterDataProvider.html](#)).
- ↳ RaycastWaterDataProvider

## Inherited Members

---

[WaterDataProvider.singleHeightArray](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_singleHeightArray](#)).

[WaterDataProvider.singlePointArray](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_singlePointArray](#)).

[WaterDataProvider.triggerCollider](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_triggerCollider](#)).

[WaterDataProvider.GetWaterFlows\(WaterObject, ref Vector3\[\], ref Vector3\[\]\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterFlows\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.GetWaterHeightsFlowsNormals\(WaterObject, ref Vector3\[\], ref float\[\], ref Vector3\[\], ref Vector3\[\], bool, bool, bool\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeightsFlowsNormals\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_System\\_Single\\_UnityEngine\\_Vector3\\_UnityEngine\\_Vector3\\_System\\_Boolean\\_System\\_Boolean\\_System\\_Boolean\\_](#)).

[WaterDataProvider.GetWaterHeightSingle\(WaterObject, Vector3\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeightSingle\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.PointInWater\(WaterObject, Vector3\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_PointInWater\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_](#)).

[WaterDataProvider.GetWaterHeight\(WaterObject, Vector3\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeight\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_](#)).

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterData](#) ([NWH.DWP2.WaterData.html](#))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class RaycastWaterDataProvider : WaterDataProvider
```

# Fields

## **`_flow`**

### Declaration

```
protected Vector3 _flow
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## **`_hit`**

### Declaration

```
protected RaycastHit _hit
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/RaycastHit.html">RaycastHit</a> ( <a href="https://docs.unity3d.com/ScriptReference/RaycastHit.html">https://docs.unity3d.com/ScriptReference/RaycastHit.html</a> ).	

## **`_layerMask`**

### Declaration

```
protected LayerMask _layerMask
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/LayerMask.html">LayerMask</a> ( <a href="https://docs.unity3d.com/ScriptReference/LayerMask.html">https://docs.unity3d.com/ScriptReference/LayerMask.html</a> ).	

## **`_mesh`**

### Declaration

```
protected Mesh _mesh
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ),	

## **\_normals**

### Declaration

```
protected Vector3[] _normals
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ),[]	

## **\_prevDataSize**

### Declaration

```
protected int _prevDataSize
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ),	

## **\_queryParameters**

### Declaration

```
protected QueryParameters _queryParameters
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/QueryParameters.html">QueryParameters</a> ( <a href="https://docs.unity3d.com/ScriptReference/QueryParameters.html">https://docs.unity3d.com/ScriptReference/QueryParameters.html</a> ),	

## **\_ray**

### Declaration

```
protected Ray _ray
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Ray.html">Ray</a>	

## **\_rayDirection**

### Declaration

```
protected Vector3 _rayDirection
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a>	

## **\_rayStartOffset**

### Declaration

```
protected Vector3 _rayStartOffset
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a>	

## **\_raycastCommands**

### Declaration

```
protected NativeArray<RaycastCommand> _raycastCommands
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Unity.Collections.NativeArray_1.html">NativeArray</a> < <a href="https://docs.unity3d.com/ScriptReference/RaycastCommand.html">RaycastCommand</a> >	

## **\_raycastHits**

## Declaration

```
protected NativeArray<RaycastHit> _raycastHits
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Unity.Collections.NativeArray_1.html">NativeArray</a> (<a href="https://docs.unity3d.com/ScriptReference/Unity.Collections.NativeArray_1.html">https://docs.unity3d.com/ScriptReference/Unity.Collections.NativeArray_1.html</a>)< <a href="https://docs.unity3d.com/ScriptReference/RaycastHit.html">RaycastHit</a> (<a href="https://docs.unity3d.com/ScriptReference/RaycastHit.html">https://docs.unity3d.com/ScriptReference/RaycastHit.html</a>)>	

## **\_raycastJobHandle**

### Declaration

```
protected JobHandle _raycastJobHandle
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Unity.Jobs.JobHandle.html">JobHandle</a> (<a href="https://docs.unity3d.com/ScriptReference/Unity.Jobs.JobHandle.html">https://docs.unity3d.com/ScriptReference/Unity.Jobs.JobHandle.html</a>).	

## **\_tmp**

### Declaration

```
protected Vector3 _tmp
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> (<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a>).	

## **\_tmpCommand**

### Declaration

```
protected RaycastCommand _tmpCommand
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/RaycastCommand.html">RaycastCommand</a> (<a href="https://docs.unity3d.com/ScriptReference/RaycastCommand.html">https://docs.unity3d.com/ScriptReference/RaycastCommand.html</a>).	

## **\_upVector**

### Declaration

```
protected Vector3 _upVector
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## **\_uv4**

### Declaration

```
protected Vector2 _uv4
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector2.html">Vector2</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector2.html">https://docs.unity3d.com/ScriptReference/Vector2.html</a> ).	

## **\_vertDir**

### Declaration

```
protected Vector3 _vertDir
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## **\_vertIndex**

### Declaration

```
protected int _vertIndex
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## **\_zeroVector**

### Declaration

```
protected Vector3 _zeroVector
```

### Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## **commandsPerJob**

Number of raycast commands to process per job batch. Higher values may improve performance on systems with more CPU cores.

### Declaration

```
[Tooltip("Minimum number of RaycastCommands per job.")]  
public int commandsPerJob
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## **objectLayer**

Layer that floating objects are on. Used to prevent physics collisions between water and objects.

### Declaration

```
[Tooltip(" Layer the water object(s) are on. Required to be able to disable physics collisions between water and object.")]  
public int objectLayer
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## **raycastDistance**

Maximum distance raycasts can travel in each direction. Raycasts extend this distance above and below each point. Lower values improve performance but may miss water surfaces that are far from the object.

## Declaration

```
[Tooltip(" Raycasts will start at this distance above the point and extend this distance below the point. This means\r\n that if the water surface is raycastDistance below or above the point, it will not be detected.\r\n Using lower value will slightly improve performance of Raycasts.")]\npublic float raycastDistance
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## waterLayer

Layer that water surface colliders are on. Used to filter raycasts and prevent physics collisions.

## Declaration

```
[Tooltip(" Layer the water is on. Required to be able to disable physics collisions between water and object.")]\npublic int waterLayer
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## Methods

### Awake()

#### Declaration

```
public override void Awake()
```

#### Overrides

[WaterDataProvider.Awake\(\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_Awake](#))

### Deallocate()

Deallocates native arrays used for raycasting. Called automatically on disable or destroy.

## Declaration

```
public virtual void Deallocate()
```

## GetWaterHeights(WaterObject, ref Vector3[], ref float[])

Returns water height at each given point. Override this method to provide water height data from your water system.

## Declaration

```
public override void GetWaterHeights(WaterObject waterObject, ref Vector3[] points, ref float[] waterHeights)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ) []	<i>points</i>	Position array in world coordinates.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ) []	<i>waterHeights</i>	Water height array in world coordinates. Corresponds to positions.

## Overrides

[WaterDataProvider.GetWaterHeights\(WaterObject, ref Vector3\[\], ref float\[\]\)](#).

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterHeights\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_System\\_Single\\_](#)).

## GetWaterNormals(WaterObject, ref Vector3[], ref Vector3[])

Returns water surface normals at each given point. Override this method to provide water normal data from your water system.

## Declaration

```
public override void GetWaterNormals(WaterObject waterObject, ref Vector3[] points, ref Vector3[] waterNormals)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>points</i>	Position array in world coordinates.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>waterNormals</i>	Water surface normal array in world coordinates. Corresponds to positions.

## Overrides

[WaterDataProvider.GetWaterNormals\(WaterObject, ref Vector3\[\], ref Vector3\[\]\)](#)  
([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_GetWaterNormals\\_NWH\\_DWP2\\_WaterObjects\\_WaterObject\\_UnityEngine\\_Vector3\\_UnityEngine\\_Vector3\\_](#)).

## OnDestroy()

### Declaration

```
public virtual void OnDestroy()
```

## OnDisable()

### Declaration

```
public virtual void OnDisable()
```

## SupportsWaterFlowQueries()

Does this water system support water velocity queries?

### Declaration

```
public override bool SupportsWaterFlowQueries()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

## Overrides

[WaterDataProvider.SupportsWaterFlowQueries\(\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_SupportsWaterFlowQueries](#)).

## SupportsWaterHeightQueries()

Does this water system support water height queries?

### Declaration

```
public override bool SupportsWaterHeightQueries()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

## Overrides

[WaterDataProvider.SupportsWaterHeightQueries\(\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_SupportsWaterHeightQueries](#)).

## SupportsWaterNormalQueries()

Does this water system support water normal queries?

### Declaration

```
public override bool SupportsWaterNormalQueries()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

## Overrides

[WaterDataProvider.SupportsWaterNormalQueries\(\)](#)

([NWH.DWP2.WaterData.WaterDataProvider.html#NWH\\_DWP2\\_WaterData\\_WaterDataProvider\\_SupportsWaterNormalQueries](#)).

# Class WaterDataProvider

Base class for providing water surface data to WaterObjects. Implementations provide water height, flow velocity, and surface normal information. Uses a trigger collider to automatically detect and register WaterObjects that enter the water. Inherit from this class to create adapters for different water systems.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ WaterDataProvider
  - ↳ [FlatWaterDataProvider](NWH.DWP2.WaterData.FlatWaterDataProvider.html) (<NWH.DWP2.WaterData.FlatWaterDataProvider.html>).
  - ↳ [RaycastWaterDataProvider](NWH.DWP2.WaterData.RaycastWaterDataProvider.html) (<NWH.DWP2.WaterData.RaycastWaterDataProvider.html>).

**Namespace:** [NWH \(NWH.html\).DWP2 \(NWH.DWP2.html\).WaterData \(NWH.DWP2.WaterData.html\)](NWH(NWH.html).DWP2(NWH.DWP2.html).WaterData(NWH.DWP2.WaterData.html))

**Assembly:** NWH.DWP2.dll

## Syntax

```
public abstract class WaterDataProvider : MonoBehaviour
```

## Fields

### **singleHeightArray**

#### Declaration

```
protected float[] _singleHeightArray
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ), []	

### **singlePointArray**

#### Declaration

```
protected Vector3[] _singlePointArray
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> (https://docs.unity3d.com/ScriptReference/Vector3.html)[]	

## **\_triggerCollider**

### Declaration

```
protected Collider _triggerCollider
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Collider.html">Collider</a> (https://docs.unity3d.com/ScriptReference/Collider.html).	

## Methods

### **Awake()**

#### Declaration

```
public virtual void Awake()
```

### **GetWaterFlows(WaterObject, ref Vector3[], ref Vector3[])**

Returns water flow velocity at each given point. Override this method to provide water flow data from your water system. Flow should be in world space and relative to the world, not the WaterObject.

#### Declaration

```
public virtual void GetWaterFlows(WaterObject waterObject, ref Vector3[] points, ref Vector3[] waterFlows)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ). []	<i>points</i>	Position array in world coordinates.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ). []	<i>waterFlows</i>	Water flow velocity array in world coordinates. Corresponds to positions.

## GetWaterHeight(WaterObject, Vector3)

Returns water height at the given world position.

### Declaration

```
public float GetWaterHeight(WaterObject waterObject, Vector3 worldPoint)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject making the query.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>worldPoint</i>	Position in world coordinates.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Water surface height at the given point.

## GetWaterHeightSingle(WaterObject, Vector3)

Returns water height at a single point. Less efficient than batch queries but useful for one-off checks.

### Declaration

```
public virtual float GetWaterHeightSingle(WaterObject waterObject, Vector3 point)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>point</i>	Position in world coordinates.

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Water height at the given point.

## GetWaterHeights(WaterObject, ref Vector3[], ref float[])

Returns water height at each given point. Override this method to provide water height data from your water system.

### Declaration

```
public virtual void GetWaterHeights(WaterObject waterObject, ref Vector3[] points, ref float [] waterHeights)
```

### Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ), []	<i>points</i>	Position array in world coordinates.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ), []	<i>waterHeights</i>	Water height array in world coordinates. Corresponds to positions.

## GetWaterHeightsFlowsNormals(WaterObject, ref Vector3[], ref float[], ref Vector3[], ref Vector3[], bool, bool, bool)

Queries water data based on enabled flags. Calls the appropriate getter methods based on which data types are requested.

### Declaration

```
public void GetWaterHeightsFlowsNormals(WaterObject waterObject, ref Vector3[] points, ref float[] waterHeights, ref Vector3[] waterFlows, ref Vector3[] waterNormals, bool useWaterHeight, bool useWaterNormals, bool useWaterFlow)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ),	<i>waterObject</i>	WaterObject requesting the data.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ), []	<i>points</i>	Position array in world coordinates.
<a href="#">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ), []	<i>waterHeights</i>	Output water heights array.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ), []	<i>waterFlows</i>	Output water flows array.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ), []	<i>waterNormals</i>	Output water normals array.
<a href="#">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ),	<i>useWaterHeight</i>	Should water heights be queried.
<a href="#">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ),	<i>useWaterNormals</i>	Should water normals be queried.
<a href="#">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ),	<i>useWaterFlow</i>	Should water flows be queried.

## GetWaterNormals(WaterObject, ref Vector3[], ref Vector3[])

Returns water surface normals at each given point. Override this method to provide water normal data from your water system.

### Declaration

```
public virtual void GetWaterNormals(WaterObject waterObject, ref Vector3[] points, ref Vector3[] waterNormals)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject requesting the data.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>points</i>	Position array in world coordinates.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>waterNormals</i>	Water surface normal array in world coordinates. Corresponds to positions.

## PointInWater(WaterObject, Vector3)

Checks if a point is underwater. Accounts for wave height when water normals are supported.

### Declaration

```
public bool PointInWater(WaterObject waterObject, Vector3 worldPoint)
```

## Parameters

Type	Name	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	<i>waterObject</i>	WaterObject making the query.
<a href="#">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>worldPoint</i>	Position to check in world coordinates.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if the point is below the water surface.

## SupportsWaterFlowQueries()

Does this water system support water velocity queries?

### Declaration

```
public abstract bool SupportsWaterFlowQueries()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

## SupportsWaterHeightQueries()

Does this water system support water height queries?

### Declaration

```
public abstract bool SupportsWaterHeightQueries()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

## SupportsWaterNormalQueries()

Does this water system support water normal queries?

### Declaration

```
public abstract bool SupportsWaterNormalQueries()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if it does, false if it does not.

# Namespace NWH.DWP2.WaterObjects

## Classes

### **MassFromChildren (NWH.DWP2.WaterObjects.MassFromChildren.html)**

Calculates mass of a Rigidbody from the children that have MassFromVolume script attached.

### **MassFromVolume (NWH.DWP2.WaterObjects.MassFromVolume.html)**

Script to calculate mass from mesh volume and material density. Removes need for guessing mass and ensures that all objects of same density are submerged equally.

### **MeshUtility (NWH.DWP2.WaterObjects.MeshUtility.html)**

Utility class for mesh processing operations used by WaterObject. Handles mesh simplification, convexification, vertex welding, and volume calculations.

### **SerializedMesh (NWH.DWP2.WaterObjects.SerializedMesh.html)**

Serializable representation of a mesh. Used to store simulation mesh data without keeping mesh references in game files.

### **WaterObject (NWH.DWP2.WaterObjects.WaterObject.html)**

Core component for mesh-based buoyancy simulation. Calculates buoyancy and hydrodynamic forces by slicing mesh triangles at the water surface. Requires a MeshFilter with a valid mesh and a Rigidbody to apply forces to. Use WaterObjectWizard for one-click setup or manually configure the simulation mesh.

### **WaterObjectMaterial (NWH.DWP2.WaterObjects.WaterObjectMaterial.html)**

ScriptableObject defining material properties for mass calculation. Contains density value used by MassFromVolume to calculate object mass. Create via Assets > Create > Dynamic Water Physics 2 > Water Object Material.

### **WaterObjectWizard (NWH.DWP2.WaterObjects.WaterObjectWizard.html)**

Configuration for the WaterObject setup wizard. Used by the editor to automate WaterObject component setup.

### **WaterParticleSystem (NWH.DWP2.WaterObjects.WaterParticleSystem.html)**

Generates water spray and splash particles based on WaterObject simulation data. Emits particles at the waterline where triangles intersect the water surface. Particle emission is controlled by object velocity and triangle forces. Requires a ParticleSystem component.

# Class MassFromChildren

Calculates mass of a Rigidbody from the children that have MassFromVolume script attached.

## Inheritance

---

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ MassFromChildren

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(Rigidbody))]  
public class MassFromChildren : MonoBehaviour
```

## Methods

### Calculate()

Calculates the total mass from all child MassFromVolume components and applies it to the Rigidbody. Also updates the VariableCenterOfMass component if present.

### Declaration

```
public void Calculate()
```

# Class MassFromVolume

Script to calculate mass from mesh volume and material density. Removes need for guessing mass and ensures that all objects of same density are submerged equally.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ MassFromVolume

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)),

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(WaterObject))]  
public class MassFromVolume : MonoBehaviour
```

## Fields

### density

Calculated density of the material in kg/m<sup>3</sup>.

#### Declaration

```
public float density
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

### mass

Calculated mass of the object in kg.

#### Declaration

```
public float mass
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## material

Material preset containing density value.

### Declaration

```
public WaterObjectMaterial material
```

## Field Value

Type	Description
<a href="#">WaterObjectMaterial</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObjectMaterial.html</a> ).	

## volume

Calculated volume of the simulation mesh in m<sup>3</sup>.

### Declaration

```
public float volume
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Methods

## CalculateAndApplyFromDensity(float)

Calculates mass from the given density and applies it to the Rigidbody.

### Declaration

```
public float CalculateAndApplyFromDensity(float density)
```

### Parameters

Type	Name	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>density</i>	Material density in kg/m <sup>3</sup> .

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Calculated mass value.

## CalculateAndApplyFromMaterial()

Calculates mass from the assigned material's density and applies it to the Rigidbody.

### Declaration

```
public float CalculateAndApplyFromMaterial()
```

## Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Calculated mass value.

## CalculateSimulationMeshVolume()

Gets volume of the simulation mesh. Scale-sensitive.

### Declaration

```
public void CalculateSimulationMeshVolume()
```

## SetDefaultAsMaterial()

Sets the default WaterObjectMaterial from Resources.

### Declaration

```
public void SetDefaultAsMaterial()
```

# Class MeshUtility

Utility class for mesh processing operations used by WaterObject. Handles mesh simplification, convexification, vertex welding, and volume calculations.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)  
↳ MeshUtility

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)),

**Assembly:** NWH.DWP2.dll

## Syntax

```
public static class MeshUtility
```

## Methods

### GenerateConvexMesh(Mesh)

Creates a convex hull from the input mesh. Useful for partially hollow meshes or open hulls.

#### Declaration

```
public static Mesh GenerateConvexMesh(Mesh mesh)
```

#### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>mesh</i>	Mesh to convexify.

#### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	Convex mesh wrapping the input mesh.

### GenerateMesh(Vector3[], int[])

Generate mesh from vertices and triangles.

#### Declaration

```
public static Mesh GenerateMesh(Vector3[] vertices, int[] triangles)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ),[]	<i>vertices</i>	Array of vertices.
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ),[]	<i>triangles</i>	Array of triangles (indices).

## Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	

## GenerateSimMesh(ref Mesh, ref Mesh, bool, bool, bool, float)

Generates a simulation mesh from the original mesh with optional processing steps. Processes the mesh according to the specified flags and simplification ratio.

## Declaration

```
public static void GenerateSimMesh(ref Mesh originalMesh, ref Mesh simMesh, bool simplifyMesh = false, bool convexifyMesh = false, bool weldColocatedVertices = true, float simplificationRatio = 1)
```

## Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>originalMesh</i>	Source mesh to process.
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>simMesh</i>	Output simulation mesh.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>simplifyMesh</i>	Should the mesh be simplified to reduce triangle count.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>convexifyMesh</i>	Should the mesh be made convex.
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	<i>weldColocatedVertices</i>	Should vertices at the same position be merged.
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>simplificationRatio</i>	Target triangle count as ratio of original (0-1).

## SignedVolumeOfTriangle(Vector3, Vector3, Vector3)

Calculates the signed volume of a triangle with respect to the origin. Used for mesh volume calculations.

### Declaration

```
public static float SignedVolumeOfTriangle(Vector3 p1, Vector3 p2, Vector3 p3)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p1</i>	First vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p2</i>	Second vertex.
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>p3</i>	Third vertex.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Signed volume of the triangle.

## VolumeOfMesh(Mesh, Transform)

Calculates the volume of a mesh in world space. Takes into account the transform's scale, position and rotation.

### Declaration

```
public static float VolumeOfMesh(Mesh mesh, Transform transform)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>mesh</i>	Mesh to calculate volume for.
<a href="https://docs.unity3d.com/ScriptReference/Transform.html">Transform</a> ( <a href="https://docs.unity3d.com/ScriptReference/Transform.html">https://docs.unity3d.com/ScriptReference/Transform.html</a> ).	<i>transform</i>	Transform containing scale information.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Volume of the mesh in cubic meters.

## WeldVertices(ref Mesh, float)

Merges vertices that are closer than the specified distance threshold. Improves performance by reducing vertex count and removing duplicates.

## Declaration

```
public static void WeldVertices(ref Mesh aMesh, float aMaxDelta = 0.001)
```

## Parameters

Type	Name	Description
<u>Mesh</u> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	<i>aMesh</i>	Mesh to process.
<u>float</u> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	<i>aMaxDelta</i>	Maximum distance between vertices to be considered duplicates.

# Class SerializedMesh

Serializable representation of a mesh. Used to store simulation mesh data without keeping mesh references in game files.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>)  
↳ SerializedMesh

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)),

**Assembly:** NWH.DWP2.dll

## Syntax

```
[Serializable]  
public class SerializedMesh
```

## Fields

### triangles

Triangle indices of the mesh.

#### Declaration

```
[SerializeField]  
public int[] triangles
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).[]	

### vertices

Vertex positions of the mesh.

#### Declaration

```
[SerializeField]  
public Vector3[] vertices
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> ,[]	

## Methods

### Deserialize()

Deserializes the stored data back into a Mesh object.

#### Declaration

```
public Mesh Deserialize()
```

#### Returns

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh (https://docs.unity3d.com/ScriptReference/Mesh.html)</a>	Reconstructed mesh or null if data is invalid.

### Serialize(Mesh)

Serializes a mesh into vertex and triangle arrays.

#### Declaration

```
public void Serialize(Mesh mesh)
```

#### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh (https://docs.unity3d.com/ScriptReference/Mesh.html)</a>	<i>mesh</i>	Mesh to serialize.

# Class WaterObject

Core component for mesh-based buoyancy simulation. Calculates buoyancy and hydrodynamic forces by slicing mesh triangles at the water surface. Requires a MeshFilter with a valid mesh and a Rigidbody to apply forces to. Use WaterObjectWizard for one-click setup or manually configure the simulation mesh.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).  
↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).  
↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).  
↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).  
↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).  
↳ WaterObject

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(MeshFilter))]  
[DisallowMultipleComponent]  
public class WaterObject : MonoBehaviour
```

## Fields

### CurrentWaterDataProvider

Currently active WaterDataProvider.

#### Declaration

```
[NonSerialized]  
[Tooltip("Currently active WaterDataProvider.")]  
public WaterDataProvider CurrentWaterDataProvider
```

#### Field Value

Type	Description
<a href="#">WaterDataProvider</a> ( <a href="#">NWH.DWP2.WaterData.WaterDataProvider.html</a> ).	

### LocalVertices

Vertices used for simulation, in local space.

## Declaration

```
[NonSerialized]
[Tooltip("Vertices used for simulation, in local space.")]
public Vector3[] LocalVertices
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> []	

## ResultAreas

Result triangle areas.

## Declaration

```
[NonSerialized]
[Tooltip("Result triangle areas.")]
public float[] ResultAreas
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a> []	

## ResultCenters

Result triangle centers in world coordinates.

## Declaration

```
[NonSerialized]
[Tooltip("Result triangle centers in world coordinates.")]
public Vector3[] ResultCenters
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> []	

## ResultDistances

Result distances to water surface.

## Declaration

```
[NonSerialized]
[Tooltip("Result distances to water surface.")]
public float[] ResultDistances
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ),[]	

## ResultForce

Total result force.

## Declaration

```
[NonSerialized]
[Tooltip("Total result force.")]
public Vector3 ResultForce
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## ResultForces

Per-triangle result forces.

## Declaration

```
[NonSerialized]
[Tooltip("Per-triangle result forces.")]
public Vector3[] ResultForces
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ),[]	

## ResultNormals

Result triangle normals. Not equal to the mesh normals.

## Declaration

```
[NonSerialized]
[Tooltip("Result triangle normals. Not equal to the mesh normals.")]
public Vector3[] ResultNormals
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> ,[]	

## ResultP0s

Result sliced triangle vertices.

## Declaration

```
[NonSerialized]
[Tooltip("Result sliced triangle vertices.")]
public Vector3[] ResultP0s
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> ,[]	

## ResultStates

Result triangle states. 0 - Triangle is underwater 1 - Triangle is partially underwater 2 - Triangle is above water 3 - Triangle's object is disabled 4 - Triangle's object is deleted

## Declaration

```
[NonSerialized]
[Tooltip("Result triangle states.\r\n0 - Triangle is underwater\r\n1 - Triangle is partially underwater\r\n2 - Triangle is above water\r\n3 - Triangle's object is disabled\r\n4 - Triangle's object is deleted")]
public int[] ResultStates
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a> ,[]	

## ResultTorque

Result total torque acting on the Rigidbody.

## Declaration

```
[NonSerialized]
[Tooltip("Result total torque acting on the Rigidbody.")]
public Vector3 ResultTorque
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## ResultVelocities

Result velocities at triangle centers.

## Declaration

```
[NonSerialized]
[Tooltip("Result velocities at triangle centers.")]
public Vector3[] ResultVelocities
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> )[ <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">]</a>	

## RigidbodyAngVel

Angular velocity of the target Rigidbody.

## Declaration

```
[NonSerialized]
[Tooltip("Angular velocity of the target Rigidbody.")]
public Vector3 RigidbodyAngVel
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	

## RigidbodyCoM

Center-of-mass of the target Rigidbody.

## Declaration

```
[NonSerialized]
[Tooltip("Center of mass of the target Rigidbody.")]
public Vector3 RigidbodyCoM
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## RigidbodyLinearVel

(Linear) velocity of the target Rigidbody.

## Declaration

```
[NonSerialized]
[Tooltip("(Linear) velocity of the target Rigidbody.")]
public Vector3 RigidbodyLinearVel
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## TriIndices

Triangles indices of the simulation mesh.

## Declaration

```
[NonSerialized]
[Tooltip("Triangles indices of the simulation mesh.")]
public int[] TriIndices
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a> []	

## WaterFlows

Water flows of the current water data provider. Default is used if no water data provider is present.

## Declaration

```
[NonSerialized]
[Tooltip("Water flows of the current water data provider. Default is used if no water data p
rovider is present.")]
public Vector3[] WaterFlows
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> (https://docs.unity3d.com/ScriptReference/Vector3.html)[]	

## WaterHeights

Water surface heights of the current water data provider. Default is used if no water data provider is present.

## Declaration

```
[NonSerialized]
[Tooltip("Water surface heights of the current water data provider. Default is used if no wa
ter data provider is present.")]
public float[] WaterHeights
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> (https://learn.microsoft.com/dotnet/api/system.single)[]	

## WaterNormals

Water normals of the current water data provider. Default is used if no water data provider is present.

## Declaration

```
[NonSerialized]
[Tooltip("Water normals of the current water data provider. Default is used if no water data
provider is present.")]
public Vector3[] WaterNormals
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> (https://docs.unity3d.com/ScriptReference/Vector3.html)[]	

## WorldVertices

Simulation vertices converted to world coordinates.

## Declaration

```
[NonSerialized]
[Tooltip("Simulation vertices converted to world coordinates.")]
public Vector3[] WorldVertices
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a> ,[]	

## buoyantForceCoefficient

Coefficient by which the buoyancy forces are multiplied.

## Declaration

```
[Tooltip("Coefficient by which the the buoyancy forces are multiplied.")]
public float buoyantForceCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a> .	

## calculateWaterFlows

Should the water flows be queried and calculated?

## Declaration

```
[Tooltip("Should the water flows be queried and calculated?")]
public bool calculateWaterFlows
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a> .	

## calculateWaterHeights

Should the water heights be queried and calculated?

## Declaration

```
[Tooltip("Should the water heights be queried and calculated?")]  
public bool calculateWaterHeights
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## calculateWaterNormals

Should the water normals be queried and calculated?

## Declaration

```
[Tooltip("Should the water normals be queried and calculated?")]  
public bool calculateWaterNormals
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## convexifyMesh

Should the simulation mesh be made convex? Can be useful for half-open hulls and otherwise partially hollow meshes.

## Declaration

```
[Tooltip("Should the simulation mesh be made convex?\r\nCan be useful for half-open hulls and otherwise partially hollow meshes.")]  
public bool convexifyMesh
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## defaultWaterFlow

World water flow to be used when there is no WaterDataProvider present and calculateWaterFlows is enabled.

## Declaration

```
[Tooltip("World water flow to be used when there is no WaterDataProvider present and calculateWaterFlows is enabled.")]  
public Vector3 defaultWaterFlow
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## defaultWaterHeight

World water height to be used when there is no WaterDataProvider present.

## Declaration

```
[Tooltip("World water height to be used when there is no WaterDataProvider present.")]  
public float defaultWaterHeight
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## defaultWaterNormal

World water normal to be used when there is no WaterDataProvider present and calculateWaterNormals is enabled.

## Declaration

```
[Tooltip("World water normal to be used when there is no WaterDataProvider present and calculateWaterNormals is enabled.")]  
public Vector3 defaultWaterNormal
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3 (https://docs.unity3d.com/ScriptReference/Vector3.html)</a>	

## finalForceCoefficient

Coefficient by which the result force will get multiplied.

## Declaration

```
[Tooltip("Coefficient by which the result force will get multiplied.")]  
public float finalForceCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## finalTorqueCoefficient

The coefficient by which the torque force will get multiplied.

## Declaration

```
[Tooltip("Coefficient by which the torque force will get multiplied.")]  
public float finalTorqueCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## fluidDensity

Density of the fluid the object is in.

## Declaration

```
[Tooltip("Density of the fluid the object is in.")]  
public float fluidDensity
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## hydrodynamicForceCoefficient

Coefficient by which the hydrodynamic forces are multiplied.

## Declaration

```
[Tooltip("Coefficient by which the hydrodynamic forces are multiplied..")]  
public float hydrodynamicForceCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## instanceID

Cached instance ID of the GameObject.

### Declaration

```
[NonSerialized]
[Tooltip("Cached instance ID of the GameObject.")]
public int instanceID
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## originalMesh

Original mesh of the object, non-simplified and non-convexified.

### Declaration

```
[SerializeField]
[Tooltip("Original mesh of the object, non-simplified and non-convexified.")]
public Mesh originalMesh
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	

## serializedSimulationMesh

Serialized version of the simulation mesh, used to prevent having to store the mesh in game files.

### Declaration

```
[SerializeField]
[Tooltip("Serialized version of the simulation mesh, used to prevent having to store the mesh in game files.")]
public SerializedMesh serializedSimulationMesh
```

## Field Value

Type	Description
<a href="#">SerializedMesh (NWH.DWP2.WaterObjects.SerializedMesh.html)</a>	

## simplifyMesh

Should the simulation mesh be simplified / decimated?

### Declaration

```
[Tooltip("Should the simulation mesh be simplified / decimated?")]  
public bool simplifyMesh
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool (https://learn.microsoft.com/dotnet/api/system.boolean)</a>	

## skinDragCoefficient

The coefficient by which the skin drag force is multiplied. Skin drag is a force caused by water flowing over a surface.

### Declaration

```
[Tooltip("Coefficient by which the skin drag force is multiplied.\r\nSkin drag is a force ca  
used by water flowing over a surface.")]  
public float skinDragCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## slamForceCoefficient

Coefficient applied to forces when a face of the object is entering the water.

### Declaration

```
[Tooltip("Coefficient applied to forces when a face of the object is entering the water.")]  
public float slamForceCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## submergedVolume

Current submerged volume in cubic meters. Updated each physics step based on how much of the mesh is underwater.

### Declaration

```
[Tooltip("Resulting volume of buoyancy calculation.")]  
public float submergedVolume
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## suctionForceCoefficient

Coefficient applied to forces when a face of the object is leaving the water.

### Declaration

```
[Tooltip("Coefficient applied to forces when a face of the object is leaving the water.")]  
public float suctionForceCoefficient
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## targetRigidbody

Rigidbody that the forces will be applied to.

### Declaration

```
[Tooltip("Rigidbody that the forces will be applied to.")]  
public Rigidbody targetRigidbody
```

## Field Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Rigidbody.html">Rigidbody (https://docs.unity3d.com/ScriptReference/Rigidbody.html)</a>	

## targetTriangleCount

Target triangle count for the simulation mesh. The original mesh will be decimated to this number of triangles if "SimplifyMesh" is enabled.

### Declaration

```
[FormerlySerializedAs("targetTris")]  
[Range(8, 256)]  
[Tooltip("Target triangle count for the simulation mesh.\r\nOriginal mesh will be decimated  
to this number of triangles if 'SimplifyMesh' is enabled.\r\nOtherwise does nothing.")]  
public int targetTriangleCount
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## triangleCount

Total number of triangles (not indices) on the simulation mesh.

### Declaration

```
[Tooltip("Total number of triangles (not indices) on the simulation mesh.")]  
public int triangleCount
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int (https://learn.microsoft.com/dotnet/api/system.int32)</a>	

## velocityDotPower

Determines to which power the dot product between velocity and triangle normal will be raised. Higher values will result in lower hydrodynamic forces for situations in which the triangle is nearly parallel to the water velocity.

### Declaration

```
[Range(0.01, 2)]  
[Tooltip("Determines to which power the dot product between velocity and triangle normal will  
be raised.\r\nHigher values will result in lower hydrodynamic forces for situations in which  
the triangle is nearly parallel to the\r\nwater velocity.")]  
public float velocityDotPower
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float (https://learn.microsoft.com/dotnet/api/system.single)</a>	

## vertexCount

Total number of vertices on the simulation mesh.

### Declaration

```
[Tooltip("Total number of vertices on the simulation mesh.")]  
public int vertexCount
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## weldColocatedVertices

If true, the vertices with the same position will be welded. Improves performance and is highly recommended.

### Declaration

```
[Tooltip("    If true vertices with same position will be welded.\r\n    Improves performance and is highly recommended.")]  
public bool weldColocatedVertices
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## Properties

### PreviewEnabled

Returns true if the simulation mesh is currently being previewed in the scene view.

### Declaration

```
public bool PreviewEnabled { get; }
```

### Property Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## SimulationMesh

Gets the simulation mesh, deserializing from serialized data if necessary.

### Declaration

```
public Mesh SimulationMesh { get; }
```

### Property Value

Type	Description
<a href="https://docs.unity3d.com/ScriptReference/Mesh.html">Mesh</a> ( <a href="https://docs.unity3d.com/ScriptReference/Mesh.html">https://docs.unity3d.com/ScriptReference/Mesh.html</a> ).	

## Methods

### GenerateSimMesh()

Generates or regenerates the simulation mesh based on current settings. Applies simplification, convexification, and vertex welding as configured. Must be called after changing mesh processing settings.

### Declaration

```
public void GenerateSimMesh()
```

### GetWaterHeightSingle(Vector3)

Returns water height at a single point using the current WaterDataProvider. Falls back to defaultWaterHeight if no provider is active.

### Declaration

```
public float GetWaterHeightSingle(Vector3 point)
```

### Parameters

Type	Name	Description
<a href="https://docs.unity3d.com/ScriptReference/Vector3.html">Vector3</a> ( <a href="https://docs.unity3d.com/ScriptReference/Vector3.html">https://docs.unity3d.com/ScriptReference/Vector3.html</a> ).	<i>point</i>	Position in world coordinates.

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	Water height at the given point.

## IsTouchingWater()

Checks if any part of the object is currently in contact with water. Returns true if at least one triangle is fully or partially submerged. Cache the result if calling frequently.

### Declaration

```
public bool IsTouchingWater()
```

### Returns

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	True if object is touching water.

## OnEnterWaterDataProvider(WaterDataProvider)

Called when the WaterObject enters a WaterDataProvider's trigger volume. Registers the provider for water data queries.

### Declaration

```
public void OnEnterWaterDataProvider(WaterDataProvider wdp)
```

### Parameters

Type	Name	Description
<a href="#">WaterDataProvider</a> ( <a href="#">NWH.DWP2.WaterData.WaterDataProvider.html</a> )	<i>wdp</i>	WaterDataProvider that was entered.

## OnExitWaterDataProvider(WaterDataProvider)

Called when the WaterObject exits a WaterDataProvider's trigger volume. Unregisters the provider and resets to default water data if no providers remain.

### Declaration

```
public void OnExitWaterDataProvider(WaterDataProvider wdp)
```

### Parameters

Type	Name	Description
<a href="#">WaterDataProvider</a> ( <a href="#">NWH.DWP2.WaterData.WaterDataProvider.html</a> )	<i>wdp</i>	WaterDataProvider that was exited.

## StartSimMeshPreview()

Enables visualization of the simulation mesh in the scene view. Temporarily replaces the MeshFilter's mesh with the simulation mesh.

### Declaration

```
public void StartSimMeshPreview()
```

## StopSimMeshPreview()

Disables simulation mesh visualization in the scene view. Restores the original mesh to the MeshFilter.

### Declaration

```
public void StopSimMeshPreview()
```

## See Also

[WaterObjectWizard \(NWH.DWP2.WaterObjects.WaterObjectWizard.html\)](#).

[WaterDataProvider \(NWH.DWP2.WaterData.WaterDataProvider.html\)](#).

[WaterObjectMaterial\(\)](#)

[AdvancedShipController \(NWH.DWP2.ShipController.AdvancedShipController.html\)](#).

# Class WaterObjectMaterial

ScriptableObject defining material properties for mass calculation. Contains density value used by MassFromVolume to calculate object mass. Create via Assets > Create > Dynamic Water Physics 2 > Water Object Material.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [ScriptableObject](https://docs.unity3d.com/ScriptReference/ScriptableObject.html) (<https://docs.unity3d.com/ScriptReference/ScriptableObject.html>).
- ↳ WaterObjectMaterial

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[CreateAssetMenu(fileName = "WaterObjectMaterial", menuName = "Dynamic Water Physics 2/Water Object Material", order = 0)]  
public class WaterObjectMaterial : ScriptableObject
```

## Fields

### density

Material density in kg/m<sup>3</sup>. Used with mesh volume to calculate realistic object mass. Examples: Wood ~600, Ice ~920, Aluminum ~2700, Steel ~7850.

### Declaration

```
public float density
```

### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

# Class WaterObjectWizard

Configuration for the WaterObject setup wizard. Used by the editor to automate WaterObject component setup.

## Inheritance

- ↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).
- ↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).
- ↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).
- ↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).
- ↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).
- ↳ WaterObjectWizard

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
public class WaterObjectWizard : MonoBehaviour
```

## Fields

### addWaterParticleSystem

Should the wizard add a WaterParticleSystem component for splash effects.

#### Declaration

```
public bool addWaterParticleSystem
```

#### Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

# Class WaterParticleSystem

Generates water spray and splash particles based on WaterObject simulation data. Emits particles at the waterline where triangles intersect the water surface. Particle emission is controlled by object velocity and triangle forces. Requires a ParticleSystem component.

## Inheritance

↳ [object](https://learn.microsoft.com/dotnet/api/system.object) (<https://learn.microsoft.com/dotnet/api/system.object>).  
↳ [Object](https://docs.unity3d.com/ScriptReference/Object.html) (<https://docs.unity3d.com/ScriptReference/Object.html>).  
↳ [Component](https://docs.unity3d.com/ScriptReference/Component.html) (<https://docs.unity3d.com/ScriptReference/Component.html>).  
↳ [Behaviour](https://docs.unity3d.com/ScriptReference/Behaviour.html) (<https://docs.unity3d.com/ScriptReference/Behaviour.html>).  
↳ [MonoBehaviour](https://docs.unity3d.com/ScriptReference/MonoBehaviour.html) (<https://docs.unity3d.com/ScriptReference/MonoBehaviour.html>).  
↳ WaterParticleSystem

**Namespace:** [NWH](#) ([NWH.html](#)), [DWP2](#) ([NWH.DWP2.html](#)), [WaterObjects](#) ([NWH.DWP2.WaterObjects.html](#)).

**Assembly:** NWH.DWP2.dll

## Syntax

```
[RequireComponent(typeof(ParticleSystem))]  
public class WaterParticleSystem : MonoBehaviour
```

## Fields

### ReferenceWaterObject

WaterObject to read simulation data from. Will auto-detect from parent if not assigned.

#### Declaration

```
public WaterObject ReferenceWaterObject
```

#### Field Value

Type	Description
<a href="#">WaterObject</a> ( <a href="#">NWH.DWP2.WaterObjects.WaterObject.html</a> ).	

### emit

Should the particle system emit?

#### Declaration

```
[Tooltip("Should the particle system emit?")]  
public bool emit
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.boolean">bool</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.boolean">https://learn.microsoft.com/dotnet/api/system.boolean</a> ).	

## emitPerCycle

How many particles should be emitted each 'emitTimeInterval' seconds.

### Declaration

```
[Tooltip("How many particles should be emitted each 'emitTimeInterval' seconds.")]  
[Range(0, 20)]  
public int emitPerCycle
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## emitTimeInterval

Determines how often the particles will be emitted.

### Declaration

```
[Tooltip("Determines how often the particles will be emitted.")]  
[Range(0, 0.1)]  
public float emitTimeInterval
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## initialAlphaModifier

Multiplies initial alpha by this value. Alpha cannot be higher than maxInitialAlpha.

### Declaration

```
[Tooltip("Multiplies initial alpha by this value. Alpha cannot be higher than maxInitialAlpha.")]  
[Range(0, 10)]  
public float initialAlphaModifier
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## initialVelocityModifier

Determines how much velocity of the object will affect initial particle speed.

### Declaration

```
[Tooltip("Determines how much velocity of the object will affect initial particle speed.")]  
[Range(0, 5)]  
public float initialVelocityModifier
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## maxInitialAlpha

Limit initial alpha to this value.

### Declaration

```
[Tooltip("Limit initial alpha to this value.")]  
[Range(0, 1)]  
public float maxInitialAlpha
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## positionExtrapolationFrames

Number of frames ahead to predict particle emission position. Higher values spawn particles ahead of the object for better visual continuity.

### Declaration

```
[Tooltip("Script will try to predict where the object will be in the next n frames.")]  
public int positionExtrapolationFrames
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## renderQueue

Render queue of the particle material.

### Declaration

```
[Tooltip("Render queue of the particle material.")]  
public int renderQueue
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.int32">int</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.int32">https://learn.microsoft.com/dotnet/api/system.int32</a> ).	

## sleepThresholdVelocity

Velocity object has to have to emit particles.

### Declaration

```
[FormerlySerializedAs("sleepTresholdVelocity")]  
[Tooltip("Velocity object has to have to emit particles.")]  
[Range(0.1, 5)]  
public float sleepThresholdVelocity
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## startSize

Initial size of the particle.

### Declaration

```
[Tooltip("Initial size of the particle.")]  
[Range(0, 64)]  
public float startSize
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	

## surfaceElevation

Elevation above water at which the particles will spawn. Used to avoid clipping.

### Declaration

```
[Tooltip("Elevation above water at which the particles will spawn. Used to avoid clipping.")]  
[Range(0, 0.1)]  
public float surfaceElevation
```

## Field Value

Type	Description
<a href="https://learn.microsoft.com/dotnet/api/system.single">float</a> ( <a href="https://learn.microsoft.com/dotnet/api/system.single">https://learn.microsoft.com/dotnet/api/system.single</a> ).	